

Alaris inVoice

Release notes

version 3.6.0

Copyright © 2005 - 2025 Alarislabs Pte Ltd.
All rights reserved.

The information contained in this document is the property of Alarislabs Pte Ltd. No part of this publication may be reproduced or copied in any form or by any means - graphic, electronic or mechanical including photocopying, recording, taping, or any other information storage and retrieval System - without written consent of Alarislabs Pte Ltd. No third party, organization or individual, is authorized to grant such permission.

1 Enhancements

General

- The logic of hotkeys has been implemented, which can be used to quickly navigate through the interface:
 - a. The Ctrl+Alt+T key combination restores the previously closed tabs of the System.
 - b. The Ctrl+Alt+` combination works similarly to Ctrl+Alt (in Windows): it opens a window containing lists of open interfaces for quick navigation.
 - c. Ctrl+Alt+Q: opens a quick menu in the lower panel of the System with the possibility to enter or manually select an interface to open. A corresponding keyboard shortcut is added next to the *Start* menu. For interfaces that have the same name in Alaris inVoice and Alaris SMS Platform (for example, *Limitation rules*), a color tip has been added on the right side, corresponding to the colors of the interfaces (blue for Alaris inVoice, green for Alaris SMS Platform).
 - d. If the cursor is placed in a field on the *Add/Edit* panel, the *Delete*, *Clone*, *Reset*, *Submit* buttons can be invoked using hotkeys when Ctrl+Alt is pressed. The list of keys is also available when Ctrl+Alt is pressed: D for Delete, C for Clone, R for Reset, S for Submit.
 - e. When Ctrl+Alt is pressed, the icons/names of open interfaces are changed to sequential numbers - pressing the required number (e.g. 2) while Ctrl+Alt is pressed switches to the specified interface.
 - f. The hotkeys Ctrl+Alt+Page Up are used to open the first tab and Ctrl+Alt+Page Down to open the last tab. Additionally, you can use arrows (also in combination with Ctrl+Alt) to move between open and second-level interfaces and subtabs (for example, in the *Carriers* interface).

You can additionally check System shortcuts (Keyboard shortcuts), as well as add custom shortcuts in the list called by Ctrl+Alt+Fn+F1 or Ctrl+Alt+F1, or the *User shortcuts* menu. It should be noted that custom settings are saved at the browser level - you cannot assign a combination that is already used by the System. The changes take effect after restarting the web interface of the System.






- Two-factor authentication has been redesigned: user settings (*Settings/User settings* interface) now contain a separate *Two-factor authentication (2FA)* block with brief instructions on how to enable 2FA. If the user does not have the *Security policy control* role, they will not be able to edit this block - a pop-up window will appear when hovering over the uneditable section. In the new version, the user must additionally have the *User administration* permission to be able to configure 2FA for other users. If 2FA has been enabled by another user, the user cannot disable 2FA.
 - Verification has been added that the parameters of the created task (for example, in the *CDR export tool* interface) do not coincide with previously created tasks. If they do, an error will be displayed if the verification interval is not passed (default: 1 minute). Additionally, a verification is performed to make sure that a task with the same parameters is not among the unfinished tasks (interval between task creation: 6 hours). To change the intervals, contact the Alaris technical support team and report the code BZ71656. Note that the verification does not apply to the *Simulation* interface.
-

- The new System parameter *Forbidden character sequences* (possible values are 0 and 1) has been added to enable improved password creation policy for the main web interface. The default value is 1 (logic enabled). When logic is enabled and a password is changed or assigned, the following verifications will be performed:

1) the password does not contain the user's login name

2) the password is not included in the black list, which is set by default and contains the most compromised passwords (for example, qwerty). The list can be supplemented through the technical support service by providing the code BZ49367

Otherwise, an error message is shown.

- The *Unique field* flag has been added for the *Number* and *Text field* types. Parameters containing the flag must have unique values when creating or editing the corresponding entity. For example, if this entry is specified for the parameter named *Super email* which was created for the *Account* entity, then the *Super email* field for each of the accounts must have a unique value, otherwise the error "The parameter must be unique" appears.
 - The authorization form for the main (admin) System interface has been enhanced. A video background has been added, which can be disabled either at the System level (by contacting Technical support team and specifying the code BZ71894) or at the user level. Enabling and disabling at the user level is possible if the background is enabled at the System level. It is enabled/disabled by the *Animated login background* flag in the *User settings* interface.
 - Operations with presets have been modified - particularly, in the *CDR export*, and *Rate export* interfaces. Buttons for working with presets (*Load*, *Save*, *Delete*) have been changed to icons (*Save/Rename* , *Delete*  and *Reset selected preset* ). If no preset is selected, only the *Save/Rename*  button is available. When selecting a preset and changing any filters for the loaded preset, the icon is displayed with a blue dot. When you click *Save/Rename*  for the modified preset, a window appears with a choice: update the current preset or save the changes as a new preset.
 - The new System parameter *Inactivity logout timeout, min* has been added that allows setting values from 1 to 60 (in minutes) for the automatic logout timeout in case of user inactivity (the default value is 15). User activity is defined by the cursor movement on System tabs. The timeout counting starts as soon as the user switches to another tab or minimizes the browser window. Note that the setting does not affect users with the enabled new permission *Ignore inactivity logout timeout*. The new permission is automatically granted to users having the *No restrictions* role.
 - It has been allowed to specify negative values as tax (from -100 to 100) in the parameters of the *Contract companies* interface:
 - *Default tax percent for client*
 - *Default tax percent for vendor*and agreement parameters:
 - *In tax rate*
 - *Out tax rate*
 - *In default tax rate, %*
 - *Out default tax rate, %*
-

- The new source for fetching exchange rates has been added - MAS ([Monetary Authority of Singapore](#)). The corresponding value should be set in the System parameter *Currency update source* (1 - BNR, 2 - ECB, 3 - CBR, 4 - ECBf, 5 - NBU, 6 - LCB, 7 - NBRB, 8 - MAS, null - disabled). Also, the following System parameter has been added: *Key ID for MAS (Monetary Authority of Singapore)* to specify the token to access MAS.
- The *Bank accounts* permission has been added for access to the *Bank accounts* interface. After update to the new version, the permission will be automatically granted to all users having the *Payments* permission.
- The name of the System parameter *Calculate charge detail amount as volume * rate* (0 - no, 1 - yes) has been changed to *Calculate charge detail as the multiplication of volume and rate* (0 - no, 1 - yes).
- Multiple choice fields (e.g. *CDR fields to export*) are now marked as mandatory. Previously, even if a field was mandatory for selection, it was not marked with a red asterisk.
- Previously, modules responsible for generating XLS/XLSX documents (docprocessor), sending emails, analyzing voice rates (ratechangeanalysis) recorded internal logs in GMT timezone. Starting from the new version, the time zone of a server will be used.
- Upon entering an incorrect login or password to access the web interface, the password field is automatically cleared.
- The outdated *Report schedule* permission was removed.
- The descriptions of System jobs have been refined.
- The possibility to select RTP type at the client carrier's level has been added. For this purpose, the new *RTP type* field was implemented in *Carriers/Voice POI* page. The possible values are the following:
 - *Default*: the response does not contain RTP headers (the vendor's address is not transmitted in voice switch responses).
 - *Open RTP*: the header *Vendor RTP: open* is added to the response.
 - *Close RTP*: the header *Vendor RTP: close* is added to the response.

Note that the functionality is only available for the voice switch supplied by Alaris (internal setting: responseMode=17).

- Dial codes uploading has been optimized.
- Invoices and rates will not be sent to partner users' emails if the user is inactive (even if the *Send invoices* and *send to partner emails* checkboxes are enabled, respectively).
- Possibility has been added for *Outgoing email accounts* to send emails using OAuth. New fields *OAuth Token*, *Client ID* and *Client Secret* have been added. If the *OAuth Token* field is not filled in, OAuth is not used for sending. The enhancement applies only to Google mail servers.

The following steps will be required to obtain the accesses (token, ID, secret):

1. Create a project or use an existing one:
<https://console.cloud.google.com/projectselector2/apis/dashboard?supportedpurview=project>
 2. Go to *Enable APIs & services* and enable 'Gmail API' with ENABLE APIS AND SERVICES
 3. On the *OAuth consent screen* tab create an entry (*Create button*).
-

4. On the *Credentials* tab select CREATE CREDENTIALS -> OAuth client ID and specify *Application type* as 'Desktop app', save *Client ID* and *Client secret*.
5. Follow the link: https://accounts.google.com/o/oauth2/v2/auth?scope=https://mail.google.com/&access_type=offline&include_granted_scopes=true&response_type=code&state=state_parameter_passthrough_value&redirect_uri=http://localhost&client_id=CLIENT_ID

where CLIENT_ID should be replaced by a specific Client ID value. In response, a link will be received from which the value of the code field should be taken.

6. To get offline_refresh token, send a POST request to: https://oauth2.googleapis.com/token?code=CODE&client_id=ID&client_secret=SECRET&redirect_uri=http://localhost&grant_type=authorization_code

where CODE must be replaced with the code value from the previous step

ID - Client ID

SECRET - Client secret

The refresh_token value should be saved from the response.

7. *Refresh (offline) token, Client ID, Client secret* values should be specified for the mail server in the System. The password should be left blank.

The following articles also describe the process of obtaining a token:

<https://support.google.com/cloud/answer/6158849>

<https://learn.microsoft.com/en-us/power-platform/admin/connect-gmail-oauth2>

If you have any questions, create a Helpdesk ticket with the code BZ66851.

- The *Disputed letter* template has been added to inform partners about dispute initiation. Emails are sent if the new System parameter *Send disputed letter* is enabled (by default - disabled) and the invoice has the status *Disputed* or *Disputed (manual)*. Emails are sent for vendor invoices if the invoice was registered with the *Disputed* property or if the invoice was already in the disputed status and was confirmed using the *Confirm without sending* button.

The following new markers have been added to use the template:

[PresentedAmount] - the presented amount

[DisputedAmount] - the amount of the dispute

Additionally, the following markers can be used: [ChargeAmount], [CompanyRegisteredName], [InvoiceRefNumber], [InvoicePeriod], [InvoiceRegDate], [InvoiceTimezone].

Active calls

- Identification of carriers in the *Active calls* interface for Sansay voice switch has been refined: since the switch works with trunk groups, carriers will be identified only by the voice POI with the correctly filled *Trunk group* field.

Analytics

- The System parameter *Apply billing increment to round raw duration in analytics (1 - yes, 0 - no)* has been deleted as it was out of use.

Billing logic

- The *Active from* and *Active till* dates have been added to the bottom table of the *Billing increments* interface in order to ensure the consistency of dial code based increments. Also, support of wildcards has been added (for example, 1%). Please note that if two similar records such as 1 and 1% are used, the record with no mask has priority. Besides, the System parameter *Override rate increments with dial code based increments* (0 - no, 1 - yes) has been added. The default value is 0 (original behaviour). When enabled, the billing increment set for a specific dial code in the interface (with account for its *Active from/till* dates) will have priority over the rate's billing increment in routing and billing. Longest-match search is used. If no billing increment is found for a dial code, the rate's billing increment will be used.
- It is now possible to specify 0/0/0 increment when importing rates and entering the increment in the corresponding reference book.
- The new flag *Force using default increments* (disabled by default) has been added for International products. When the new logic is enabled, the billing increment is searched by a combination of A-number (or its mask) and B-number (or its mask). The setting in the product takes precedence over the new System parameter *Override rate increments with dial code based increments* (0 - no, 1 - yes) if the parameter is set to 0. When the new logic is enabled, the search will be performed by records from the interface *Billing increments* (*Dial code based increments* table), for which it is now possible to specify *Origin dial code*, and then by billing increments configured in rates.

Carriers

- Values for the *In time zone/Out time zone* parameters will be automatically substituted from the *Contract companies/Agreement defaults* when creating an Agreement in the main web interface. If the value is missing, the System time zone will be used.
 - Empty default values are now allowed for the following parameters of the *Agreement defaults* tab (*Legal entities/Contract companies* interface): *Default credit limit for client*, *Default credit limit for vendor*, *Default DID credit limit for client* and *Default DID credit limit for vendor*. Previously the default value was 0.
 - The *Save without priorities* button has been changed to *Reset priorities* in the *POI routing priorities* window for vendor products. In addition, the button location has been swapped with the *Cancel* button.
 - It is now possible to automatically fill the *Account alert emails* field with the email address of a partner who has registered on Wholesale Portal. This feature can be useful for notifying partners about maintenance work resulting in portal unavailability using service notifications. To enable the functionality, please contact the Alaris technical support and provide the code BZ62874.
 - In rare cases (e.g. in cases of unstable Internet connection), the opened interface may not be loaded correctly. In such cases, the following warning message appears: 'Correct work of interface is not guaranteed. Do you want to continue?'
 - Test carriers (those with the [TEST] prefix) are now displayed at the end of the carriers list. Also, the *Show only [TEST]* checkbox has been added to show test carriers only.
 - The *Highlight balance* checkbox (enabled by default) has been added to the *Accounts* page to highlight the values in the *Balance* column depending on the balance thresholds (configured at the *Accounts* or System level). The following highlight colors are available:
 - green: the balance value does not exceed the first threshold
 - light green: the balance value is between the first and the second threshold (excluding the second threshold value)
-

- yellow: the balance value is between the second and third thresholds (excluding the third threshold value)
- orange: the balance value is between the third and fourth thresholds (excluding the fourth threshold value)
- light red: the balance value is between the fourth and fifth thresholds (excluding the fifth threshold value)
- red: the balance value exceeds the fifth threshold (or is equal to the exact value of the fifth threshold)

Note that the highlighting only applies to accounts for which a client agreement is available.

CDR management

- Multiple number search has been added to the *Dial code mask* and *A-number mask* fields in the *CDR export tool* interface. For example: 1210123%,1220011111. The fields are limited to 4000 bytes; attempting to enter more characters will result in an error.
- When calculating values for the *Partner cost* column in the *CDR reconciliation* interface, rounding is now applied (same rounding logic as for the *Owner cost* column), taking into account the *Rounding digits (vendor leg)* System parameter.
- When the *Matching column set* field is being filled in for a new task in the *CDR reconciliation* interface, a tooltip appears containing a list of columns that are mandatory for parsing.
- It is now possible to filter the tasks by *Affected start date* and *Affected end date* columns in the *Voice/CDR management/CDR rerating/Autorerating* tab.
- CDR export procedure has been improved for faster performance.
- The export speed of reconciliation results with the help of the *Download as CSV* button has been optimized in the *CDR reconciliation* interface.

Enterprise API

- The methods *add_charge_detail* and *update_charge_det* were combined into a single *update_charge_detail* method. If *det_id* is transferred as an empty value, the logic is similar to *add_charge_detail*. If *det_id* is not empty, the logic is similar to *update_charge_det*. Also the method description has been improved, and processing of input parameters has been enhanced.
- In the new version, the 2FA verification set for a user will be ignored for Enterprise API (EAPI) and REST API requests from that user.
- For methods of the *update_%* type the update logic has been refined: starting with the new version it is not necessary to pass all parameters, but only those that should be updated.

Financial module

- The value for the System settings *Global minimum client invoice amount* and *Global minimum vendor invoice amount* can now be set to 0. In this case, it is possible to generate traffic charges with a zero amount (for example, in case of zero rates). Also, the *Confirm invoice* checkbox has been removed from the recurring fee creation form.
 - In the *Product types* interface, you can now enable the *Use volume for charges* checkbox for custom product types. If enabled, the [ChargeVolume] marker used in financial templates (for example, *Invoice* and *Invoice details*) will be replaced by the *Service count* value, which is filled in when creating a manual charge for this custom product type.
-


- The prioritization when calculating financial cubes (data on which invoices are based) has been slightly changed: when old cubes are set for recalculation, they will have higher priority than current cubes. This will speed up recalculation of financial data and invoicing.
 - Starting with the new version, System parameters *Charge detail rounding digits* and *Charge detail rounding function* now affect the amounts of invoices (parameters *Estimated amount*, *Due amount*, *Tax amount*). Note that in the invoice PDF document (when using the corresponding markers) the values are rounded according to the System parameter *Default format: numeric (monetary)* (default: 2 decimal places).
 - Verification for the first line is now performed when uploading a file for balance synchronization. If it is a header (that is, it does not contain any date), it will automatically be discarded for further processing of the file.
 - If the System parameter *Invoice due date based on (0 - issue date, 1 - registration date)* is set to 1, then when sending or resending an invoice for a payment, the registration date is not reset to the current date, but remains as the date specified by the System owner.
 - The *Recurring fees* interface has been improved: possibility to specify the history of volumes and rates has been added (that is, different validity dates within one charge). When upgrading to the new version, all existing charges will be converted to the new format without affecting the calculations. The ability to perform backdate changes of volumes and/or rates has been supported. Changes are applied after saving when the FIN_HOURLY_ROUTINES System task is started. If the charge end date is changed, rates active after the end date will be deleted. The charging logic has not changed: if the rate start date is in the middle of the billing period, the fee will be charged for the number of days remaining. Also, several rates may be valid within one billing period: the amount will be calculated with account of their validity dates.
 - When editing an invoice, it is now possible to fill in the new field *Correction to invoice ref code* to indicate the invoice number to which this correction (credit note) has been made. The corresponding column has been added to the main table with invoices. The [CorrSourceRefCode] marker has also been added for use in invoice files.
 - Invoices that belong to a closed period (according to the System parameter *The date after which the billing period is considered closed* or a similar parameter at a contract company level) are grayed out.
 - Since all previously made mappings were cleared before mapping of payments and invoices, the process took a long time to complete. With the new System version, the flag *Clear existing mapping* has been added to the *Make auto mapping* window (default: *off*), which allows you to skip this step and optimize the mapping process. Please note that when confirming invoices with the *Make auto mapping* flag or when creating/editing a payment with the same setting, the previous mappings are not cleared.
 - When generating invoices, the [ChargeDetColumn2] marker will be replaced with a blank space for recurring fees details. Previously the marker was replaced with the value *Recurring fee:<FEE_ID>*.
 - The [ProductNotes] marker has been added for *Invoice*, *Invoice details*, and *Invoice letter* templates. The marker is replaced by a list of product notes (separated by commas). The maximum allowed size for marker replacement is 100 records or 4000 characters.
 - The [ChargeDetailsDescr] marker has been added for financial templates, to display the [ChargeProductDescr] data (product name) and the details of the *Details* field of the recurring fee.
-

- It is now possible not to process payments from PayPal payment system received with the `protection_eligibility=Ineligible` attribute. When receiving such payment the 200OK response will be returned, and the payment will not be registered. To enable the logic, contact the Alaris technical support team and report the code BZ43430.
- If a *Fee* is set for the *Stripe* payment system, then the amount before *Fee* will be entered in the payment parameter *Bank statement amount*, and the amount after *Fee* will be entered in the *Amount debited* parameter.
- When exporting payments, two new columns will be added to the file: *Bank account* and *Contract company*.
- It is now possible to sort by the *ID* column in the *Charges* interface.
- Previously, corresponding charges were not deleted when using the *Delete this recurring fee and all existing charges* button. This behavior has been fixed. Additionally, the button has been made available only to users with the *No restriction* permission.
- The new System parameter *Calculate invoice amount as sum of rounded charges (0 - no, 1 - yes)* has been added (default value 0), which defines the sequence of actions to calculate the invoice amount. If the value is 0 (previous behavior), the values of the charges are first added up and then rounded. For example, suppose the invoice contains the following cost values by country:
 - 74.77739
 - 10.29628
 - 191.39846
 - 78.60825Then the total invoice amount (355.08038) will be rounded up to 355.08.
If the parameter is set to 1, the values are first rounded to two digits (e.g. 74.77739 is rounded to 74.78 and 78.60825 is rounded to 78.61) and then the values are added up. Hence, the invoice amount will be 355.09.
- For products of the *International* type and *Invoice details* template, the [DetVolumeInt] marker has been added to display the call duration in the format HH24:MI:SS. If the marker is specified for inappropriate product types, it will be replaced with a blank.

Limitation rules

- Calculation of deals with the *month* period has been improved - the calculation starts from the current day minus the number of months specified in the *Period length* field if the System has enough daily cubes to calculate an incomplete month.
 - Possibility has been added select the direction for the *Product notes* field (in the new *Product notes direction* field). Thus, a limitation rule can be triggered for the vendor product notes as well - the displayed list will be filtered by direction.
 - Possibility has been added to set a list of vendor products in the new *Vendor products* field (Exclusive or Inclusive list). The original *Product* field has been renamed to *Client product*. In this way, rules can be created specifically for tracking the limitations of a client product or for the client-vendor product association.
 - A *Lock statistics* column has been added to the *Voice/Routing/Limitation rules* interface. The column displays two rows: how many destinations have been locked (*Locked* counter) and how many destinations have been unlocked (*Unlocked* counter).
-

Number management

- The *Export to CSV*  icon has been added for exporting the *Number management* interface data (*Numbers* tab sheet).
- The message that appears when editing or deleting a scheme that is currently being used has been corrected: "The scheme that uses the existing code is not edited" has been changed to "Billing scheme that is used by active numbers can not be deleted".
- An additional check is now performed when deleting a billing scheme. If the scheme is bound to a number belonging to the client Carrier (or was bound earlier), it will not be possible to delete such a scheme. Previously, a similar restriction was added for the vendor side.
- The checkbox *Issue NRC charges immediately* to bill NRC charges with a one-day (current) period has been added to billing schemes. If the checkbox is not selected, the invoice will be generated according to the billing period selected in the agreement.

Rate compilation

- The rates listed in the *Involved vendor dial codes* table of the *Rate compilation* interface are now sorted in ascending order (previously the order was random). This sorting also affects the order in which routing rules are selected in case *Generate routing rules* button is applied.
- Inactive vendors (i.e. those who have *Is active* flag disabled at the *Carrier* or *Product* level) are now excluded from rate compilation. If it is necessary to include inactive vendors in rate compilation, contact Alaris technical support team and communicate the code BZ63886.

Rate editor

- The new reference book *A-number groups and codes* has been added for creating A-number group and A-dial codes associations. The corresponding filter *A-number group* has been added to the interface of rate editing. Additionally the grouping capability (*Group by*) by the A-number group has been added. When creating or editing a rate it is required to specify a group instead of a specific A-dial code, the corresponding column is also present on the *Rates* panel, where its value is a hyperlink to the corresponding group in the new reference book.

Rate export

- A tooltip has been added to the *Add column* field of the *Column settings* tab sheet, explaining that it is possible to use control structures for column values. The following control structures are supported:
 - |B - highlight the cell with a border line of medium thickness
 - |BX - highlight the cell with a border line of predefined thickness, where X is the thickness (1 - thin, 2 - medium thickness, 3 - thick)
 - |NR - show negative values in red font
 - |NS - separate groups of three orders by a blank space (for example, 1 234 567 890.123)
 - |NX - round the value to X decimal places (X must be replaced with the number of decimal places). Negative values m, -2 - round to hundreds)
 - |WX - fixed column width where X is the number of pixels
 - |WT - take the column width from a template. If no template is selected when creating the document, the System will use the value from the System parameter "Excel column width settings ('WT' - Width from Template, 'E' - external, 'I' - internal)"
-

- |WE - the column width is defined automatically by means of the Apache POI library (method `sheet.autoSizeColumn`)
- |WI - the column width is defined by an internal algorithm: the maximum width of the inserted value; the value can not exceed 50 pixels
- |H0 - define the column height automatically (if the structure is not used, the height is defined as per template)
- |F - MS Excel auto filter; the structure must be set in multiple columns, and the filter will be applied to the columns between them
- |T - treat the value as text and not try to translate it to a number
- |WR - use word wrap for the cell

Example: `Rate|B3`

- For greater customizability of the pages to be exported when selecting A-number based products, the *ANI rate export type* field has been added with the options *Single page* and *Multiple pages*. For the multi-page format (selected by default) the pages *Rates without ANI groups*, *Rates with ANI groups* and *A-number codes* will be exported (columns for the pages are customized on the *Column settings* tab). For the single-page mode the *Main* and *A-number codes* pages will be exported. If the *Multiple pages* type is selected, the options of grouping by code or by destination for pages with and without ANI groups become available (*Grouping for list with ANI groups* and *Grouping for list without ANI groups* parameters).
- The `[ConfirmationLink]` marker now references the address from the *Wholesale portal URL* parameter (previously it was replaced by the address of the main web interface).

Rate import

- The new System parameter *Dialcode ignore markers* has been added. It allows specifying markers to ignore specific dial codes (not filled in by default). When a marker is specified (e.g. -), if the specified value occurs in the second *Dial code* column, only the codes from the first column will be used for the rate import.
 - The *Post processor* field is now hidden from the *Rate import* interface, since this functionality is obsolete.
 - The critical error text for automatic import "Rate <= 0" has been corrected to "Rate < 0", since the value 0 does not cause an error.
 - The *Rates based on* field is marked as mandatory (previously it was mandatory, but without explicit indication) when importing rates for client products with US domestic type or DID type.
 - Previously, if there were duplicate lines with rates for the same phone code, the price from the first line encountered was imported. Starting from the new version, the rate with the maximum price will be chosen for import.
 - For easy analysis of imported rates, a tooltip has been added to the *Summary* column of the *Tasks* table. The tooltip shows import type (*Rate merging options*). The same information can be opened by double clicking the column.
 - A new *Line #* column has been added to the *Rate import* interface (available when analyzing changes through the view hyperlink), similar to the *Rate import (old)* interface. The column displays the sheet name and line number of the source file for the rate change, and is also shown when the results are uploaded to Excel.
-

- The *Do not close rates without price* checkbox is now unavailable when the *Rate merging options* field is set to something other than *Update only rates for fully matching dial codes*, as not closing empty rates is not the intention when selecting a close type.
- The following templates have been added for sending full and short reports to the System owner and carrier, respectively, during auto rate import. Previously such reports were defined by the System code and could not be configured by the user:
 - *Voice auto rate import owner notification (full report)*
 - *Voice auto rate import owner notification (short report)*
 - *Voice auto rate import carrier notification (full report)*
 - *Voice auto rate import carrier notification (short report)*

Short reports contain a summary of new, closed and extended rates. Full reports additionally contain attachments (xlsx files with a list of errors and rate preview). The following markers can be used in the templates:

- [CompanyName] - contract company name
 - [OwnerName] - System owner name
 - [AutoRateImportStatus] - import status (0 - not imported; 1 - imported)
 - [RateImportStartDate] - import start date and time in the format YYYY-MM-DD HH24:MI:SS
 - [RateImportEndDate] - import end date and time in the format YYYY-MM-DD HH24:MI:SS
 - [Product] - product ID
 - [ClosedRatesNum] - number of closed rates. It is replaced with 0 if AutoRateImportStatus=0
 - [ValidRatesNum] - number of valid rates. It is replaced with 0 if AutoRateImportStatus=0
 - [NewRatesNum] - the number of new rates. It is replaced with 0 if AutoRateImportStatus=0
 - [ExistRatesExpndOrClosedNum] - the number of closed or expanded existing rates. It is replaced with 0 if AutoRateImportStatus=0
 - [DeletedRatesNum] - the number of removed rates
 - [CriticalErrors] - list of errors (error group names) detected during import, and their count. The maximum number of displayed errors is 3
 - [PleaseSeeAttached] - the marker is replaced by the entry "Please find the full list of warnings attached." if an attachment is present; otherwise it returns an empty result
 - [RateImportPresetName] - name of preset used for rate import
 - [AutoRateImportRuleID] - auto rate import rule used for rate import
 - [EffectiveFrom] - rate effective from date and time
 - [EffectiveTill] - rate effective till date and time
 - [CloseType] - rate close type
 - [Link] - link to a file with new rates
- The *libreoffice* value has been removed from the *Parser list* options when loading rates.
-

Reference books

- The *Regular expressions* interface has been improved as follows:
 - A separate *Mass edit* tab has been added to the *Edit* panel for mass editing of regular expressions. The tab becomes active when several groups are selected in left section of the interface. The standard *Edit* tab becomes inactive in this case.
- Possibility has been added to receive active calls for the voice switch supplied by Alaris - OpenSIPS. For this purpose, the option to select *Software manufacturer=OpenSIPS* has been added to the Soft switch editor interface. It is possible to enable the checkbox *Use in active calls* in the record, and fill in the required fields. Note that the internal configuration must be set up in advance. For this purpose contact the Alaris Technical Support team and communicate the code BZ52027.
- Hints (steps) showed when multi-editing codes in the *Dial codes* reference book have been changed to make them more understandable.
- For the OpenSIPS voice switch, possibility has been added to check the availability of the IP address from which the call comes, in existing POIs before routing. For this purpose, the *enable IP whitelisting* flag has been added to the Soft switch editor. When enabled, the *MySQL IP*, *MySQL port*, *MySQL login*, *MySQL password*, *MySQL whitelist table* fields become available to determine access to the internal MySQL table where information on available IP addresses is stored. To fill the fields with correct values, contact the Alaris technical support service and provide the code BZ64021.
- Now the *Payment systems* tab (*Reference books/Contract companies*) will display only those systems that are set up for the user's contract company, according to the user's permissions.
- The new *Datetime patterns* reference book has been added to enable the creation of custom date and time patterns and their subsequent use in interfaces - for example, in the *Rate import* interface.
- A syntax check has been added when a regular expression is specified. If the check is not passed (for example, if the number of brackets in the regular expression does not match) and the user attempts to save the rule, an error will be generated.
- It is now possible to specify different sources for automatic fetching of different currencies. When creating a currency in the *Currency exchange rates* interface (*Existing currencies*), it is necessary to fill in the *Currency rate source* field with the required source:
 - *System default* - the value will be taken from the System parameter *Currency update source* (1 - BNR, 2 - ECB, 3 - CBR, 4 - ECBf, 5 - NBU, 6 - LCB, 7 - NBRB, 8 - MAS, null - disabled).
 - *Manual* - the currency rate will not be updated automatically.
 - Other value (for example, ECB) - the exchange rate will be updated from the specified bank.

The corresponding (uneditable) *Source* column has been added to the exchange rates table to display the bank selected for the currency. If the *Currency update source* is changed for the currency, the previously loaded exchange rates remain with the source specified for them previously. When adding the exchange rate manually (*Add* button), the value will be set to *Manual*. Note that the System parameter *Currency update source* (possible values - ECB, LCB, BNR, NBU, NBRB, CBR, null - disabled) has been renamed to *Currency update source* (1 - BNR, 2 - ECB, 3 - CBR, 4 - ECBf, 5 - NBU, 6 - LCB, 7 - NBRB, 8 - MAS, null - disabled). The previously set value will be changed to the corresponding new one.

- It is no longer allowed to edit the values of the *Date* column for existing exchange rates.
-

Reports

- It is now possible to select inactive carriers for the *Reports* interface.
- The *User creation log (Change logs)* report has been added, which displays information about new users.
- In the new version, forced resetting of modified roles to the default role (*Reports*) has been removed for System reports.
- *User logon history (Administration)* report has been modified: previously the report included records only if a regular logout from the System was performed. Starting from the new System version there will be no dependence on the way of logging out. Please note that in case of a non-nominal logout from the System (for example, closing the browser), the session end time will be recorded with a slight delay, which will affect the session duration displayed in the report.
- The *Statement of account with start/end balance* report has been modified to take into account unconfirmed invoices for which the *Presented amount* value was different from the *Estimated amount* and the *Amount source* was set as *Amount presented by partner*. Now, the balance displayed by the report is brought closer to the account balance.
- The tooltip for report schedules has been improved: if the schedule is not explicitly set, the tooltip previously reported that the report would be run every minute. Since the reports are not actually run, the situation has been fixed.
- The following reports have been added: *User change log (Change logs)* and *User roles change log (Change logs)*, replacing the former *Permission change log (Change logs)*, to track changes applied to users and user roles, respectively.
- Possibility to select a category has been added to the *Reports* interface - the *Category* field is available when adding or editing a report. The category will be automatically added to the report name (in brackets).
- The *CDR Export (Voice)* report has been added that shows CDR data.
- The *Vendor cost report (Stats)* report has been reworked: the possibility of multiple selection of carriers and their products has been added, as well as the new checkbox *Show only traffic with duration*, which is used to display only the traffic with duration. Additionally, the report's output now contains the *Total* row.
- The bottom grid with report execution tasks can now be extended so that more tasks can be seen on the web page.

REST API

- The PUT:param method has been removed from REST API.
- Now the *ip* parameter for the REST API method *GET:auth* can be transferred as case insensitive (for example *IP* or *Ip*).
- The REST API method PUT:invoice has been hidden from the interface.
- Verifications for the GET:cdr_export method have been improved. For users that were created under any partner other than the System owner, the method returns only those records that belong to the user's partner.

Routing

- The *ANI dial code* column was added to the table with routes to display dial code of A-number to make working with products with A-number billing more convenient.
- To make the logic easier to understand, the System parameter *Prohibit traffic going to products of the same carrier (0 - disabled, 1 - full block, 2 - block by product name)* has been renamed to *Enable traffic exchange between the same carrier products (0 - disabled, 1 - enabled for all product names, 2 - enabled for different product names)*. The System parameter values will be updated to maintain the previous behavior. Additionally, the flag *Allow traffic within the same partner products* has been changed to a drop-down list *Allow routing to products of the same carrier* with possible values:
 - No
 - Yes, for all product names
 - Yes, for different product names
 - System setting

Swap deals

- The *Swap deals* interface has been moved to *Finance* from the root menu.
- The TRD_SWAP_UPDATE_JOB System task is now run every hour instead of once a day to make the statistics for active swap deals more up-to-date.



Tags

- The *Treat dial codes as masks* checkbox in the *Tags import* interface has been renamed to *Treat numeric tag values as masks*.

Template manager

- It is now possible to specify the direction for the *Balance alert letter* and *Credit alert letter* templates.
- The marker [POIActiveCarTranslations] has been added for finance templates (for example, *Invoice*, *Invoice letter* and *Invoice details*). The marker is replaced with values of the parameter *Carrier-specific number translation* from the product's POIs. The maximum number of replaced symbols is 256.

Wholesale Portal

- The payment icon  has been replaced with the 'money'  icon as it could be perceived as 'payment in USD'.
-

2 Fixed issues

General

- Incorrect operation of the *Database info* function has been fixed.
- Previously, if there were several sessions of the same user and the password for this user was changed, the parallel open sessions were not terminated.
- If a mail server has been removed from the *Outgoing email accounts* interface, and the internal queue has unsent messages (for example, due to failed authorization), the following error will appear: "A mail server with the queued emails to be sent cannot be deleted".
- If the password for connection to the email server of the *Outgoing email accounts* interface contained the ' symbol, an error occurred when verifying connection with the server. The issue has been fixed.
- Sorting by the *Product* column in the *Rate import* interface has been fixed, as well as on the *Files* tab of the *Email processing rules* interface.
- Due to the failure of the SNMP protocol to collect metrics for the start page, the corresponding script and the *Enable SNMP metrics gathering (0 - disable, 1 - enable)* System setting have been removed.

Active calls

- The incorrect display of ports for the *Client IP* and *Vendor IP* columns has been fixed.

Analytics

- When setting a fractional time zone (for example, GMT+3.30) on the user device, an incorrect time shift was observed for the days on which daylight saving time change occurs.
- When exporting a large amount of data using *Export from grid* button, the error 'Allowed memory size of ... bytes exhausted' may occur, saying that the allocated amount of memory is exceeded. Previously, the error was visible only in the browser console. The behavior has been fixed and the error now appears in the web interface. To increase the memory size, contact Alaris technical support team.

Carriers

- When deleting a product, the error "result of string concatenation is too long" could occur caused by the product being present in a large number of rules. This situation has been resolved.
 - If a product is used in a large number of rules, upon removing the product from all routing rules with the help of the *Delete this product from all routing rules* button, the following error could occur: "Maximum number of filtering parameters exceeded. Please reduce the number of parameters to filter". Starting with the new version, the situation has been fixed.
 - Previously, a voice POI could be selected incorrectly when authorization was based on the trunk group and the IP address of the switch from which the call came due to the fact that several POIs could have the same trunk group but use different switches. The situation has been fixed.
 - The method called when deleting a voice POI has been optimized. Previously, it could generate the 'user requested cancellation of current operation' error due to timeout when deleting POIs.
-

Fixed issues

- When the *Is active* checkbox is disabled either for a product or for a corresponding carrier, POIs associated with the product become inactive as well (greyed out); from that moment on, all traffic for these POIs will be blocked.
- Previously, if there were several inactive and active products with the same name, the product name in the filter could be colored either grey (inactive) or black (active) depending on the internal sorting of the web interface. To standardize the behavior, now all product names (including inactive ones) in the filter are colored black.

CDR management

- Previously, when modifying a rate with a future date in the CDR rerating interface, an auto recalculation task could be created, although the change did not affect past traffic. The issue has been fixed.
- Loading of the *CDR rerating* interface and corresponding subtabs has been optimized.
- Rounding of fractional values has been corrected for the *Owner duration, min.* and *Partner duration, min.* columns in the output of CDR reconciliation.

CDR export

- Filtering in the *Comments* column operated incorrectly if capital letters were used in the field when creating a task.

Enterprise API

- Verification for mandatory input parameters for the *start_packet_simulation_wfr* method has been added. Also, documentation has been updated.

Financial module

- Previously, when creating an NRC charge, the *Billing scheme* name column was not filled in. The issue has been fixed.
- If there were two agreements of the same carrier with different time zones, the traffic amount for the overlapping period was duplicated. The issue has been corrected: the start date of the charge will not be earlier than the end date of the previous charge.
- When creating a subscription in the *Finance\Recurring fees* interface, the availability of an active agreement for the subscription period will be verified. In case it is not available, the following message will be displayed: "No actual agreement found for the account id: %ID%; period: %period%"/"No actual agreement found for the account id: %ID%; period: %period%" .
- When exporting the payment table to Excel, the *Covered amount* and *Amount debited* columns are now available in the file. Additionally, the *Reference number* filter now allows search by mask.
- An internal error could occur when uploading a file to compare charges using the *Compare* button. The issue has been resolved.
- When changing the billing period from daily to weekly, and then recalculating the invoice period for recurring fees, incorrect rows (additional charges) were added to the recalculated invoices. The issue has been fixed.

Number management

- When removing a partner and its child entities that were specified in the *Number management interface*, the Deassign operation was performed; however this fact was not registered in the history of operations.

Rate import

- Limitation on extensions of imported files has been introduced in rate import interfaces: now only files with extensions xls,xlsx, csv are allowed to be imported.
- Previously, when processing emails for automatic import, the following tags could be detected in the corresponding .eml files, which disrupted the operation of the *Email processing rules* and *Rate import* interfaces:

```
<meta name="color-scheme" ...>
```

```
<meta name="supported-color-schemes"...>
```

This issue has been fixed.

- Previously, the System could not correctly define a mail processing rule if keywords specified in the Mail text mask field were separated by a line break in the source mail. The situation has been fixed.
- Previously, the simulation result for mail processing rules could be different from the actual result, as when specifying multiple emails in the *To* field during simulation, the rule's field *Mail to/CC/BCC mask* was treated as a mask even if exact match was required. The logic was synchronised.
- Previously, getting auto import emails the *To*, *CC* and *BCC* fields of which exceed 4000 bytes (in total) caused the following error upon opening the *Email processing rules* and *Rate import* interfaces: "Please provide your database administrator with this error. ORA-01489: result of string concatenation is too long". The situation has been fixed: now if the length of the fields exceeds the allowed value, the check is performed only for the *To* and *CC* fields, otherwise — only for the *To* field.
- An empty window was shown for the *Rate import (old)* interface when viewing *Import history*.
- Previously, incorrect verification of dates for sending notifications (i.e. *New rate/Close rate/Decrease/Increase notification period violated*) was observed if the partner and System time zones were different. Starting with the new version, when checking dates in the *Effective from* column, the partner's time zone specified in the agreement is taken into account along with the allowed *Rate notification* periods. Suppose the partner's time zone is GMT+3 and the System time zone is GMT+0. If the rate start date and the allowed date (as per agreement settings) for applying changes is 2022.11.08 00:00 GMT+3, during import the date will be changed to 2022.11.07 21:00 GMT+0 and a notification will appear that this is incorrect.

Reference books

- In rare cases, when receiving simultaneous changes to dial codes, the changes could not reach the voice router. To avoid such situations the new internal System parameter RAT-LOG_RETROSPECTION_PERIOD has been added to allow changes to be tracked retrospectively (the default value is 5 minutes). To change the value, contact the Alaris technical support team and provide the code BZ31928.
 - Entries on the *Payment systems* tab will be grayed out if the values for the payment system are completely inherited from the *Default* contract company. If at least one value of the payment system has been overridden for a particular contract company, the entries will be in the usual (black) color.
-

- When a contract company is removed, payment system settings for the contract company are now also removed from the respective tab.
- When attempting to edit a record in the *Reference Books/Bank accounts* interface, if the required permissions are lacking, an editing error appears. Previously, the record was not edited, but no error was generated.

Reports

- Incorrect data display for filters of the *Advanced multiselect* and *multiselect* types has been fixed, if the filter depended on another filter of the *Advanced multiselect* type.
- An error occurred when transmitting a large number of values in the incoming parameters (filters). The situation has been corrected.
- The pagination panel displayed an incorrect number of available rows in certain cases. The issue has been fixed.
- The output of the *Generation delay passed* column of the *Invoice generation delay (Finance/Voice)* report has been adjusted, as previously the column could display incorrect data.

REST API


- Previously, a deactivated user could send requests to REST API. Starting with the new version, the situation has been fixed.

Routing

- Due to the specifics of information storage by tag, incorrect update of tag values was observed in the routing module if several identical values were available under one tag (with different periods). Starting with the new version, the routing module will use the tag ID to avoid the described situation.
- Previously, when filtering rules by the *Yes* value in the *Is active* column, rules that were filtered had the *Is active* checkbox enabled, but they could be considered inactive due to their effective dates. In the new version, a rule will be considered eligible for filtering (as active) if the checkbox is enabled and the rule is active based on its effective dates.
- Correct display of the *Vendor products* field has been enhanced when changing the rule type from *Block* to *Regular routing*.

Tags

- Previously, import of tags with the types *Merge* and *Close all existing records* closed the tags only if there was a full match (thus, the tags and their values in the file had to match the names and values that were already present in the System). In the new version, closing will be done by matching tag name.
 - The incorrect application of the *Delete tag and its content* function has been fixed. Note that a tag is not deleted (a corresponding warning is displayed) in case it is used in the routing rules or in the translation rules.
 - Tag import for the types *Merge* or *Close all existing records* closes tags only in case of exact match (thus, tags and their values in the file must fully match names and values existing in the System).
 - When importing tags with the *Delete matching records* or *Close matching records* import types and specifying only the *Tag values* column, the records of the existing tag are deleted/closed as intended.
-



Fixed issues

Alaris Labs
Telecom Software Products
Carrier-Neutral, Protocol-Agnostic

Wholesale Portal

- Previously, if a portal user had a large list of permissions (e.g. *No restrictions*), some menu items (e.g. CDRs) were unavailable for the user. The situation has been fixed, now only the permissions associated with the portal will be available for portal users to avoid the situation described above.
-

3 Known issues

General

- When the user logs out of the System by clicking the *Log out* button and then logs in again, the previously opened tabs are not restored.
- When selecting a region in a carrier filter, some carriers may be available that have a region with an ID that partly matches the region in question (for example, region ID=1 partly matches region ID=11). The issue is observed in multipickers, for example in *CDR export tool*.
- A user with the *Invoicing* permission but with no *Generate client invoice/Register vendor invoice* permissions can recalculate period for an account available to the user if *Direction: All* is selected. The situation is incorrect.

Rate editor

- Schedule for the *Offpeak* and *Weekend* periods is not cloned correctly when cloning a rate.

Rate import

- In rare cases, empty rows are added to xlsx files that make the file processing inconvenient.
 - If an email has an empty field (for example, email subject or body), it will be considered matching an auto import rule even if the rule for the field contains a specific mask (for example, %test%).
-



Database structure changes

4 Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
ACA_SANSAY_CALLS_TMP	-- Table --	created in 3.6.0				Temporary table for Sansay active calls
BAS_ACCOUNT	ACC_ALLOW_INCOMING	created in 3.6.0	NUMBER	22	N	Inbound traffic allowed
BAS_ACCOUNT	ACC_ALLOW_OUTGOING	created in 3.6.0	NUMBER	22	N	Outbound traffic allowed
BAS_AGREEMENT	AGR_IN_RAW_DURATION_SEC	created in 3.6.0	NUMBER	22	Y	In raw duration for 1 sec of increment (0 - no, 1 - yes)
BAS_AGREEMENT	AGR_OUT_RAW_DURATION_SEC	created in 3.6.0	NUMBER	22	Y	Out raw duration for 1 sec part of increment (0 - no, 1 - yes)
BAS_AREA	-- Table --	created in 3.6.0				Dictionary of dial code zones
BAS_AREA	AREA_ID	created in 3.6.0	NUMBER	22	N	Area id



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
BAS_AREA	AREA_NAME	created in 3.6.0	VARCHAR2	256	Y	Area name
BAS_AVAILABLE_PRODUCT_TMP	-- Table --	created in 3.6.0				Temporary list of products
BAS_AVAILABLE_PRODUCT_TMP	DIRECTION	created in 3.6.0	NUMBER	22	Y	Direction
BAS_AVAILABLE_PRODUCT_TMP	PRODUCT_ID	created in 3.6.0	NUMBER	22	Y	Product ID
BAS_BALANCE_CHANGE	AMOUNT_WITH_TAX	created in 3.6.0	NUMBER	22	Y	Usage amount with taxes
BAS_CARRIER	CAR_INBOUND_ALLOWED	changed in 3.6.0	NUMBER	22	Y	Inbound traffic allowed (1 - allowed, 0 - not allowed)
BAS_CARRIER	CAR_OUTBOUND_ALLOWED	changed in 3.6.0	NUMBER	22	Y	Outbound traffic allowed (1 - allowed, 0 - not allowed)
BAS_CAR_WATCHLIST	-- Table --	created in 3.6.0				Carriers watchlist
BAS_CAR_WATCHLIST	CAR_ID	created in 3.6.0	NUMBER	22	N	Carrier ID



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
BAS_CAR_WATCHLIST	ID	created in 3.6.0	NUMBER	22	N	ID
BAS_CAR_WATCHLIST	USER_ID	created in 3.6.0	NUMBER	22	N	User ID
BAS_CONTRACT_COMPANY	CC_IM_CHANNELS	created in 3.6.0	VARCHAR2	4000	Y	List of allowed channels for message termination - sms + list from product note
BAS_COUNTRY_DETAILS	-- Table --	created in 3.6.0				Country details
BAS_COUNTRY_DETAILS	COUNTRY_COUNTRY_ID	created in 3.6.0	NUMBER	22	N	Country id
BAS_COUNTRY_DETAILS	COUNTRY_REGION_ID	created in 3.6.0	NUMBER	22	Y	Country region id
BAS_COUNTRY_LOAD	-- Table --	created in 3.6.0				Table for loading countries
BAS_COUNTRY_LOAD	COUNTRY_ID	created in 3.6.0	NUMBER	22	N	Country ID
BAS_COUNTRY_LOAD	COUNTRY_NAME	created in 3.6.0	VARCHAR2	256	N	Country name
BAS_COUNTRY_TAX	-- Table --	created in 3.6.0				Country taxes



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
BAS_COUNTRY_TAX	COUNTRY_ID	created in 3.6.0	NUMBER	22	N	Country ID
BAS_COUNTRY_TAX	COUNTRY_TAX_ID	created in 3.6.0	NUMBER	22	N	Country tax id
BAS_COUNTRY_TAX	COUNTRY_TAX_RATE	created in 3.6.0	NUMBER	22	Y	Country tax rate
BAS_COUNTRY_TAX	END_DATE	created in 3.6.0	DATE	7	N	Effective till
BAS_COUNTRY_TAX	START_DATE	created in 3.6.0	DATE	7	N	Effective from
BAS_CURRENCY	CURRENCY_ISO_ID	created in 3.6.0	NUMBER	22	Y	ID of currency name according to standard
BAS_CURRENCY	CURRENCY_UPDATE_SOURCE	created in 3.6.0	NUMBER	22	Y	Currency update source
BAS_CURRENCY_ISO	-- Table --	created in 3.6.0				Currency iso codes
BAS_CURRENCY_ISO	CURRENCY_ISO_CODE	created in 3.6.0	VARCHAR2	3	N	Currency iso code
BAS_CURRENCY_ISO	CURRENCY_ISO_ID	created in 3.6.0	NUMBER	22	N	id of the currency name according to standard



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
BAS_CURRENCY_RATE	CURRENCY_RATE_UPD_SRC	created in 3.6.0	NUMBER	22	Y	Currency rate update source
BAS_CURRENCY_SOURCE	-- Table --	created in 3.6.0				List of currency update sources
BAS_CURRENCY_SOURCE	SOURCE_ID	created in 3.6.0	NUMBER	22	Y	Currency update source ID
BAS_CURRENCY_SOURCE	SOURCE_NAME	created in 3.6.0	VARCHAR2	16	Y	Currency update source name
BAS_DATETIME_FMT	ID	created in 3.6.0	NUMBER	22	Y	id
BAS_DIAL_CODE_LOAD	-- Table --	created in 3.6.0				Table for loading dial codes
BAS_DIAL_CODE_LOAD	DIAL_CODE	created in 3.6.0	VARCHAR2	16	N	Dial code
BAS_DIAL_CODE_LOAD	DIAL_CODE_COUNTRY	created in 3.6.0	VARCHAR2	256	N	Country dial code
BAS_DIAL_CODE_LOAD	DIAL_CODE_IS_HIDDEN	created in 3.6.0	NUMBER	22	Y	Is hidden flag



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
BAS_DIAL_CODE_LOAD	DIAL_CODE_REGION	created in 3.6.0	VARCHAR2	256	Y	Dial code region
BAS_DIAL_CODE_LOAD	DIAL_CODE_TYPE	created in 3.6.0	VARCHAR2	256	N	Dial code type
BAS_DIAL_CODE_MATCHER	-- Table --	deleted in 3.6.0				Dial code matching table used for rate analysis and rate compilation
BAS_DIAL_CODE_MATCHER	DIFF	deleted in 3.6.0	NUMBER	22	Y	Length difference
BAS_DIAL_CODE_MATCHER	DST_DIAL_CODE	deleted in 3.6.0	VARCHAR2	16	Y	Destination code
BAS_DIAL_CODE_MATCHER	MATCH_CODE	deleted in 3.6.0	NUMBER	22	Y	Matching code
BAS_DIAL_CODE_MATCHER	PM2	deleted in 3.6.0	NUMBER	22	Y	Matching index
BAS_DIAL_CODE_MATCHER	PM3	deleted in 3.6.0	NUMBER	22	Y	Matching index



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
BAS_DIAL_CODE_MATCHER	RIDC1	deleted in 3.6.0	ROWID	10	Y	Matching index
BAS_DIAL_CODE_MATCHER	RIDC2	deleted in 3.6.0	ROWID	10	Y	Matching index
BAS_DIAL_CODE_MATCHER	SRC_DIAL_CODE	deleted in 3.6.0	VARCHAR2	16	Y	Source code
BAS_DIAL_CODE_MATCHER_STAGE	-- Table --	deleted in 3.6.0				Intermediate table used to store data generated for bas_dial_code_matcher
BAS_DIAL_CODE_MATCHER_STAGE	DIAL_CODE	deleted in 3.6.0	VARCHAR2	16	Y	Staging code
BAS_DIAL_CODE_MATCHER_STAGE	DIAL_CODE1	deleted in 3.6.0	VARCHAR2	16	Y	Staging code
BAS_DIAL_CODE_MATCHER_STAGE	DIAL_CODE10	deleted in 3.6.0	VARCHAR2	16	Y	Staging code
BAS_DIAL_CODE_MATCHER_STAGE	DIAL_CODE11	deleted in 3.6.0	VARCHAR2	16	Y	Staging code



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
BAS_DIAL_CODE_MATCHER_STAGE	DIAL_CODE12	deleted in 3.6.0	VARCHAR2	16	Y	Staging code
BAS_DIAL_CODE_MATCHER_STAGE	DIAL_CODE13	deleted in 3.6.0	VARCHAR2	16	Y	Staging code
BAS_DIAL_CODE_MATCHER_STAGE	DIAL_CODE14	deleted in 3.6.0	VARCHAR2	16	Y	Staging code
BAS_DIAL_CODE_MATCHER_STAGE	DIAL_CODE15	deleted in 3.6.0	VARCHAR2	16	Y	Staging code
BAS_DIAL_CODE_MATCHER_STAGE	DIAL_CODE2	deleted in 3.6.0	VARCHAR2	16	Y	Staging code
BAS_DIAL_CODE_MATCHER_STAGE	DIAL_CODE3	deleted in 3.6.0	VARCHAR2	16	Y	Staging code
BAS_DIAL_CODE_MATCHER_STAGE	DIAL_CODE4	deleted in 3.6.0	VARCHAR2	16	Y	Staging code
BAS_DIAL_CODE_MATCHER_STAGE	DIAL_CODE5	deleted in 3.6.0	VARCHAR2	16	Y	Staging code



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
BAS_DIAL_CODE_MATCHER_STAGE	DIAL_CODE6	deleted in 3.6.0	VARCHAR2	16	Y	Staging code
BAS_DIAL_CODE_MATCHER_STAGE	DIAL_CODE7	deleted in 3.6.0	VARCHAR2	16	Y	Staging code
BAS_DIAL_CODE_MATCHER_STAGE	DIAL_CODE8	deleted in 3.6.0	VARCHAR2	16	Y	Staging code
BAS_DIAL_CODE_MATCHER_STAGE	DIAL_CODE9	deleted in 3.6.0	VARCHAR2	16	Y	Staging code
BAS_DIAL_CODE_MATCHER_STAGE	DIAL_CODE_COUNTRY	deleted in 3.6.0	VARCHAR2	256	Y	Staging code country
BAS_DIAL_CODE_MATCHER_STAGE	DIAL_CODE_DESTINATION	deleted in 3.6.0	VARCHAR2	772	Y	Staging code destination
BAS_DIAL_CODE_MATCHER_STAGE	DIAL_CODE_REGION	deleted in 3.6.0	VARCHAR2	256	Y	Staging code region
BAS_DIAL_CODE_MATCHER_STAGE	DIAL_CODE_TYPE	deleted in 3.6.0	VARCHAR2	256	Y	Staging code type



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
BAS_DIAL_CODE_MATCHER_STAGE	RID	deleted in 3.6.0	ROWID	10	Y	Index
BAS_DID_BILL_SCHEME	CHARGE_FULL_MRC	created in 3.6.0	NUMBER	22	Y	Charge full MRC (0 or null - no / 1 - yes)
BAS_DID_BILL_SCHEME	CHARGE_NRC_IMMEDIATELY	created in 3.6.0	NUMBER	22	Y	Issue NRC charges immediately (0 or null - no / 1 - yes)
BAS_DID_DIAL_CODE	ADDED	created in 3.6.0	DATE	7	Y	Date added
BAS_DID_DIAL_CODE	CLI_ACCOUNT_ID	created in 3.6.0	NUMBER	22	Y	SMS client account id
BAS_DID_DIAL_CODE	FWD_ANI	created in 3.6.0	NUMBER	22	Y	Forward ANI
BAS_DID_DIAL_CODE	FWD_DNIS	created in 3.6.0	NUMBER	22	Y	Forward POI, numbers only
BAS_DID_DIAL_CODE	FWD_POI_ID	created in 3.6.0	NUMBER	22	Y	POIs belonging to the selected product, required when selecting Forward product.



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
BAS_DID_DIAL_CODE	FWD_PROD_ID	created in 3.6.0	NUMBER	22	Y	Only DID loop vendor products can be selected.
BAS_DID_DIAL_CODE	ROUTING_MODE	created in 3.6.0	NUMBER	22	Y	The routing mode of a specific number. (Standard/Forward/Failover)
BAS_INCOMING_MAIL	BODY	created in 3.6.0	CLOB	4000	Y	Mail body
BAS_MANAGER_ACC	-- Table --	created in 3.6.0				Managers
BAS_MANAGER_ACC	ACC_ID	created in 3.6.0	NUMBER	22	N	Account ID account id
BAS_MANAGER_ACC	MANAGER_NAME	created in 3.6.0	VARCHAR2	1000	Y	Manager name
BAS_MANAGER_ACC	MAN_ACC_ID	created in 3.6.0	NUMBER	22	N	Manager acc id
BAS_MANAGER_ACC	START_DATE	created in 3.6.0	DATE	7	N	Effective from
BAS_MENU	MENU_ITEM_ROLE_CODE	changed in 3.6.0	VARCHAR2	30	Y	Role code required to access this menu item



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
BAS_PASSWORD_LIST	-- Table --	created in 3.6.0				Password list
BAS_PASSWORD_LIST	PASSWORD	created in 3.6.0	VARCHAR2	256	N	password
BAS_PAYSYSTEM_WEBHOOK	-- Table --	created in 3.6.0				Paysystem webhooks
BAS_PAYSYSTEM_WEBHOOK	CC_ID	created in 3.6.0	NUMBER	22	N	CC ID
BAS_PAYSYSTEM_WEBHOOK	PAYSYSTEM_NAME	created in 3.6.0	VARCHAR2	100	N	Paysystem name
BAS_PAYSYSTEM_WEBHOOK	WEBHOOK_ID	created in 3.6.0	VARCHAR2	100	N	Webhook ID
BAS_PAYSYSTEM_WEBHOOK	WEBHOOK_KEY	created in 3.6.0	VARCHAR2	250	Y	Webhook key
BAS_PAYSYSTEM_WEBHOOK	WEBHOOK_URL	created in 3.6.0	VARCHAR2	1000	Y	Webhook URL



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
BAS_PAY_POST_PROC_FIELD	-- Table --	created in 3.6.0				Fiscal data operator list
BAS_PAY_POST_PROC_FIELD	POST_PROC_FIELD_NAME	created in 3.6.0	VARCHAR2	4000	N	Fiscal data operator parameter name
BAS_PAY_POST_PROC_FIELD	POST_PROC_NAME	created in 3.6.0	VARCHAR2	100	Y	Fiscal data operator name
BAS_PAY_POST_PROC_FIELD_VAL	-- Table --	created in 3.6.0				Fiscal data operator parameters values
BAS_PAY_POST_PROC_FIELD_VAL	CC_ID	created in 3.6.0	NUMBER	22	Y	Contract company ID
BAS_PAY_POST_PROC_FIELD_VAL	PAYSYSTEM_NAME	created in 3.6.0	VARCHAR2	100	Y	Paysystem name
BAS_PAY_POST_PROC_FIELD_VAL	POST_PROC_FIELD_NAME	created in 3.6.0	VARCHAR2	4000	Y	Fiscal data operator parameter name
BAS_PAY_POST_PROC_FIELD_VAL	POST_PROC_FIELD_VALUE	created in 3.6.0	VARCHAR2	4000	Y	Fiscal data operator parameter value



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
BAS_PRODUCT	DELIVERY_REROUTING_TIMEOUT	created in 3.6.0	NUMBER	22	Y	Maximum shift for rewriting, minutes. Only for client sms products.
BAS_PRODUCT	FORCE_ORIGIN_INCR	created in 3.6.0	NUMBER	22	Y	Force using origin-based increments (null - no, 1 - yes)
BAS_PRODUCT	IM_CHANNEL_ID	created in 3.6.0	NUMBER	22	Y	ID im-channel
BAS_PRODUCT	RETAIL_PRODUCT	created in 3.6.0	NUMBER	22	Y	Use the product in the Campaign portal (0 - do not use, 1 - use)



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
BAS_PRODUCT	SEND_IMPORT_RESULT	created in 3.6.0	NUMBER	22	Y	Indicates whether to launch rate export to the managers email account for this product after a successful rate import. Only for International, US domestic, DID and SMS product types. Flag: 1 - start exporting, everything else - do not start.
BAS_PRODUCT	USE_ANI_BILLING	changed in 3.6.0	NUMBER	22	Y	Check ANI fields in rates
BAS_PRODUCT	USE_SENDER_MCCMNC_RATES	created in 3.6.0	NUMBER	22	Y	Billing mode based on A number
BAS_PRODUCT	USE_VERIFY_SMS	deleted in 3.6.0	NUMBER	22	Y	Google VerifySMS usage flag (1 - active, 0 or null - inactive)
BAS_PRODUCT_TYPE	FINANCE_ONLY	changed in 3.6.0	NUMBER	22	Y	Can create products of this type (1 - yes, 2 - no)



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
BAS_PRODUCT_TYPE	USE_VOLUME_FOR_CHARGES	created in 3.6.0	NUMBER	22	Y	Use volume for charges in invoice (1 - yes, 0 - no)
BAS_REGEX	GROUP_ID	created in 3.6.0	NUMBER	22	N	Group id
BAS_REGION	REGION_MANAGER_USER_ID	created in 3.6.0	NUMBER	22	Y	Region manager id
BAS_REGION_MANAGER	-- Table --	created in 3.6.0				Region managers
BAS_REGION_MANAGER	REGION_ID	created in 3.6.0	NUMBER	22	N	Region ID (primary key)
BAS_REGION_MANAGER	REGION_MANAGER_USER_ID	created in 3.6.0	NUMBER	22	Y	Region manager id
BAS_RESET_PWD	RESET_ATTEMPT	created in 3.6.0	NUMBER	22	Y	Increasing delay between password reset attempts
BAS_SIMULATION	ANI_DIAL_CODE	created in 3.6.0	VARCHAR2	256	Y	ANI Dial code
BAS_SIMULATION	HLR_RATE	created in 3.6.0	NUMBER	22	Y	HLR rate



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
BAS_TEMPLATE_TYPE	TEMPLATE_TYPE_HIDDEN	created in 3.6.0	NUMBER	22	Y	Whether to hide the template type in the web: 1 - hide, null - do not hide
BAS_USER	IS_SYSTEM	created in 3.6.0	NUMBER	22	Y	System user
BAS_USER	MANAGER_ANALYTICS_VIEW	created in 3.6.0	NUMBER	22	Y	The attribute is responsible for displaying sales analytics
BAS_USER_ACCESS	-- Table --	created in 3.6.0				Access list
BAS_USER_ACCESS	ACCESS_CODE	created in 3.6.0	VARCHAR2	256	N	Access code
BAS_USER_ACCESS	ACCESS_EXPLICIT	created in 3.6.0	NUMBER	22	N	Explicit flag
BAS_USER_ACCESS	ACCESS_OUT_OF_SCOPE	created in 3.6.0	NUMBER	22	N	Out of scope flag
BAS_USER_ACCESS	ACCESS_USER_ID	created in 3.6.0	NUMBER	22	Y	User ID
BAS_USER_ACCESS	ACC_ID	created in 3.6.0	NUMBER	22	Y	Account ID account id



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
BAS_USER_ACCESS	CAR_ID	created in 3.6.0	NUMBER	22	Y	Carrier ID Alert group carrier
BAS_USER_ACCESS	PRODUCT_ID	created in 3.6.0	NUMBER	22	Y	Product ID
BAS_USER_CC	-- Table --	changed in 3.6.0				User's contract companies
BAS_VOIP_POI	VOIP_POI_RTP_TYPE	created in 3.6.0	NUMBER	22	N	RTP type: 0 - default (off), 1 - open rtp type, 2 - close rtp type
CLP_CDR_EXPORT_TMP	-- Table --	created in 3.6.0				Temporary table for cdr export
CLP_EDR_EXPORT_TMP	-- Table --	created in 3.6.0				Temporary table for edr export
CLP_PAYMENT_METHOD	-- Table --	created in 3.6.0				Campaign portal payment methods
CLP_PAYMENT_METHOD	CARDHOLDER	created in 3.6.0	VARCHAR2	100	N	Cardholder
CLP_PAYMENT_METHOD	CARD_NUMBER	created in 3.6.0	VARCHAR2	20	N	Card number



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
CLP_PAYMENT_METHOD	CVV	created in 3.6.0	VARCHAR2	3	Y	CVV
CLP_PAYMENT_METHOD	EXP_MONTH	created in 3.6.0	VARCHAR2	2	N	Expiration month
CLP_PAYMENT_METHOD	EXP_YEAR	created in 3.6.0	VARCHAR2	4	N	Expiration year
CLP_PAYMENT_METHOD	IS_DEFAULT	created in 3.6.0	NUMBER	22	N	Is default
CLP_PAYMENT_METHOD	METHOD_ID	created in 3.6.0	NUMBER	22	N	Method id
CLP_PAYMENT_METHOD	USER_ID	created in 3.6.0	NUMBER	22	N	User numeric ID (primary key) Manager User-creator
CLP_REPLY_TEMPL	-- Table --	created in 3.6.0				Campaign portal reply templates
CLP_REPLY_TEMPL	CAR_ID	created in 3.6.0	NUMBER	22	Y	Carrier ID Alert group carrier
CLP_REPLY_TEMPL	REPLY_TEMPL_ID	created in 3.6.0	NUMBER	22	N	Reply template
CLP_REPLY_TEMPL	REPLY_TEMPL_NAME	created in 3.6.0	VARCHAR2	256	N	Reply template name



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
CLP_REPLY_TEMPL_OPTION	-- Table --	created in 3.6.0				Campaign portal reply template options
CLP_REPLY_TEMPL_OPTION	ID	created in 3.6.0	NUMBER	22	N	ID
CLP_REPLY_TEMPL_OPTION	KEY_WORD	created in 3.6.0	VARCHAR2	4000	N	Keyword
CLP_REPLY_TEMPL_OPTION	KEY_WORD_TYPE	created in 3.6.0	VARCHAR2	10	Y	Keyword type
CLP_REPLY_TEMPL_OPTION	PRIORITY	created in 3.6.0	NUMBER	22	Y	Priority
CLP_REPLY_TEMPL_OPTION	REPLY_TEMPL_ID	created in 3.6.0	NUMBER	22	N	Reply template
CLP_REPLY_TEMPL_OPTION	REPLY_TEXT	created in 3.6.0	VARCHAR2	4000	Y	Reply text
CLP_TAG	IS_DEFAULT	created in 3.6.0	NUMBER	22	N	Is default



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
CLP_TAG	TYPE	created in 3.6.0	NUMBER	22	N	type
CLP_VOX_EXPORT_TMP	-- Table --	created in 3.6.0				Temporary table for export voip cdr
DOC_CONFIRMATION	-- Table --	created in 3.6.0				Document confirmation
DOC_CONFIRMATION	CNFRM_COMMENT	created in 3.6.0	VARCHAR2	4000	Y	Confirmation comment
DOC_CONFIRMATION	CNFRM_DATE	created in 3.6.0	DATE	7	Y	Confirmation date
DOC_CONFIRMATION	CNFRM_HASH	created in 3.6.0	VARCHAR2	64	N	Confirmation hash
DOC_CONFIRMATION	CNFRM_STATUS	created in 3.6.0	VARCHAR2	16	Y	Confirmation status
DOC_CONFIRMATION	DOC_ID	created in 3.6.0	NUMBER	22	Y	Document ID (primary key)
DOC_CONFIRMATION	TASK_NAME	created in 3.6.0	VARCHAR2	256	Y	Task name
DOC_MAIL	MAIL_ATTACHMENT_DOC_ID	created in 3.6.0	NUMBER	22	Y	ID of attached document



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
DOC_MAIL	MAIL_SERVER_TYPE_ID	changed in 3.6.0	NUMBER	22	Y	Mail server type ID
DOC_MAIL	MAIL_SIGNATURE	created in 3.6.0	CLOB	4000	Y	Mail signature (image in base64)
E164_IMP_SRC	-- Table --	created in 3.6.0				Temporary table for import e.164 records
E164_IMP_SRC	COUNTRY_DIAL_CODE	created in 3.6.0	VARCHAR2	4000	Y	Country prefix dial code
E164_IMP_SRC	COUNTRY_NAME	created in 3.6.0	VARCHAR2	4000	Y	Country name
E164_IMP_SRC	DSC	created in 3.6.0	VARCHAR2	4000	Y	Description description
E164_IMP_SRC	E164_1	created in 3.6.0	VARCHAR2	4000	Y	E164 first part
E164_IMP_SRC	E164_2	created in 3.6.0	VARCHAR2	4000	Y	E164 second part
E164_IMP_SRC	E164_3	created in 3.6.0	VARCHAR2	4000	Y	E164 third part
E164_IMP_SRC	E164_END	created in 3.6.0	VARCHAR2	4000	Y	E164 end



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
E164_IMP_SRC	E164_START	created in 3.6.0	VARCHAR2	4000	Y	E164 start
E164_IMP_SRC	E212	created in 3.6.0	VARCHAR2	4000	Y	MCCMNC
E164_IMP_SRC	END_DATE	created in 3.6.0	VARCHAR2	4000	Y	Effective till
E164_IMP_SRC	LINE	created in 3.6.0	NUMBER	22	N	Import line
E164_IMP_SRC	LOT	created in 3.6.0	VARCHAR2	4000	Y	LOT Level of trust (from 0 to 100) trust: from 100
E164_IMP_SRC	MCC	created in 3.6.0	VARCHAR2	4000	Y	Mcc
E164_IMP_SRC	MNC	created in 3.6.0	VARCHAR2	4000	Y	Mnc
E164_IMP_SRC	NET_NAME	created in 3.6.0	VARCHAR2	4000	Y	Network name
E164_IMP_SRC	START_DATE	created in 3.6.0	VARCHAR2	4000	Y	Effective from
EDR_MASKING_RULES	-- Table --	created in 3.6.0				EDR masking rules
EDR_MASKING_RULES	CDR_CALLED_LIST	created in 3.6.0	VARCHAR2	4000	Y	Cdr called list



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
EDR_MASKING_RULES	CREATED	created in 3.6.0	DATE	7	Y	Creation date Alert group create time Created Create
EDR_MASKING_RULES	CREATED_BY	created in 3.6.0	VARCHAR2	256	Y	Created by User who created the object
EDR_MASKING_RULES	END_DATE	created in 3.6.0	DATE	7	Y	Effective till
EDR_MASKING_RULES	LAST_EXEC_DATE	created in 3.6.0	DATE	7	Y	Last execution date Previous
EDR_MASKING_RULES	LAST_UPDATED	created in 3.6.0	DATE	7	Y	Last updated date update
EDR_MASKING_RULES	LAST_UPDATED_BY	created in 3.6.0	VARCHAR2	256	Y	Last updated by update date
EDR_MASKING_RULES	NEXT_EXEC_DATE	created in 3.6.0	DATE	7	Y	Next execution date
EDR_MASKING_RULES	PERIOD_TYPE	created in 3.6.0	NUMBER	22	Y	Period: 1 - hour, 2 day, 3 week, 4 month



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
EDR_MASKING_RULES	RULE_CLIENT_PRODUCT_LIST	created in 3.6.0	VARCHAR2	4000	Y	List of client product IDs separated by comma Rule list
EDR_MASKING_RULES	RULE_CLIENT_PRODUCT_SCOPE	created in 3.6.0	NUMBER	22	N	Client product scope: 1 - inclusive, -1 exclusive, 0 - all
EDR_MASKING_RULES	RULE_ID	created in 3.6.0	NUMBER	22	N	Routing rule ID Rule (primary key) rule_id id
EDR_MASKING_RULES	RULE_NAME	created in 3.6.0	VARCHAR2	256	Y	Rule name (description)
EDR_MASKING_RULES	SCHEDULE	created in 3.6.0	VARCHAR2	256	Y	Preset schedule Schedule in the flesh
EDR_MASKING_RULES	START_DATE	created in 3.6.0	DATE	7	Y	Effective from
FIN_CHARGE	CHARGE_ISSUE_DATE	created in 3.6.0	DATE	7	Y	Charge issue date
FIN_CHARGE_BACKUP	-- Table --	created in 3.6.0				Charges backup



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
FIN_CHARGE_BACKUP	CHARGE_ACC_ID	created in 3.6.0	NUMBER	22	N	Link to account ID (link to BAS_ACCOUNT table)
FIN_CHARGE_BACKUP	CHARGE_AMOUNT	created in 3.6.0	NUMBER	22	N	Charge amount
FIN_CHARGE_BACKUP	CHARGE_CURRENCY_CODE	created in 3.6.0	VARCHAR2	16	N	Currency_code
FIN_CHARGE_BACKUP	CHARGE_DIRECTION	created in 3.6.0	NUMBER	22	N	Direction: 0 - to partner, 1 - from partner
FIN_CHARGE_BACKUP	CHARGE_END_DATE	created in 3.6.0	DATE	7	N	Charge end date
FIN_CHARGE_BACKUP	CHARGE_ID	created in 3.6.0	NUMBER	22	N	Charge ID
FIN_CHARGE_BACKUP	CHARGE_INV_ID	created in 3.6.0	NUMBER	22	Y	Invoice ID (link to FIN_INVOICE table)
FIN_CHARGE_BACKUP	CHARGE_LAST_UPDATE_DATE	created in 3.6.0	DATE	7	N	Charge last update date
FIN_CHARGE_BACKUP	CHARGE_RATES_BASED_ON	created in 3.6.0	NUMBER	22	Y	Rate based on option



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
FIN_CHARGE_BACKUP	CHARGE_SERVICE_CNT	created in 3.6.0	NUMBER	22	Y	Service count
FIN_CHARGE_BACKUP	CHARGE_START_DATE	created in 3.6.0	DATE	7	N	Charge start date
FIN_CHARGE_BACKUP	CHARGE_SYS_END_DATE	created in 3.6.0	DATE	7	N	Charge system end date
FIN_CHARGE_BACKUP	CHARGE_SYS_START_DATE	created in 3.6.0	DATE	7	N	Charge system start date
FIN_CHARGE_BACKUP	CHARGE_TRN_ID	created in 3.6.0	NUMBER	22	Y	Transaction ID
FIN_CHARGE_BACKUP	CHARGE_TYPE_ID	created in 3.6.0	NUMBER	22	N	Charge type
FIN_CHARGE_BACKUP	CHARGE_VOLUME	created in 3.6.0	NUMBER	22	Y	Volume
FIN_CHARGE_DETAIL	DET_AMOUNT_WITH_TAX	created in 3.6.0	NUMBER	22	Y	Amount with tax
FIN_CHARGE_DETAIL	DET_COLUMNS5	changed in 3.6.0	VARCHAR2	4000	Y	SMS dial code
FIN_CHARGE_DETAIL	DET_TAX_RATE	created in 3.6.0	NUMBER	22	Y	Tax rate



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
FIN_CHARGE_DETAIL_BA CKUP	-- Table --	created in 3.6.0				Charge details backup
FIN_CHARGE_DETAIL_BA CKUP	DET_CHARGE_ID	created in 3.6.0	NUMBER	22	N	Record ID
FIN_CHARGE_DETAIL_BA CKUP	DET_COLUMN1	created in 3.6.0	VARCHAR2	4000	N	Details column 1
FIN_CHARGE_DETAIL_BA CKUP	DET_COLUMN2	created in 3.6.0	VARCHAR2	4000	Y	Details column 2
FIN_CHARGE_DETAIL_BA CKUP	DET_PRODUCT_ID	created in 3.6.0	NUMBER	22	Y	Product ID
FIN_CHARGE_DETAIL_BA CKUP	DET_SERVICE_AMOUN T	created in 3.6.0	NUMBER	22	N	Amount
FIN_CHARGE_DETAIL_BA CKUP	DET_SERVICE_CNT	created in 3.6.0	NUMBER	22	N	Service count
FIN_CHARGE_DETAIL_BA CKUP	DET_SERVICE_RATE	created in 3.6.0	NUMBER	22	N	Rate



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
FIN_CHARGE_DETAIL_BACKUP	DET_SERVICE_RATE_ID	created in 3.6.0	NUMBER	22	Y	Rate ID
FIN_INVOICE	CORRECTION_INV_REF_CODE	created in 3.6.0	VARCHAR2	4000	Y	Correction to invoice ref code
FIN_INVOICE	INV_PREV_BALANCE_WOEXPIRED	created in 3.6.0	NUMBER	22	Y	Previous Balance without expired
FIN_INVOICE_BACKUP	-- Table --	created in 3.6.0				Invoice backup
FIN_INVOICE_BACKUP	INV_ACC_ID	created in 3.6.0	NUMBER	22	N	Invoice account ID (link to BAS_ACCOUNT table)
FIN_INVOICE_BACKUP	INV_AUTO_GENERATED_ATTACH	created in 3.6.0	NUMBER	22	N	Auto generated attachment: 1 - auto, 0 - manual
FIN_INVOICE_BACKUP	INV_CAPTION	created in 3.6.0	VARCHAR2	481	Y	Invoice caption
FIN_INVOICE_BACKUP	INV_DETAILS_FILENAME	created in 3.6.0	VARCHAR2	256	Y	Invoice details filename



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
FIN_INVOICE_BACKUP	INV_DIRECTION	created in 3.6.0	NUMBER	22	N	Invoice direction (0 - due to partner, 1 - due to system owner)
FIN_INVOICE_BACKUP	INV_DISPUTED_AMOUNT	created in 3.6.0	NUMBER	22	Y	Difference between internal and partner data
FIN_INVOICE_BACKUP	INV_DOC_ID	created in 3.6.0	NUMBER	22	Y	Invoice file link
FIN_INVOICE_BACKUP	INV_DUE_DATE	created in 3.6.0	DATE	7	Y	Invoice due date
FIN_INVOICE_BACKUP	INV_END_DATE	created in 3.6.0	DATE	7	Y	Invoice period end date (in partner timezone)
FIN_INVOICE_BACKUP	INV_ESTIMATED_AMOUNT	created in 3.6.0	NUMBER	22	N	Invoice total amount
FIN_INVOICE_BACKUP	INV_ID	created in 3.6.0	NUMBER	22	N	Invoice ID
FIN_INVOICE_BACKUP	INV_ISSUE_DATE	created in 3.6.0	DATE	7	Y	Invoice issue date
FIN_INVOICE_BACKUP	INV_LAST_UPDATED	created in 3.6.0	DATE	7	Y	Date of last invoice recalculation



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
FIN_INVOICE_BACKUP	INV_NOTES	created in 3.6.0	VARCHAR2	256	Y	Invoice notes
FIN_INVOICE_BACKUP	INV_OUTDATED	created in 3.6.0	NUMBER	22	N	Invoice outdated
FIN_INVOICE_BACKUP	INV_PAID_AMOUNT	created in 3.6.0	NUMBER	22	N	Amount paid towards this invoice. Invoice is fully paid if estimation amount = disputed amount + paid amount
FIN_INVOICE_BACKUP	INV_PAY_STATUS_ID	created in 3.6.0	NUMBER	22	N	Invoice payment status ID
FIN_INVOICE_BACKUP	INV_PRESENTED_AMOUNT	created in 3.6.0	NUMBER	22	Y	For client invoice: presented always = estimated - disputed. For vendor inv: amount calculated from traffic
FIN_INVOICE_BACKUP	INV_PREV_BALANCE	created in 3.6.0	NUMBER	22	N	Account balance prior to invoice generation
FIN_INVOICE_BACKUP	INV_REF_CODE	created in 3.6.0	VARCHAR2	256	Y	Invoice reference number



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
FIN_INVOICE_BACKUP	INV_START_DATE	created in 3.6.0	DATE	7	Y	Invoice period from date (in partner timezone)
FIN_INVOICE_BACKUP	INV_STATUS_ID	created in 3.6.0	NUMBER	22	N	Invoice status ID
FIN_INVOICE_BACKUP	INV_SYS_END_DATE	created in 3.6.0	DATE	7	Y	Invoice period end date (in system timezone)
FIN_INVOICE_BACKUP	INV_SYS_START_DATE	created in 3.6.0	DATE	7	Y	Invoice period start date (in system timezone)
FIN_INVOICE_BACKUP	INV_TYPE_ID	created in 3.6.0	NUMBER	22	N	Invoice type ID
FIN_SUBSCR	NEED_RECALC	created in 3.6.0	VARCHAR2	1	Y	Flag for fee recalculation
FIN_SUBSCR	SUBSCR_CONFIRM_CHARGE	changed in 3.6.0	NUMBER	22	N	Confirm invoice
FIN_SUBSCR	SUBSCR_MODE	changed in 3.6.0	NUMBER	22	N	Generation type (at the beginning/end of billing period)
FIN_SUBSCR	SUBSCR_RATE	deleted in 3.6.0	NUMBER	22	N	Rate



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
FIN_SUBSCR	SUBSCR_VOLUME	deleted in 3.6.0	NUMBER	22	N	Volume
FIN_SUBSCR_DETAIL	DCHECK	changed in 3.6.0	DATE	7	Y	date of charging
FIN_SUBSCR_DETAIL	SUBSCR_SUPPRESSED	created in 3.6.0	NUMBER	22	Y	Suppressed flag (1 - yes, null - no)
FIN_SUBSCR_DETAIL	USAGE_ID	created in 3.6.0	NUMBER	22	Y	usage id
FIN_SUBSCR_PERIOD	-- Table --	created in 3.6.0				Subscriptions/recurring fee periods
FIN_SUBSCR_PERIOD	END_DATE	created in 3.6.0	DATE	7	Y	Period end date
FIN_SUBSCR_PERIOD	RATE	created in 3.6.0	NUMBER	22	Y	Rate
FIN_SUBSCR_PERIOD	START_DATE	created in 3.6.0	DATE	7	N	Period start date
FIN_SUBSCR_PERIOD	SUBSCR_ID	created in 3.6.0	NUMBER	22	N	Fee ID
FIN_SUBSCR_PERIOD	VOLUME	created in 3.6.0	NUMBER	22	Y	Volume



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
FIN_SUBSCR_PERIOD_TMP	-- Table --	created in 3.6.0				Temporary table for recurring fee
FIN_USAGE	USAGE_DIRECTION	changed in 3.6.0	NUMBER	22	N	Usage direction: 0 - client, 1 - vendor)
IM_CHANNEL_CARRIER_SETTING	-- Table --	created in 3.6.0				IM channel carrier settings
IM_CHANNEL_CARRIER_SETTING	CAR_ID	created in 3.6.0	NUMBER	22	N	Carrier ID Alert group carrier
IM_CHANNEL_CARRIER_SETTING	IM_CHANNEL_ID	created in 3.6.0	NUMBER	22	N	ID im-channel of IM-channel
IM_CHANNEL_CARRIER_SETTING	IM_TTL	created in 3.6.0	NUMBER	22	Y	Current TTL is seconds
LOG_BAS_BALANCE	-- Table --	created in 3.6.0				Partner balances
LOG_BAS_BALANCE	ACC_BALANCE	created in 3.6.0	NUMBER	22	N	Current balance



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
LOG_BAS_BALANCE	ACC_BALANCE_UPDATED	created in 3.6.0	DATE	7	Y	Last updated date
LOG_BAS_BALANCE	ACC_ID	created in 3.6.0	NUMBER	22	N	Account ID
LOG_BAS_BALANCE	EXEC_ID	created in 3.6.0	NUMBER	22	Y	exec id
LOG_BAS_BALANCE	LOG_ACTION	created in 3.6.0	VARCHAR2	4	N	Log action
LOG_BAS_BALANCE	LOG_ID	created in 3.6.0	NUMBER	22	Y	log id
LOG_BAS_BALANCE	LOG_TIME	created in 3.6.0	DATE	7	N	Log time
LOG_BAS_BALANCE	SESSION_ID	created in 3.6.0	NUMBER	22	Y	session id
LOG_BAS_BALANCE	SUBMIT_ID	created in 3.6.0	NUMBER	22	Y	submit id (for retrospection)
LOG_SMS_EMA_ASR	-- Table --	created in 3.6.0				SMS EMA statistics (send rate) log



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
LOG_SMS_EMA_DLR	-- Table --	created in 3.6.0				SMS EMA statistics (delivery rate) log
PRV_ABSTRACT_TABLE	-- Table --	created in 3.6.0				Internal temporary table
PRV_API_METHOD	API_MSG_CODE	created in 3.6.0	VARCHAR2	264	Y	Message code for method description
PRV_API_RESOURCE	IS_HIDDEN	created in 3.6.0	NUMBER	22	Y	1 - hidden, 0 - not hidden
PRV_CUBE_STAGE_TAB	-- Table --	created in 3.6.0				Staging table list for analytical cubes
PRV_CUBE_STAGE_TAB	CREATE_DATE	created in 3.6.0	DATE	7	Y	Staging table creation date
PRV_CUBE_STAGE_TAB	SRC_TAB_DATE	created in 3.6.0	DATE	7	Y	Source cube table partition date
PRV_CUBE_STAGE_TAB	SRC_TAB_NAME	created in 3.6.0	VARCHAR2	256	Y	Source cube table name
PRV_CUBE_STAGE_TAB	STG_TAB_NAME	created in 3.6.0	VARCHAR2	256	N	Staging table name



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
PRV_DB_COMMENTS_HISTORY	-- Table --	created in 3.6.0				Table comments history
PRV_DB_COMMENTS_HISTORY	COLUMN_NAME	created in 3.6.0	VARCHAR2	32	N	Column name
PRV_DB_COMMENTS_HISTORY	COMMENTS	created in 3.6.0	VARCHAR2	1024	Y	Comment
PRV_DB_COMMENTS_HISTORY	DATA_LENGTH	created in 3.6.0	NUMBER	22	Y	Data length
PRV_DB_COMMENTS_HISTORY	DATA_TYPE	created in 3.6.0	VARCHAR2	32	Y	Data type
PRV_DB_COMMENTS_HISTORY	NULLABLE	created in 3.6.0	VARCHAR2	1	Y	Flag: 1 - field can be null, 0 null means undefined
PRV_DB_COMMENTS_HISTORY	PN	created in 3.6.0	VARCHAR2	256	N	Patch number
PRV_DB_COMMENTS_HISTORY	TABLE_NAME	created in 3.6.0	VARCHAR2	64	N	Table name Analytic cube table



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
PRV_DEBUG	BACKTRACE	created in 3.6.0	VARCHAR2	4000	Y	Call stack
PRV_DML_MSG	-- Table --	deleted in 3.6.0				Advanced queue DML messages
PRV_EXP_MARK_TMP	-- Table --	created in 3.6.0				Temporary table for markers
PRV_JOB_THREAD	THREAD_JOB	created in 3.6.0	VARCHAR2	128	Y	Thread job
PRV_LAST_FAILED_QUERY	ID	created in 3.6.0	NUMBER	22	Y	ID
PRV_LAST_FAILED_QUERY	NAME	created in 3.6.0	VARCHAR2	4000	Y	Method name
PRV_LAST_FAILED_QUERY	TS	created in 3.6.0	TIMESTAMP(6)	11	Y	Date
PRV_LOCK_HIST	-- Table --	created in 3.6.0				RESTMAN locks history
PRV_LOCK_HIST	ADD_DATE	created in 3.6.0	TIMESTAMP(6)	11	N	From date



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
PRV_LOCK_HIST	COST	created in 3.6.0	NUMBER	22	Y	Vendor average cost Cost
PRV_LOCK_HIST	ID	created in 3.6.0	NUMBER	22	N	ID
PRV_LOCK_HIST	IM_CHANNEL	created in 3.6.0	VARCHAR2	1000	N	IM channel
PRV_LOCK_HIST	LAST_UNLOCK_DATE	created in 3.6.0	DATE	7	Y	Last unlock date
PRV_LOCK_HIST	MESSAGE_ID	created in 3.6.0	VARCHAR2	65	N	Client message ID SMS Message text
PRV_LOCK_HIST	PACK_ID	created in 3.6.0	NUMBER	22	Y	Pack ID ORA error type
PRV_LOCK_HIST	PRODUCT_ID	created in 3.6.0	NUMBER	22	Y	Product ID
PRV_LOCK_HIST	RATE_ID	created in 3.6.0	NUMBER	22	Y	rate_id Rate ID (primary key) Client POI SMS rate
PRV_LOCK_HIST	RELEASE_DATE	created in 3.6.0	TIMESTAMP(6)	11	Y	Release date
PRV_LOCK_HIST	RELEASE_REASON	created in 3.6.0	VARCHAR2	200	Y	Release reason



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
PRV_LOCK_HIST	SUBSCR_ID	created in 3.6.0	NUMBER	22	Y	Fee ID Subscription
PRV_LOCK_HIST	TILL_DATE	created in 3.6.0	TIMESTAMP(6)	11	Y	Till date
PRV_LOG_BOOKMARK	-- Table --	deleted in 3.6.0				Last IDs used for log generation
PRV_LOG_BOOKMARK	DCHECK	deleted in 3.6.0	DATE	7	Y	Last check date
PRV_LOG_BOOKMARK	LOG_ID	deleted in 3.6.0	NUMBER	22	Y	Log ID
PRV_LOG_BOOKMARK	SCN	deleted in 3.6.0	NUMBER	22	Y	SCN
PRV_LOG_BOOKMARK	TABLE_NAME	deleted in 3.6.0	VARCHAR2	30	Y	Table name
PRV_MAIL_QUEUE	SIGNATURE	created in 3.6.0	CLOB	4000	Y	Mail signature (image in base64)
PRV_MAIL_SERVER	CLIENT_ID	created in 3.6.0	VARCHAR2	256	Y	Tocken client ID
PRV_MAIL_SERVER	CLIENT_SECRET	created in 3.6.0	VARCHAR2	256	Y	Tocken client_secret



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
PRV_MAIL_SERVER	MAIL_CC_ID	changed in 3.6.0	NUMBER	22	Y	Contract company ID
PRV_MAIL_SERVER	OAUTH2TOKEN	created in 3.6.0	VARCHAR2	2048	Y	Token oauth
PRV_MANUAL_QUEUE	-- Table --	created in 3.6.0				Events queue
PRV_MANUAL_QUEUE	ENQ_TIME	created in 3.6.0	TIMESTAMP(6)	11	Y	Queue messages column enq_time
PRV_MANUAL_QUEUE	EVENT_TYPE	created in 3.6.0	VARCHAR2	256	Y	Event type
PRV_MANUAL_QUEUE	PAYLOAD	created in 3.6.0	VARCHAR2	4000	Y	Payload
PRV_MANUAL_QUEUE	SYS_TYPE	created in 3.6.0	VARCHAR2	256	Y	Event system type
PRV_RESULT_TMP	-- Table --	created in 3.6.0				Temporary table for standby server
PRV_SE_SEQUENCE_SNA PSHOT	-- Table --	created in 3.6.0				Recovery sequence snapshot



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
PRV_SE_SEQUENCE_SNA PSHOT	LAST_NUMBER	created in 3.6.0	NUMBER	22	Y	Last number
PRV_SE_SEQUENCE_SNA PSHOT	SEQUENCE_NAME	created in 3.6.0	VARCHAR2	128	N	Sequence name
PRV_STATE	-- Table --	created in 3.6.0				System state
PRV_STATE	PARAM_CODE	created in 3.6.0	VARCHAR2	256	N	Parameter name (primary key)
PRV_STATE	PARAM_IS_HIDDEN	created in 3.6.0	NUMBER	22	N	Flag: 1 - hidden, 0 - not hidden
PRV_STATE	PARAM_LAST_UPDATE D	created in 3.6.0	DATE	7	Y	Last change date
PRV_STATE	PARAM_VALIDATION_J SON	created in 3.6.0	VARCHAR2	4000	N	Validation JSON
PRV_STATE	PARAM_VALUE	created in 3.6.0	VARCHAR2	2048	N	Parameter value
PRV_TASK	TASK_RESULT_TRNSL	created in 3.6.0	VARCHAR2	4000	Y	Translation codes



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
PRV_TASK_PARAM	-- Table --	created in 3.6.0				System background task parameters
PRV_TASK_PARAM	PARAM_NAME	created in 3.6.0	VARCHAR2	4000	N	Parameter name
PRV_TASK_PARAM	PARAM_VALUE	created in 3.6.0	VARCHAR2	4000	Y	Parameter value
PRV_TASK_PARAM	TASK_JOB_NAME	created in 3.6.0	VARCHAR2	128	N	Task job name (prv_task)
PRV_TASK_STATUS	-- Table --	created in 3.6.0				System background task statuses
PRV_TASK_STATUS	DESCRIPTION	created in 3.6.0	VARCHAR2	4000	Y	Constant description Description
PRV_TASK_STATUS	ID	created in 3.6.0	NUMBER	22	N	ID
PRV_TASK_STATUS	NAME	created in 3.6.0	VARCHAR2	256	Y	Name
PRV_TASK_TYPE	VERSION_BITMAP	deleted in 3.6.0	NUMBER	22	N	SMS/Voice/Retail task availability



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
RAT_AUTO_IMP_RULE	CAR_REPORT_MODE	changed in 3.6.0	VARCHAR2	10	Y	Notification type: 'full' - Full report, 'short' - Short report
RAT_AUTO_IMP_RULE	CREATED	created in 3.6.0	DATE	7	Y	Created date
RAT_AUTO_IMP_RULE	CREATED_BY	created in 3.6.0	VARCHAR2	256	Y	Created by
RAT_AUTO_IMP_RULE	FULL_REPORT_RECIPIENTS	changed in 3.6.0	VARCHAR2	4000	Y	Full recipients list (separate ',')
RAT_AUTO_IMP_RULE	LAST_UPDATED	created in 3.6.0	DATE	7	Y	Last updated date
RAT_AUTO_IMP_RULE	LAST_UPDATED_BY	created in 3.6.0	VARCHAR2	256	Y	Last updated by
RAT_AUTO_IMP_RULE	OWNER_REPORT_MODE	changed in 3.6.0	VARCHAR2	10	Y	Notification type: 'full' - Full report, 'short' - Short report
RAT_AUTO_IMP_RULE	SHORT_REPORT_RECIPIENTS	changed in 3.6.0	VARCHAR2	4000	Y	Short recipients list (separate ',')



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
RAT_BILL_INC_COUNTRY	COUNTRY_DIAL_CODE	changed in 3.6.0	VARCHAR2	16	N	Country dial code
RAT_BILL_INC_COUNTRY	END_DATE	created in 3.6.0	DATE	7	N	End date
RAT_BILL_INC_COUNTRY	ID	created in 3.6.0	NUMBER	22	N	ID
RAT_BILL_INC_COUNTRY	INC_TYPE	created in 3.6.0	NUMBER	22	Y	Deprecated since 3.5.29
RAT_BILL_INC_COUNTRY	ORIGIN_PREFIX	created in 3.6.0	VARCHAR2	16	Y	Origin prefix
RAT_BILL_INC_COUNTRY	START_DATE	created in 3.6.0	DATE	7	N	Start date
RAT_CA_RATE_STATUS	ANI_DIAL_CODE	created in 3.6.0	VARCHAR2	16	Y	Origin dial code
RAT_DEPEND_RATE_TMP	RATE_ANI_CSCD	deleted in 3.6.0	VARCHAR2	4000	Y	Carrier-specific origin destination
RAT_DEPEND_RATE_TMP	RATE_ANI_DIAL_CODE	deleted in 3.6.0	VARCHAR2	16	Y	Origin dial code
RAT_EXP_DEFERRED_TASK	-- Table --	created in 3.6.0				Deferred rate export task list



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
RAT_EXP_DEFERRED_TASK	MAIL_BODY	created in 3.6.0	CLOB	4000	Y	Mail body
RAT_EXP_DEFERRED_TASK	MAIL_SUBJECT	created in 3.6.0	VARCHAR2	1024	Y	Mail subject
RAT_EXP_DEFERRED_TASK	TASK_JOB_NAME	created in 3.6.0	VARCHAR2	256	N	Task job name (prv_task)
RAT_EXP_DEFERRED_TASK	TASK_PARAM_JSON	created in 3.6.0	VARCHAR2	4000	Y	Task parameters in simple JSON format
RAT_EXP_PRESET	PRESET_COLUMN_LIST	changed in 3.6.0	VARCHAR2	4000	N	Internal column names list
RAT_EXP_TAG_CHILD_TEMP	-- Table --	created in 3.6.0				Temporary table for child records for tag based rate export
RAT_EXP_TAG_MERGE_TEMP	-- Table --	created in 3.6.0				Temporary table for merging child and parent records for tag based rate export



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
RAT_EXP_TAG_PARENT_T MP	-- Table --	created in 3.6.0				Temporary table for parent records for tag based rate export
RAT_GEN_COMPILATION	CLIENT_CSCD	changed in 3.6.0	VARCHAR2	256	Y	CSCD destination
RAT_GEN_COMPILATION	CLIENT_DIAL_CODE	changed in 3.6.0	VARCHAR2	16	N	Client dial code
RAT_GEN_COMPILATION	CLIENT_VOLUME	changed in 3.6.0	NUMBER	22	Y	Client volume
RAT_GEN_COMPILATION	CLIENT_VOLUME_LAST _X_DAYS	changed in 3.6.0	NUMBER	22	Y	Client volume last X days (X - defined in compilation settings)
RAT_GEN_COMPILATION	DEF_VENDORS_USED	changed in 3.6.0	NUMBER	22	Y	Flag: 1 - default vendor used, 0 - not default vendor used
RAT_GEN_COMPILATION	RATE_CHANGE_TYPE	changed in 3.6.0	NUMBER	22	Y	Rate change type code: 0 - equal, 1 - decrease, 2 - increase, 3 - mess, 4 - undefied



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
RAT_GEN_COMPILATION	RATE_ID	changed in 3.6.0	NUMBER	22	Y	Client rate ID from RAT_RATE table
RAT_GEN_COMPILATION	RULE_ID	changed in 3.6.0	NUMBER	22	Y	Used rule ID
RAT_GEN_COMPILATION	SYS_DESTINATION	changed in 3.6.0	VARCHAR2	256	Y	System destination
RAT_GEN_COMPILATION	TASK_NAME	changed in 3.6.0	VARCHAR2	256	N	Compilation ID
RAT_GEN_COMPILATION	VENDOR_COUNT	changed in 3.6.0	NUMBER	22	Y	Analyzed vendor count
RAT_GEN_COMPILATION	VENDOR_LIST	changed in 3.6.0	VARCHAR2	4000	Y	Analyzed vendor breakouts
RAT_GEN_COMPILATION	VENDOR_TOTAL_VOLUME	changed in 3.6.0	NUMBER	22	Y	Vendor total volume
RAT_GEN_COMPILATION	WARNINGS	changed in 3.6.0	VARCHAR2	256	Y	Warnings
RAT_GROUPS_GTT	-- Table --	created in 3.6.0				Temporary table for rate editor



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
RAT_IMP_CHECKPOINT_TMP	-- Table --	created in 3.6.0				Temporary table for voice rate import
RAT_IMP_ERR_LOG	RATE_ANI_CSCD	changed in 3.6.0	VARCHAR2	4000	Y	Carrier-specific origin destination
RAT_IMP_LOAD_ORIGIN_CODE	ANI_CSCD	changed in 3.6.0	VARCHAR2	4000	Y	Carrier-specific origin destination
RAT_IMP_LOAD_RATE	RATE_ANI_CSCD	changed in 3.6.0	VARCHAR2	4000	Y	Carrier-specific origin destination
RAT_IMP_LOG	COUNTRY_SET_JSON	changed in 3.6.0	CLOB	4000	Y	List of new country
RAT_IMP_ORIGIN_TMP	-- Table --	created in 3.6.0				Temporary table for voice rate import
RAT_IMP_RATE_ORIGIN_STATUS	ANI_CODE_STATUS	created in 3.6.0	NUMBER	22	Y	ANI code status (1 - new, 2 - close)
RAT_IMP_RATE_ORIGIN_STATUS	ANI_CSCD	changed in 3.6.0	VARCHAR2	4000	N	Carrier-specific origin destination



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
RAT_IMP_RATE_ORIGIN_STATUS	ANI_DIAL_CODE	changed in 3.6.0	VARCHAR2	16	N	Origin dial code
RAT_IMP_RATE_ORIGIN_STATUS	TASK_JOB_NAME	changed in 3.6.0	VARCHAR2	128	N	Task job name (prv_task)
RAT_IMP_RATE_STATUS	ANI_CSCD	created in 3.6.0	VARCHAR2	256	Y	Carrier-specific origin destination
RAT_IMP_RATE_STATUS	ANI_DIAL_CODE	created in 3.6.0	VARCHAR2	16	Y	Origin dial code
RAT_IMP_RATE_STATUS	FILE_SRC_ADDR	created in 3.6.0	VARCHAR2	2048	Y	File sheet name and row number
RAT_IMP_SETTING	CHK_ANI	created in 3.6.0	NUMBER	22	Y	Check ANI
RAT_IMP_SETTING	SAME_FIELD	created in 3.6.0	VARCHAR2	30	Y	Same not-ANI field
RAT_MATCHING_DIAL_CODES_TMP	-- Table --	created in 3.6.0				Table for temporary usage of rate generator
RAT_MATCHING_DIAL_CODES_TMP	DST_DIAL_CODE	created in 3.6.0	VARCHAR2	16	Y	Dial code



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
RAT_MATCHING_DIAL_CODES_TMP	RATE_ID	created in 3.6.0	NUMBER	22	Y	Rate id
RAT_RATE	RATE_ANI_CSCD	deleted in 3.6.0	VARCHAR2	4000	Y	Carrier-specific origin destination
RAT_RATES_GTT	-- Table --	created in 3.6.0				Temporary table for rate editor
RAT_RATE_ARCHIVE	RATE_ANI_GRP_ID	created in 3.6.0	NUMBER	22	Y	Origin dial codes group ID
RAT_RATE_ERROR_LOG	-- Table --	deleted in 3.6.0				Error log table for RAT_RATE
RAT_RATE_ERROR_LOG	CONN_FEE	deleted in 3.6.0	VARCHAR2	4000	Y	Connection fee
RAT_RATE_ERROR_LOG	ORA_ERR_MESG\$	deleted in 3.6.0	VARCHAR2	2000	Y	Error message
RAT_RATE_ERROR_LOG	ORA_ERR_NUMBER\$	deleted in 3.6.0	NUMBER	22	Y	Error ORA number
RAT_RATE_ERROR_LOG	ORA_ERR_OPTYP\$	deleted in 3.6.0	VARCHAR2	2	Y	Error ORA type



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
RAT_RATE_ERROR_LOG	ORA_ERR_ROWID\$	deleted in 3.6.0	UROWID	4000	Y	Error ROWID
RAT_RATE_ERROR_LOG	ORA_ERR_TAG\$	deleted in 3.6.0	VARCHAR2	2000	Y	Error tag
RAT_RATE_ERROR_LOG	RATE1	deleted in 3.6.0	VARCHAR2	4000	Y	Rate 1
RAT_RATE_ERROR_LOG	RATE2	deleted in 3.6.0	VARCHAR2	4000	Y	Rate 2
RAT_RATE_ERROR_LOG	RATE3	deleted in 3.6.0	VARCHAR2	4000	Y	Rate 3
RAT_RATE_ERROR_LOG	RATE4	deleted in 3.6.0	VARCHAR2	4000	Y	Rate 4
RAT_RATE_ERROR_LOG	RATE5	deleted in 3.6.0	VARCHAR2	4000	Y	Rate 5
RAT_RATE_ERROR_LOG	RATE6	deleted in 3.6.0	VARCHAR2	4000	Y	Rate 6
RAT_RATE_ERROR_LOG	RATE_BILL_INC_ID	deleted in 3.6.0	VARCHAR2	4000	Y	Billing increment ID
RAT_RATE_ERROR_LOG	RATE_CSCD	deleted in 3.6.0	VARCHAR2	4000	Y	Carrier-specific destination
RAT_RATE_ERROR_LOG	RATE_DIAL_CODE	deleted in 3.6.0	VARCHAR2	4000	Y	Dial code



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
RAT_RATE_ERROR_LOG	RATE_END_DATE	deleted in 3.6.0	VARCHAR2	4000	Y	End date
RAT_RATE_ERROR_LOG	RATE_ID	deleted in 3.6.0	VARCHAR2	4000	Y	Rate ID
RAT_RATE_ERROR_LOG	RATE_NOTES	deleted in 3.6.0	VARCHAR2	4000	Y	Rate note
RAT_RATE_ERROR_LOG	RATE_PRODUCT_ID	deleted in 3.6.0	VARCHAR2	4000	Y	Product ID
RAT_RATE_ERROR_LOG	RATE_START_DATE	deleted in 3.6.0	VARCHAR2	4000	Y	Start date
RAT_RATE_ERROR_LOG	RATE_TIMEMASK_ID	deleted in 3.6.0	VARCHAR2	4000	Y	Timemask ID
RAT_RATE_IMPORT_TMP_NEW	-- Table --	created in 3.6.0				Temporary table for voice rate import
RAT_RATE_IMPORT_TMP_NEW	RATE1	created in 3.6.0	NUMBER	22	Y	Rate 1 New price Price
RAT_RATE_IMPORT_TMP_NEW	RATE_ANI_GRP_ID	created in 3.6.0	NUMBER	22	Y	Origin dial codes group ID



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
RAT_RATE_IMPORT_TMP_NEW	RATE_BILL_INC_ID	created in 3.6.0	NUMBER	22	Y	Billing increment ID Increment scheme
RAT_RATE_IMPORT_TMP_NEW	RATE_CSCD	created in 3.6.0	VARCHAR2	256	Y	Carrier-specific destination CSCD
RAT_RATE_IMPORT_TMP_NEW	RATE_DIAL_CODE	created in 3.6.0	VARCHAR2	16	Y	Dial code Rate dial Change code/Sender ID e.164 (optional)
RAT_RATE_IMPORT_TMP_NEW	RATE_END_DATE	created in 3.6.0	DATE	7	Y	End date Rate effective till rate record end affective
RAT_RATE_IMPORT_TMP_NEW	RATE_ID	created in 3.6.0	NUMBER	22	Y	rate_id Rate ID (primary key) Client POI SMS rate
RAT_RATE_IMPORT_TMP_NEW	RATE_NOTES	created in 3.6.0	VARCHAR2	256	Y	Rate note notes
RAT_RATE_IMPORT_TMP_NEW	RATE_PRODUCT_ID	created in 3.6.0	NUMBER	22	Y	Product ID rate product id (link to BAS_PRODUCT table)



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
RAT_RATE_IMPORT_TMP_NEW	RATE_START_DATE	created in 3.6.0	DATE	7	Y	Rate effective from
RAT_RATE_IMPORT_TMP_NEW	RATE_TIMEMASK_ID	created in 3.6.0	NUMBER	22	Y	Timemask ID
RAT_RATE_IMPORT_TMP_OLD	-- Table --	created in 3.6.0				Temporary table for voice rate import
RAT_RATE_IMPORT_TMP_OLD	RATE1	created in 3.6.0	NUMBER	22	Y	Rate 1 New price Price
RAT_RATE_IMPORT_TMP_OLD	RATE_ANI_GRP_ID	created in 3.6.0	NUMBER	22	Y	Origin dial codes group ID
RAT_RATE_IMPORT_TMP_OLD	RATE_BILL_INC_ID	created in 3.6.0	NUMBER	22	Y	Billing increment ID Increment scheme
RAT_RATE_IMPORT_TMP_OLD	RATE_CSCD	created in 3.6.0	VARCHAR2	256	Y	Carrier-specific destination CSCD
RAT_RATE_IMPORT_TMP_OLD	RATE_DIAL_CODE	created in 3.6.0	VARCHAR2	16	Y	Dial code Rate dial Change code/Sender ID e.164 (optional)



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
RAT_RATE_IMPORT_TMP_OLD	RATE_END_DATE	created in 3.6.0	DATE	7	Y	End date Rate effective till rate record end affective
RAT_RATE_IMPORT_TMP_OLD	RATE_ID	created in 3.6.0	NUMBER	22	Y	rate_id Rate ID (primary key) Client POI SMS rate
RAT_RATE_IMPORT_TMP_OLD	RATE_NOTES	created in 3.6.0	VARCHAR2	256	Y	Rate note notes
RAT_RATE_IMPORT_TMP_OLD	RATE_PRODUCT_ID	created in 3.6.0	NUMBER	22	Y	Product ID rate product id (link to BAS_PRODUCT table)
RAT_RATE_IMPORT_TMP_OLD	RATE_START_DATE	created in 3.6.0	DATE	7	Y	Rate effective from
RAT_RATE_IMPORT_TMP_OLD	RATE_TIMEMASK_ID	created in 3.6.0	NUMBER	22	Y	Timemask ID
RAT_RATE_ORIGIN_CODE	-- Table --	created in 3.6.0				Rate origin dial codes
RAT_RATE_ORIGIN_CODE	ANI_DIAL_CODE	created in 3.6.0	VARCHAR2	16	N	Origin dial code



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
RAT_RATE_ORIGIN_CODE	CODE_GRP_ID	created in 3.6.0	NUMBER	22	N	ID origin dial code group
RAT_RATE_ORIGIN_GROUP	-- Table --	deleted in 3.6.0				Rate origin dial codes
RAT_RATE_ORIGIN_GROUP	ANI_DIAL_CODE	deleted in 3.6.0	VARCHAR2	16	N	Origin dial code
RAT_RATE_ORIGIN_GROUP	GRP_ID	deleted in 3.6.0	NUMBER	22	N	Origin dial codes group ID
RAT_RATE_ORIGIN_GROUP_TMP	ANI_CSCD	created in 3.6.0	VARCHAR2	256	N	Carrier-specific origin destination
RAT_RATE_ORIGIN_GROUP_TMP	ANI_DIAL_CODE	created in 3.6.0	VARCHAR2	16	N	Origin dial code
RAT_RATE_ORIGIN_GROUP_TMP	END_DATE	created in 3.6.0	DATE	7	Y	End date
RAT_RATE_ORIGIN_GROUP_TMP	GRP_ID	created in 3.6.0	NUMBER	22	Y	ID origin dial code group



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
RAT_RATE_ORIGIN_GROUP_TMP	START_DATE	created in 3.6.0	DATE	7	Y	Start date
RAT_RATE_ORIGIN_GRP	-- Table --	created in 3.6.0				Rate origin group
RAT_RATE_ORIGIN_GRP	CODE_GRP_ID	created in 3.6.0	NUMBER	22	Y	ID origin dial code group
RAT_RATE_ORIGIN_GRP	GRP_DIRECTION	created in 3.6.0	NUMBER	22	N	Group direction
RAT_RATE_ORIGIN_GRP	GRP_ID	created in 3.6.0	NUMBER	22	N	ID origin group
RAT_RATE_ORIGIN_GRP	GRP_IS_ACTIVE	created in 3.6.0	NUMBER	22	Y	Activity flag (0/1)
RAT_RATE_ORIGIN_GRP	GRP_NAME	created in 3.6.0	VARCHAR2	256	N	Group name
RAT_RATE_ORIGIN_GRP	GRP_PRODUCT_ID	created in 3.6.0	NUMBER	22	Y	ID vendor product,
RAT_RATE_TMP	NOT_FOR_IMPORT	created in 3.6.0	NUMBER	22	Y	Rate update flag
RAT_RATE_TMP	RATE_ANI_CSCD	changed in 3.6.0	VARCHAR2	4000	Y	Carrier-specific origin destination



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
RAT_RATE_TMP	RATE_ANI_GRP_ID	created in 3.6.0	NUMBER	22	Y	ANI-group ID
RAT_RCN_IN	-- Table --	created in 3.6.0				Rate change notification
RAT_RCN_IN	RATE1	created in 3.6.0	NUMBER	22	Y	Rate 1 New price Price
RAT_RCN_IN	RATE2	created in 3.6.0	NUMBER	22	Y	Old price Rate 2
RAT_RCN_IN	RATE3	created in 3.6.0	NUMBER	22	Y	Rate 3
RAT_RCN_IN	RATE4	created in 3.6.0	NUMBER	22	Y	Rate 4
RAT_RCN_IN	RATE5	created in 3.6.0	NUMBER	22	Y	Rate 5
RAT_RCN_IN	RATE6	created in 3.6.0	NUMBER	22	Y	Rate 6
RAT_RCN_IN	RATE_BILL_INC_ID	created in 3.6.0	NUMBER	22	N	Billing increment ID Increment scheme
RAT_RCN_IN	RATE_CSCD	created in 3.6.0	VARCHAR2	256	Y	Carrier-specific destination CSCD



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
RAT_RCN_IN	RATE_DIAL_CODE	created in 3.6.0	VARCHAR2	16	N	Dial code Rate dial Change code/Sender ID e.164 (optional)
RAT_RCN_IN	RATE_END_DATE	created in 3.6.0	DATE	7	N	End date Rate effective till rate record end affective
RAT_RCN_IN	RATE_HASH	created in 3.6.0	VARCHAR2	20	Y	Rate hash
RAT_RCN_IN	RATE_ID	created in 3.6.0	NUMBER	22	N	rate_id Rate ID (primary key) Client POI SMS rate
RAT_RCN_IN	RATE_NOTES	created in 3.6.0	VARCHAR2	256	Y	Rate note notes
RAT_RCN_IN	RATE_PRODUCT_ID	created in 3.6.0	NUMBER	22	N	Product ID rate product id (link to BAS_PRODUCT table)
RAT_RCN_IN	RATE_START_DATE	created in 3.6.0	DATE	7	N	Rate effective from
RAT_RCN_IN	RATE_TIMEMASK_ID	created in 3.6.0	NUMBER	22	N	Timemask ID



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
RAT_RCN_MERGE_TREE	-- Table --	created in 3.6.0				Rate change notification temporary table
RAT_RCN_MERGE_TREE	DIAL_CODE	created in 3.6.0	VARCHAR2	16	Y	Dial code
RAT_RCN_MERGE_TREE	END_DATE	created in 3.6.0	DATE	7	Y	Effective till
RAT_RCN_MERGE_TREE	PRODUCT_ID	created in 3.6.0	NUMBER	22	Y	Product ID
RAT_RCN_MERGE_TREE	RATE_HASH	created in 3.6.0	VARCHAR2	20	Y	Hash
RAT_RCN_MERGE_TREE	RATE_ID	created in 3.6.0	NUMBER	22	Y	rate_id Rate ID (primary key) Client POI SMS rate
RAT_RCN_MERGE_TREE	START_DATE	created in 3.6.0	DATE	7	Y	Effective from
RAT_RCN_SCHEDULE	LAST_EXEC_DATE	changed in 3.6.0	DATE	7	Y	Previous execution date
RAT_RCN_SCHEDULE	SCHEDULE	changed in 3.6.0	VARCHAR2	256	Y	Schedule in the flesh
RAT_RCN_TASK	SYS_JOB_NAME	created in 3.6.0	VARCHAR2	64	Y	Job name



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
RCS_EDR_STATUS_TMP	-- Table --	created in 3.6.0				Temporary table for RCS delivery report processing
RCS_RATE_EXP_TMP	-- Table --	created in 3.6.0				RCS rate export GTT
REP_DATA	-- Table --	created in 3.6.0				Replication stats for dicts
REP_TABLE	IS_DICT	created in 3.6.0	NUMBER	22	Y	Is table a dictionary
REP_TABLE	REP_ROWS	created in 3.6.0	NUMBER	22	Y	Rows replicated
RPT_DATA	-- Table --	created in 3.6.0				Report data
RPT_DATA	REPORT_DATE	created in 3.6.0	DATE	7	Y	Report date
RPT_DATA	RPT_DETAILS	created in 3.6.0	CLOB	4000	Y	Report details
RPT_DATA	RPT_SQL	created in 3.6.0	CLOB	4000	Y	Report sql
RPT_DATA	SQL_ID	created in 3.6.0	NUMBER	22	N	Sql id
RPT_DATA	TASK_NAME	created in 3.6.0	VARCHAR2	256	Y	Task name



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
RPT_DATA	TTL	created in 3.6.0	NUMBER	22	Y	Ttl
RPT_DATA_STORE	-- Table --	created in 3.6.0				Report result
RPT_DATA_STORE	COL_DESC	created in 3.6.0	VARCHAR2	128	Y	Column decription
RPT_DATA_STORE	COL_NAME	created in 3.6.0	VARCHAR2	128	Y	Column name
RPT_DATA_STORE	COL_TYPE	created in 3.6.0	NUMBER	22	Y	Column type
RPT_DATA_STORE	ROW_NO	created in 3.6.0	NUMBER	22	Y	Roe number
RPT_DATA_STORE	SQL_ID	created in 3.6.0	NUMBER	22	Y	Sql id
RPT_DATA_STORE	VAL	created in 3.6.0	VARCHAR2	4000	Y	Value
RPT_PARAM2	-- Table --	created in 3.6.0				Report parameters
RPT_PARAM2	PARAM_BIND_NAME	created in 3.6.0	VARCHAR2	30	N	Parameter bind name (used in query)
RPT_PARAM2	PARAM_DEFAULT_EXP	created in 3.6.0	VARCHAR2	4000	Y	Default expression



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
RPT_PARAM2	PARAM_ID	created in 3.6.0	NUMBER	22	N	Parameter ID (primary key)
RPT_PARAM2	PARAM_NAME	created in 3.6.0	VARCHAR2	256	N	Parameter name
RPT_PARAM2	PARAM_ORDER_VALU E	created in 3.6.0	NUMBER	22	Y	Order value
RPT_PARAM2	PARAM_REPORT_ID	created in 3.6.0	NUMBER	22	N	Report ID (link to RPT_REPORT table)
RPT_PARAM2	PARAM_SIZE	created in 3.6.0	NUMBER	22	Y	Param size
RPT_PARAM2	PARAM_SQL_QUERY	created in 3.6.0	VARCHAR2	4000	Y	SQL query to generage list of values.
RPT_PARAM2	PARAM_TYPE_CODE	created in 3.6.0	VARCHAR2	30	N	Parameter code (primary key) Param type
RPT_PRESET2	-- Table --	created in 3.6.0				Report presets
RPT_PRESET2	BATCH_SQL	created in 3.6.0	VARCHAR2	4000	Y	Scheduler SQL



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
RPT_PRESET2	BCC_EMAILS	created in 3.6.0	VARCHAR2	4000	Y	BCC emails for report sending
RPT_PRESET2	CC_EMAILS	created in 3.6.0	VARCHAR2	4000	Y	Cc emails
RPT_PRESET2	CC_ID	created in 3.6.0	NUMBER	22	Y	Contract company ID id contract
RPT_PRESET2	LAST_ERROR	created in 3.6.0	VARCHAR2	4000	Y	Last error when applying send if occurred execution
RPT_PRESET2	LAST_EXEC_DATE	created in 3.6.0	DATE	7	Y	Last execution date Previous
RPT_PRESET2	MAIL_OUT_TYPE	created in 3.6.0	VARCHAR2	16	N	Format type (HTML/XLS/CSV)
RPT_PRESET2	NEXT_EXEC_DATE	created in 3.6.0	DATE	7	Y	Next execution date
RPT_PRESET2	PRESET_DESCR	created in 3.6.0	VARCHAR2	256	N	Preset description
RPT_PRESET2	PRESET_ID	created in 3.6.0	NUMBER	22	N	Preset ID id



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
RPT_PRESET2	REPORT_ID	created in 3.6.0	NUMBER	22	Y	Report ID (primary key)
RPT_PRESET2	RESULT_SQL_ID	created in 3.6.0	NUMBER	22	Y	Result sql id
RPT_PRESET2	SCHEDULE	created in 3.6.0	VARCHAR2	512	Y	Preset schedule Schedule in the flesh
RPT_PRESET2	STATE	created in 3.6.0	NUMBER	22	N	State
RPT_PRESET2	SUBSCRIBER_EMAILS	created in 3.6.0	VARCHAR2	4000	Y	Recipients
RPT_PRESET2	TELEGRAM_CHAT_ID	created in 3.6.0	VARCHAR2	1000	Y	Telegram chat ID
RPT_PRESET2	TELEGRAM_MESSAGE	created in 3.6.0	VARCHAR2	4000	Y	Telegram message
RPT_PRESET2	USER_ID	created in 3.6.0	NUMBER	22	N	User numeric ID (primary key) Manager User-creator
RPT_PRESET_PARAM2	-- Table --	created in 3.6.0				Report preset parameter values
RPT_PRESET_PARAM2	PARAM_EXP	created in 3.6.0	VARCHAR2	4000	Y	Default expression



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
RPT_PRESET_PARAM2	PARAM_ID	created in 3.6.0	NUMBER	22	N	Parameter ID (primary key)
RPT_PRESET_PARAM2	PRESET_ID	created in 3.6.0	NUMBER	22	N	Preset ID id
RPT_PRESET_STATE	-- Table --	created in 3.6.0				Report statuse settings
RPT_PRESET_STATE	ID	created in 3.6.0	NUMBER	22	N	ID
RPT_PRESET_STATE	NAME	created in 3.6.0	VARCHAR2	2000	Y	Name
RPT_REPORT	RECURRENT_CREATOR_ID	created in 3.6.0	NUMBER	22	Y	id of the user who created the first preset with Is recurrent.
RPT_REPORT	REPORT_CHANGE_DATE	created in 3.6.0	DATE	7	Y	Report change date
RPT_REPORT	REPORT_CREATE_DATE	created in 3.6.0	DATE	7	Y	Report create date
RPT_REPORT2	-- Table --	created in 3.6.0				Reports



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
RPT_REPORT2	GROUP_ID	created in 3.6.0	NUMBER	22	Y	Group ID
RPT_REPORT2	REPORT_CHANGE_DATE	created in 3.6.0	DATE	7	Y	Report change date
RPT_REPORT2	REPORT_CREATE_DATE	created in 3.6.0	DATE	7	Y	Report create date
RPT_REPORT2	REPORT_DESCR	created in 3.6.0	VARCHAR2	4000	Y	Report description
RPT_REPORT2	REPORT_ERR_REPEAT	created in 3.6.0	NUMBER	22	Y	Error count
RPT_REPORT2	REPORT_FOR_PORTAL	created in 3.6.0	VARCHAR2	1	Y	For portal flag
RPT_REPORT2	REPORT_GUID	created in 3.6.0	VARCHAR2	64	N	GUID
RPT_REPORT2	REPORT_ID	created in 3.6.0	NUMBER	22	N	Report ID (primary key)
RPT_REPORT2	REPORT_IS_SYSTEM	created in 3.6.0	NUMBER	22	N	Is system flag
RPT_REPORT2	REPORT_NAME	created in 3.6.0	VARCHAR2	256	N	Report name



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
RPT_REPORT2	REPORT_ROLE_CODE	created in 3.6.0	VARCHAR2	30	Y	Role required for report
RPT_REPORT2	REPORT_SQL	created in 3.6.0	CLOB	4000	N	Report SQL
RPT_REPORT2	REPORT_TEMPLATE_B LOB	created in 3.6.0	BLOB	4000	Y	xls template BLOB
RPT_REPORT2	REPORT_TEMPLATE_T YPE	created in 3.6.0	VARCHAR2	16	Y	Template type
RPT_REPORT2	STORAGE_PERIOD	created in 3.6.0	NUMBER	22	Y	Storage period
RPT_REPORT2	STORAGE_ROWS	created in 3.6.0	NUMBER	22	Y	Storage rows
RPT_REPORT2	TYPE_ID	created in 3.6.0	NUMBER	22	Y	Dial code numeric ID
RPT_REPORT2_GROUP	-- Table --	created in 3.6.0				Report group
RPT_REPORT2_GROUP	DESCR	created in 3.6.0	VARCHAR2	512	N	Description description Installation
RPT_REPORT2_GROUP	GROUP_ID	created in 3.6.0	NUMBER	22	N	Group ID



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
RPT_REPORT2_GROUP	PARENT	created in 3.6.0	NUMBER	22	Y	Parent
RPT_REPORT2_TYPE	-- Table --	created in 3.6.0				Report type
RPT_REPORT2_TYPE	DESCR	created in 3.6.0	VARCHAR2	512	N	Description description Installation
RPT_REPORT2_TYPE	TYPE_ID	created in 3.6.0	NUMBER	22	N	Dial code numeric ID
RPT_TASK_HIST	-- Table --	created in 3.6.0				Report task history
RPT_TASK_HIST	TASK_HIST	created in 3.6.0	VARCHAR2	1000	Y	Task history record
RPT_TASK_HIST	TASK_NAME	created in 3.6.0	VARCHAR2	256	Y	Task name
RPT_TASK_HIST	TASK_TIME	created in 3.6.0	TIMESTAMP(6)	11	Y	Task time
RUPD\$_SMS_RATE	-- Table --	deleted in 3.6.0				temporary updatable snapshot log
RUT_LIM_LOCK	PRODUCT_ID	changed in 3.6.0	NUMBER	22	N	Product ID



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
RUT_LIM_LOCK	VND_PRODUCT_LIST	created in 3.6.0	VARCHAR2	4000	Y	Vendor product ID list
RUT_LIM_LOCK	VND_PRODUCT_LIST_ID	created in 3.6.0	NUMBER	22	Y	Vendor products list ID
RUT_LIM_LOCK	VND_PRODUCT_SCOPE	created in 3.6.0	NUMBER	22	Y	Vendor product scope: 1 - inclusive, -1 exclusive
RUT_LIM_METRIC	METRIC_CODE	created in 3.6.0	VARCHAR2	256	Y	Metric code for translation of limitations rules
RUT_LIM_RULE	PRODUCT_ID	changed in 3.6.0	NUMBER	22	Y	Product ID
RUT_LIM_RULE	PRODUCT_NOTES	created in 3.6.0	VARCHAR2	1000	Y	Product notes
RUT_LIM_RULE	PRODUCT_NOTES_DIR	created in 3.6.0	NUMBER	22	Y	Product notes direction (0 - client, 1 - vendor)
RUT_LIM_RULE	VND_PRODUCT_LIST_ID	created in 3.6.0	NUMBER	22	Y	Vendor products list ID



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
RUT_LIM_RULE	VND_PRODUCT_SCOPE	created in 3.6.0	NUMBER	22	Y	Vendor product scope: 1 - inclusive, -1 - exclusive, 0 - all
RUT_LIM_STATS_TMP	PRODUCT_ID	deleted in 3.6.0	NUMBER	22	Y	Product ID
RUT_LIM_STATS_TMP	PRODUCT_NOTES	created in 3.6.0	VARCHAR2	1000	Y	Product notes
RUT_LIM_STATS_TMP	SRC_PRODUCT_ID	created in 3.6.0	NUMBER	22	Y	Client product ID
RUT_LIM_STATS_TMP	VND_LIST_ID	created in 3.6.0	NUMBER	22	Y	Vendor products list ID
RUT_LIM_VND_LIST	-- Table --	created in 3.6.0				Limitation rules vendor product list
RUT_LIM_VND_LIST	LIST_ID	created in 3.6.0	NUMBER	22	N	Vendor product list ID
RUT_LIM_VND_LIST	PRODUCT_ID	created in 3.6.0	NUMBER	22	N	Vendor product ID
RUT_SOFT_SWITCH	IP_WHITELISTING	created in 3.6.0	NUMBER	22	N	Whitelist ip
RUT_SOFT_SWITCH	MYSQL_IP	created in 3.6.0	VARCHAR2	256	Y	Mysql ip



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
RUT_SOFT_SWITCH	MYSQL_LOGIN	created in 3.6.0	VARCHAR2	256	Y	Mysql login
RUT_SOFT_SWITCH	MYSQL_PASSWORD	created in 3.6.0	VARCHAR2	256	Y	Mysql password
RUT_SOFT_SWITCH	MYSQL_PORT	created in 3.6.0	NUMBER	22	Y	Mysql port
RUT_SOFT_SWITCH	OPENSIPS_WHITELIST_TABLE	created in 3.6.0	VARCHAR2	256	Y	Table name (varchar2), required field when enabling the option
RUT_SOFT_SWITCH	SOFT_SWITCH_JSON_REQUEST	created in 3.6.0	VARCHAR2	4000	Y	Softswitch JSON request
RUT_SOFT_SWITCH	SOFT_SWITCH_PORT	created in 3.6.0	VARCHAR2	10	Y	Softswitch port
RUT_SOFT_SWITCH	SOFT_SWITCH_URL	created in 3.6.0	VARCHAR2	4000	Y	Softswitch URL
RUT_SRC_PRFX_RAW_TMP	-- Table --	created in 3.6.0				Temporary table for raw data for tag import
RUT_SRC_PRFX_TMP	-- Table --	created in 3.6.0				Temporary table for tag import data



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
SMS_2WAY_REF_TMP	-- Table --	created in 3.6.0				Temporary table for 2way reference data import
SMS_BLOCKING_RULES	-- Table --	created in 3.6.0				Vendor blocking rules
SMS_BLOCKING_RULES	ANI_PATTERN	created in 3.6.0	VARCHAR2	4000	Y	regex
SMS_BLOCKING_RULES	BLOCK_MODE	created in 3.6.0	VARCHAR2	32	Y	block mode (id list from sms_blockrules_mode_list)
SMS_BLOCKING_RULES	BLOCK_PERIOD	created in 3.6.0	NUMBER	22	Y	integer (in minutes)
SMS_BLOCKING_RULES	CLIENT_LIST	created in 3.6.0	VARCHAR2	4000	Y	list of integers separated with space, empty field or * means any product
SMS_BLOCKING_RULES	CLIENT_LIST_TYPE	created in 3.6.0	NUMBER	22	Y	client product list type (0 - all, -1 - excluding, 1 - including)
SMS_BLOCKING_RULES	COMPLETE_PERIOD	created in 3.6.0	VARCHAR2	1	Y	complete period flag (1 - yes, null - no)



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
SMS_BLOCKING_RULES	CONDITION	created in 3.6.0	VARCHAR2	4000	Y	condition in routing rule
SMS_BLOCKING_RULES	DESTINATION_TAG_LIST	created in 3.6.0	VARCHAR2	4000	Y	list of DNIS tags allowed for the blocking rule
SMS_BLOCKING_RULES	DESTINATION_TAG_LIST_TYPE	created in 3.6.0	NUMBER	22	Y	destination ID tag list type (0 - all, -1 - excluding, 1 - including)
SMS_BLOCKING_RULES	DNIS_PATTERN	created in 3.6.0	VARCHAR2	4000	Y	regexp
SMS_BLOCKING_RULES	MCCMNC_LIST	created in 3.6.0	VARCHAR2	4000	Y	list of 3-, 5- or 6-digit values separated with space, empty field or * means any MCCMNC, MCC* also allowed
SMS_BLOCKING_RULES	MCCMNC_LIST_TYPE	created in 3.6.0	NUMBER	22	Y	mccmnc list type (0 - all, -1 - excluding, 1 - including)
SMS_BLOCKING_RULES	MESSAGE_LIMIT	created in 3.6.0	NUMBER	22	N	non-zero unsigned integer



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
SMS_BLOCKING_RULES	ROUTING_RULE_LIST	created in 3.6.0	VARCHAR2	4000	Y	list of RR which are [un]compatible with the blocking rule
SMS_BLOCKING_RULES	ROUTING_RULE_LIST_TYPE	created in 3.6.0	NUMBER	22	Y	routing rule list type (0 - all, -1 - excluding, 1 - including)
SMS_BLOCKING_RULES	RULE_ID	created in 3.6.0	NUMBER	22	N	ID
SMS_BLOCKING_RULES	RULE_NAME	created in 3.6.0	VARCHAR2	256	N	name
SMS_BLOCKING_RULES	RULE_PRIORITY	created in 3.6.0	NUMBER	22	Y	the bigger value the higher priority (integer > 0)
SMS_BLOCKING_RULES	SENDER_ID_TAG_LIST	created in 3.6.0	VARCHAR2	4000	Y	list of sender ID tags allowed for the blocking rule
SMS_BLOCKING_RULES	SENDER_ID_TAG_LIST_TYPE	created in 3.6.0	NUMBER	22	Y	sender ID tag list type (0 - all, -1 - excluding, 1 - including)



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
SMS_BLOCKING_RULES	START_DATE	created in 3.6.0	DATE	7	N	start date
SMS_BLOCKING_RULES	STOP_DATE	created in 3.6.0	DATE	7	N	start date omitted means sometime in the past, stop date omitted means far far unapproachable future
SMS_BLOCKING_RULES	TEXT_PATTERN	created in 3.6.0	VARCHAR2	4000	Y	regex
SMS_BLOCKING_RULES	TYPE_PERIOD	created in 3.6.0	VARCHAR2	2	N	SS(sec), MM(minute), HH(hour) or DD(day)
SMS_BLOCKING_RULES	VENDOR_LIST	created in 3.6.0	VARCHAR2	4000	Y	list of integers separated with space, empty field or * means any product
SMS_BLOCKING_RULES	VENDOR_LIST_TYPE	created in 3.6.0	NUMBER	22	Y	vendor product list type (0 - all, -1 - excluding, 1 - including)
SMS_BLOCKRULES_MODE_LIST	-- Table --	created in 3.6.0				mode_id for Vendor blocking rules



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
SMS_BLOCKRULES_MODE_LIST	DESCR	created in 3.6.0	VARCHAR2	256	N	Name UI-code
SMS_BLOCKRULES_MODE_LIST	ID	created in 3.6.0	NUMBER	22	N	ID
SMS_BUFFERING_RULES	CREATED	created in 3.6.0	DATE	7	Y	Created date
SMS_BUFFERING_RULES	CREATED_BY	created in 3.6.0	VARCHAR2	256	Y	Created by
SMS_BUFFERING_RULES	LAST_UPDATED	created in 3.6.0	DATE	7	Y	Last updated date
SMS_BUFFERING_RULES	LAST_UPDATED_BY	created in 3.6.0	VARCHAR2	256	Y	Last updated by
SMS_CAMPAIGN	BUTTON_ACTION_URL	created in 3.6.0	VARCHAR2	4000	Y	Button target UR
SMS_CAMPAIGN	BUTTON_CAPTION	created in 3.6.0	VARCHAR2	4000	Y	Button caption
SMS_CAMPAIGN	CAMPAIGN_KEYWORD	changed in 3.6.0	VARCHAR2	100	Y	Keyword
SMS_CAMPAIGN	EXPECT_USER_RESP	created in 3.6.0	NUMBER	22	Y	Expect user response



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
SMS_CAMPAIGN	FAILURE_ALERT_SENT	created in 3.6.0	NUMBER	22	Y	Failure alert sent
SMS_CAMPAIGN	IMAGE_URL	created in 3.6.0	VARCHAR2	4000	Y	Button icon URL
SMS_CAMPAIGN	IM_CHANNELS	created in 3.6.0	VARCHAR2	4000	Y	Im channels
SMS_CAMPAIGN	IM_MESSAGE	created in 3.6.0	VARCHAR2	4000	Y	Im message
SMS_CAMPAIGN	IM_TTLS	created in 3.6.0	VARCHAR2	4000	Y	Im ttl
SMS_CAMPAIGN	MESSAGE_LABEL	created in 3.6.0	VARCHAR2	256	Y	Message label
SMS_CAMPAIGN	MESSAGE_PURPOSE	created in 3.6.0	VARCHAR2	100	Y	Message Purpose
SMS_CAMPAIGN	REPLY_TEMPL_ID	created in 3.6.0	NUMBER	22	Y	Reply template
SMS_CAMPAIGN	SENT_ROW_INTERVALS	created in 3.6.0	VARCHAR2	4000	Y	Intervals of sent row
SMS_CDR	BILL_AMOUNT_DST	created in 3.6.0	NUMBER	22	Y	Vendor billable amount
SMS_CDR	BILL_AMOUNT_SRC	created in 3.6.0	NUMBER	22	Y	Client billable amount



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
SMS_CDR	CDR_ACTIVATION_TIME	created in 3.6.0	DATE	7	Y	Time when was received status ACTIVATED
SMS_CDR	CDR_DST_DID_BILL_SCHEME_ID	created in 3.6.0	NUMBER	22	Y	Vendor Billing scheme ID
SMS_CDR	CDR_DST_DID_END_DATE	created in 3.6.0	DATE	7	Y	Vendor did end date
SMS_CDR	CDR_DST_DID_START_DATE	created in 3.6.0	DATE	7	Y	Vendor did start date
SMS_CDR	CDR_IS_DST_DID	created in 3.6.0	NUMBER	22	Y	Is SMS sent to the DID number currently linked to the vendor product in the DVD refbook
SMS_CDR	CDR_IS_SRC_DID	created in 3.6.0	NUMBER	22	Y	Is SMS sent to the DID number currently linked to the client product in the DVD refbook



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
SMS_CDR	CDR_SRC_DID_BILL_SCHEME_ID	created in 3.6.0	NUMBER	22	Y	Client Billing scheme ID
SMS_CDR	CDR_SRC_DID_END_DATE	created in 3.6.0	DATE	7	Y	Client did end date
SMS_CDR	CDR_SRC_DID_START_DATE	created in 3.6.0	DATE	7	Y	Client did start date
SMS_CDR	HLRCACHED	created in 3.6.0	NUMBER	22	Y	HLR cached
SMS_CDR	HLRPORTED	created in 3.6.0	VARCHAR2	8	Y	HLR Ported
SMS_CDR	HLRSOURCENAME	created in 3.6.0	VARCHAR2	64	Y	HLR source name
SMS_CDR	HLRSOURCETYPE	created in 3.6.0	VARCHAR2	64	Y	HLR source type
SMS_CDR	REVERSE_CHARGE_DEST	created in 3.6.0	NUMBER	22	Y	Reverse charge for DST (-1,1)
SMS_CDR	REVERSE_CHARGE_SRC	created in 3.6.0	NUMBER	22	Y	Reverse charge for SRC (-1,1)



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
SMS_CDR	SARPARTNUMBER	created in 3.6.0	NUMBER	22	Y	SAR part number
SMS_CDR	STATEFULPROCESSING	created in 3.6.0	NUMBER	22	Y	Stateful processing
SMS_CDR_ARCHIVE	BILL_AMOUNT_DST	created in 3.6.0	NUMBER	22	Y	Vendor billable amount
SMS_CDR_ARCHIVE	BILL_AMOUNT_SRC	created in 3.6.0	NUMBER	22	Y	Client billable amount
SMS_CDR_ARCHIVE	CDR_ACTIVATION_TIME	created in 3.6.0	DATE	7	Y	Time when was received status ACTIVATED
SMS_CDR_ARCHIVE	CDR_DLR_TECH_DETAILS	changed in 3.6.0	VARCHAR2	4000	Y	Delivery technical details
SMS_CDR_ARCHIVE	CDR_DST_DID_BILL_SCHEME_ID	created in 3.6.0	NUMBER	22	Y	Vendor Billing scheme ID
SMS_CDR_ARCHIVE	CDR_DST_DID_END_DATE	created in 3.6.0	DATE	7	Y	Vendor did end date
SMS_CDR_ARCHIVE	CDR_DST_DID_START_DATE	created in 3.6.0	DATE	7	Y	Vendor did start date



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
SMS_CDR_ARCHIVE	CDR_FILE_ID	changed in 3.6.0	NUMBER	22	Y	CDR file ID references to SMS_CDR_FILE_STATUS table
SMS_CDR_ARCHIVE	CDR_HLR_RESPONSE_CODE	created in 3.6.0	VARCHAR2	4000	Y	HLR response code
SMS_CDR_ARCHIVE	CDR_IS_DST_DID	created in 3.6.0	NUMBER	22	Y	Is SMS sent to the DID number currently linked to the vendor product in the DVD refbook
SMS_CDR_ARCHIVE	CDR_IS_SRC_DID	created in 3.6.0	NUMBER	22	Y	Is SMS sent to the DID number currently linked to the client product in the DVD refbook
SMS_CDR_ARCHIVE	CDR_SRC_DID_BILL_SCHEME_ID	created in 3.6.0	NUMBER	22	Y	Client Billing scheme ID
SMS_CDR_ARCHIVE	CDR_SRC_DID_END_DATE	created in 3.6.0	DATE	7	Y	Client did end date



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
SMS_CDR_ARCHIVE	CDR_SRC_DID_START_DATE	created in 3.6.0	DATE	7	Y	Client did start date
SMS_CDR_ARCHIVE	CDR_START_TIME	changed in 3.6.0	DATE	7	Y	Route start time
SMS_CDR_ARCHIVE	CDR_STOP_TIME	changed in 3.6.0	DATE	7	Y	Route stop time
SMS_CDR_ARCHIVE	CDR_TRANSLATION_RULE_DETAILS	created in 3.6.0	VARCHAR2	4000	Y	Translation rule details
SMS_CDR_ARCHIVE	HLRCACHED	created in 3.6.0	NUMBER	22	Y	HLR cached
SMS_CDR_ARCHIVE	HLRPORTED	created in 3.6.0	VARCHAR2	8	Y	HLR Ported
SMS_CDR_ARCHIVE	HLRSOURCENAME	created in 3.6.0	VARCHAR2	64	Y	HLR source name
SMS_CDR_ARCHIVE	HLRSOURCETYPE	created in 3.6.0	VARCHAR2	64	Y	HLR source type
SMS_CDR_ARCHIVE	REVERSE_CHARGE_DST	created in 3.6.0	NUMBER	22	Y	Reverse charge for DST (-1,1)



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
SMS_CDR_ARCHIVE	REVERSE_CHARGE_SRC	created in 3.6.0	NUMBER	22	Y	Reverse charge for SRC (-1,1)
SMS_CDR_ARCHIVE	SARPARTNUMBER	created in 3.6.0	NUMBER	22	Y	SAR part number
SMS_CDR_ARCHIVE	STATEFULPROCESSING	created in 3.6.0	NUMBER	22	Y	Stateful processing
SMS_CDR_BFRD	BILL_AMOUNT_DST	created in 3.6.0	NUMBER	22	Y	Vendor billable amount
SMS_CDR_BFRD	BILL_AMOUNT_SRC	created in 3.6.0	NUMBER	22	Y	Client billable amount
SMS_CDR_BFRD	CDR_ACTIVATION_TIME	created in 3.6.0	DATE	7	Y	Time when was received status ACTIVATED
SMS_CDR_BFRD	CDR_DST_DID_BILL_SCHEME_ID	created in 3.6.0	NUMBER	22	Y	Vendor Billing scheme ID
SMS_CDR_BFRD	CDR_DST_DID_END_DATE	created in 3.6.0	DATE	7	Y	Vendor did end date
SMS_CDR_BFRD	CDR_DST_DID_START_DATE	created in 3.6.0	DATE	7	Y	Vendor did start date



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
SMS_CDR_BFRD	CDR_IS_DST_DID	created in 3.6.0	NUMBER	22	Y	Is SMS sent to the DID number currently linked to the vendor product in the DVD refbook
SMS_CDR_BFRD	CDR_IS_SRC_DID	created in 3.6.0	NUMBER	22	Y	Is SMS sent to the DID number currently linked to the client product in the DVD refbook
SMS_CDR_BFRD	CDR_SRC_DID_BILL_SCHEME_ID	created in 3.6.0	NUMBER	22	Y	Client Billing scheme ID
SMS_CDR_BFRD	CDR_SRC_DID_END_DATE	created in 3.6.0	DATE	7	Y	Client did end date
SMS_CDR_BFRD	CDR_SRC_DID_START_DATE	created in 3.6.0	DATE	7	Y	Client did start date
SMS_CDR_BFRD	HLRCACHED	created in 3.6.0	NUMBER	22	Y	HLR cached
SMS_CDR_BFRD	HLRPORTED	created in 3.6.0	VARCHAR2	8	Y	HLR Ported



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
SMS_CDR_BFRD	HLRSOURCENAME	created in 3.6.0	VARCHAR2	64	Y	HLR source name
SMS_CDR_BFRD	HLRSOURCETYPE	created in 3.6.0	VARCHAR2	64	Y	HLR source type
SMS_CDR_BFRD	REVERSE_CHARGE_DS T	created in 3.6.0	NUMBER	22	Y	Reverse charge for DST (-1,1)
SMS_CDR_BFRD	REVERSE_CHARGE_SR C	created in 3.6.0	NUMBER	22	Y	Reverse charge for SRC (-1,1)
SMS_CDR_BFRD	SARPARTNUMBER	created in 3.6.0	NUMBER	22	Y	SAR part number
SMS_CDR_BFRD	STATEFULPROCESSING	created in 3.6.0	NUMBER	22	Y	Stateful processing
SMS_CDR_ERROR_LOG	-- Table --	deleted in 3.6.0				DML Error Logging table for "SMS_CDR"
SMS_CDR_ERROR_LOG	CDR_ATTEMPT_NUM	deleted in 3.6.0	VARCHAR2	4000	Y	Attempt number
SMS_CDR_ERROR_LOG	CDR_CALLED	deleted in 3.6.0	VARCHAR2	4000	Y	B-number e.164
SMS_CDR_ERROR_LOG	CDR_CALLING	deleted in 3.6.0	VARCHAR2	4000	Y	A-number e.164



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
SMS_CDR_ERROR_LOG	CDR_DELIVERY_ERRMSG	deleted in 3.6.0	VARCHAR2	4000	Y	Delivery error message
SMS_CDR_ERROR_LOG	CDR_DELIVERY_STATUS	deleted in 3.6.0	VARCHAR2	4000	Y	Deliver status
SMS_CDR_ERROR_LOG	CDR_DELIVERY_TIME	deleted in 3.6.0	VARCHAR2	4000	Y	SMS delivery time
SMS_CDR_ERROR_LOG	CDR_DIAL_CODE	deleted in 3.6.0	VARCHAR2	4000	Y	Destination e.164 dial code
SMS_CDR_ERROR_LOG	CDR_DLR_TECH_DETAILS	deleted in 3.6.0	VARCHAR2	4000	Y	Delivery technical details
SMS_CDR_ERROR_LOG	CDR_DONE_DATE	deleted in 3.6.0	VARCHAR2	4000	Y	Date of delivery arrival
SMS_CDR_ERROR_LOG	CDR_DST_CURRENCY_CODE	deleted in 3.6.0	VARCHAR2	4000	Y	Vendor rate currency
SMS_CDR_ERROR_LOG	CDR_DST_GUID	deleted in 3.6.0	VARCHAR2	4000	Y	Vendor SMSC GUID
SMS_CDR_ERROR_LOG	CDR_DST_IP	deleted in 3.6.0	VARCHAR2	4000	Y	Vendor SMSC IP address



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
SMS_CDR_ERROR_LOG	CDR_DST_IS_SUCCESSFUL	deleted in 3.6.0	VARCHAR2	4000	Y	Vendor success flag: 1 - successful sms, 0 - not successful
SMS_CDR_ERROR_LOG	CDR_DST_MCC_MNC	deleted in 3.6.0	VARCHAR2	4000	Y	Destination MCCMNC from vendor rates
SMS_CDR_ERROR_LOG	CDR_DST_MSG_ID	deleted in 3.6.0	VARCHAR2	4000	Y	Message ID
SMS_CDR_ERROR_LOG	CDR_DST_PART_AMOUNT	deleted in 3.6.0	VARCHAR2	4000	Y	Amount of billable parts (Vendor)
SMS_CDR_ERROR_LOG	CDR_DST_PORT	deleted in 3.6.0	VARCHAR2	4000	Y	Vendor SMSC port
SMS_CDR_ERROR_LOG	CDR_DST_PRODUCT_ID	deleted in 3.6.0	VARCHAR2	4000	Y	Vendor product ID
SMS_CDR_ERROR_LOG	CDR_DST_RATE	deleted in 3.6.0	VARCHAR2	4000	Y	Vendor rate
SMS_CDR_ERROR_LOG	CDR_DST_SERVICE_TYPE	deleted in 3.6.0	VARCHAR2	4000	Y	Vendor service type
SMS_CDR_ERROR_LOG	CDR_DST_SMSC_ID	deleted in 3.6.0	VARCHAR2	4000	Y	Vendor POI ID



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
SMS_CDR_ERROR_LOG	CDR_EDR_TYPE	deleted in 3.6.0	VARCHAR2	4000	Y	EDR type: 1 - usual, 2 - 2-way, 3 - test, 4 - buffered
SMS_CDR_ERROR_LOG	CDR_EXTRA	deleted in 3.6.0	VARCHAR2	4000	Y	Extra CDR field
SMS_CDR_ERROR_LOG	CDR_HLR	deleted in 3.6.0	VARCHAR2	4000	Y	Flag: 1 - MCCMNC from HLR, 0 - from routing/DB
SMS_CDR_ERROR_LOG	CDR_HLR_MCC_MNC	deleted in 3.6.0	VARCHAR2	4000	Y	HLR rate currency
SMS_CDR_ERROR_LOG	CDR_ID	deleted in 3.6.0	VARCHAR2	4000	Y	Record counter
SMS_CDR_ERROR_LOG	CDR_IS_LAST	deleted in 3.6.0	VARCHAR2	4000	Y	Flag: 1 - last attempt, 0 not last
SMS_CDR_ERROR_LOG	CDR_IS_SUCCESSFUL	deleted in 3.6.0	VARCHAR2	4000	Y	Flag: 1 - successful sms, 0 - not successful
SMS_CDR_ERROR_LOG	CDR_MCC_MNC	deleted in 3.6.0	VARCHAR2	4000	Y	Destination MCCMNC
SMS_CDR_ERROR_LOG	CDR_RULE_ID	deleted in 3.6.0	VARCHAR2	4000	Y	Routing rule ID



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
SMS_CDR_ERROR_LOG	CDR_SRC_CURRENCY_CODE	deleted in 3.6.0	VARCHAR2	4000	Y	Client rate currency
SMS_CDR_ERROR_LOG	CDR_SRC_GUID	deleted in 3.6.0	VARCHAR2	4000	Y	Client SMSC GUID
SMS_CDR_ERROR_LOG	CDR_SRC_IP	deleted in 3.6.0	VARCHAR2	4000	Y	Client SMSC IP address
SMS_CDR_ERROR_LOG	CDR_SRC_IS_SUCCESSFUL	deleted in 3.6.0	VARCHAR2	4000	Y	Client success flag: 1 - successful sms, 0 - not successful
SMS_CDR_ERROR_LOG	CDR_SRC_MCC_MNC	deleted in 3.6.0	VARCHAR2	4000	Y	Destination MCCMNC from client rates
SMS_CDR_ERROR_LOG	CDR_SRC_MSG_ID	deleted in 3.6.0	VARCHAR2	4000	Y	SMS session transaction ID generated by SMS Switch for the client
SMS_CDR_ERROR_LOG	CDR_SRC_PART_AMOUNT	deleted in 3.6.0	VARCHAR2	4000	Y	Amount of billable parts (Client)
SMS_CDR_ERROR_LOG	CDR_SRC_PORT	deleted in 3.6.0	VARCHAR2	4000	Y	Client SMSC port



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
SMS_CDR_ERROR_LOG	CDR_SRC_PRODUCT_ID	deleted in 3.6.0	VARCHAR2	4000	Y	Client product ID
SMS_CDR_ERROR_LOG	CDR_SRC_RATE	deleted in 3.6.0	VARCHAR2	4000	Y	Client rate
SMS_CDR_ERROR_LOG	CDR_SRC_SERVICE_TYPE	deleted in 3.6.0	VARCHAR2	4000	Y	Client service type
SMS_CDR_ERROR_LOG	CDR_SRC_SMSC_ID	deleted in 3.6.0	VARCHAR2	4000	Y	Client POI ID
SMS_CDR_ERROR_LOG	CDR_START_TIME	deleted in 3.6.0	VARCHAR2	4000	Y	Route start time
SMS_CDR_ERROR_LOG	CDR_STATUS	deleted in 3.6.0	VARCHAR2	4000	Y	SMS status, i.e. SENT, DELVRD according to smpp protocol
SMS_CDR_ERROR_LOG	CDR_STATUS_CODE	deleted in 3.6.0	VARCHAR2	4000	Y	Numeric code of SMS status
SMS_CDR_ERROR_LOG	CDR_STOP_TIME	deleted in 3.6.0	VARCHAR2	4000	Y	Route stop time
SMS_CDR_ERROR_LOG	CDR_TECH_DETAILS	deleted in 3.6.0	VARCHAR2	4000	Y	SMS technical details packed in JSON



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
SMS_CDR_ERROR_LOG	CDR_TIME	deleted in 3.6.0	VARCHAR2	4000	Y	Message time
SMS_CDR_ERROR_LOG	CDR_TRANSACTION_ID	deleted in 3.6.0	VARCHAR2	4000	Y	Transaction ID
SMS_CDR_ERROR_LOG	CDR_VENDOR_ANI	deleted in 3.6.0	VARCHAR2	4000	Y	Translated vendor ANI
SMS_CDR_ERROR_LOG	ORA_ERR_MESG\$	deleted in 3.6.0	VARCHAR2	2000	Y	Error message
SMS_CDR_ERROR_LOG	ORA_ERR_NUMBER\$	deleted in 3.6.0	NUMBER	22	Y	Error ORA number
SMS_CDR_ERROR_LOG	ORA_ERR_OPTYP\$	deleted in 3.6.0	VARCHAR2	2	Y	Error ORA type
SMS_CDR_ERROR_LOG	ORA_ERR_ROWID\$	deleted in 3.6.0	UROWID	4000	Y	Error ROWID
SMS_CDR_ERROR_LOG	ORA_ERR_TAG\$	deleted in 3.6.0	VARCHAR2	2000	Y	Error tag
SMS_CDR_RECON_OWN_TMP	-- Table --	created in 3.6.0				Temporary table for SMS CDR reconciliation
SMS_CDR_RECON_PRT_TMP	-- Table --	created in 3.6.0				Temporary table for SMS CDR reconciliation



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
SMS_CDR_RECON_RESULT	OWNER_STATUS	created in 3.6.0	VARCHAR2	128	Y	Owner status
SMS_CDR_RECON_RESULT	PARTNER_STATUS	created in 3.6.0	VARCHAR2	128	Y	Partner status
SMS_CDR_STATUS	ATTEMPT_NO	created in 3.6.0	NUMBER	22	Y	Processing attempt number
SMS_CDR_STATUS	IM_CHANNEL	created in 3.6.0	VARCHAR2	4000	Y	IM channel
SMS_CDR_STATUS	NEXT_PROCESS_DATE	created in 3.6.0	DATE	7	Y	Next processing date
SMS_CDR_STATUS	REROUTE_FLAG	created in 3.6.0	NUMBER	22	Y	need reroute
SMS_CDR_STATUS_POSTPONE	IM_CHANNEL	created in 3.6.0	VARCHAR2	4000	Y	IM channel
SMS_CDR_STATUS_TMP	-- Table --	created in 3.6.0				Temporary table for SMS delivery report processing
SMS_CDR_TEXT_ERROR_LOG	-- Table --	deleted in 3.6.0				Error log table for SMS_CDR_TEXT



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
SMS_CDR_TEXT_ERROR_LOG	CDR_DIRECTION	deleted in 3.6.0	VARCHAR2	4000	Y	Direction (0 - client, 1 - vendor)
SMS_CDR_TEXT_ERROR_LOG	CDR_DST_MSG_ID	deleted in 3.6.0	VARCHAR2	4000	Y	Vendor message ID
SMS_CDR_TEXT_ERROR_LOG	CDR_TEXT	deleted in 3.6.0	VARCHAR2	4000	Y	Text
SMS_CDR_TEXT_ERROR_LOG	CDR_TEXT_PART_NUMBER	deleted in 3.6.0	VARCHAR2	4000	Y	Text part number
SMS_CDR_TEXT_ERROR_LOG	CDR_TIME	deleted in 3.6.0	VARCHAR2	4000	Y	EDR time
SMS_CDR_TEXT_ERROR_LOG	CDR_TRANSACTION_ID	deleted in 3.6.0	VARCHAR2	4000	Y	Transaction ID
SMS_CDR_TEXT_ERROR_LOG	ORA_ERR_MESG\$	deleted in 3.6.0	VARCHAR2	2000	Y	ORA error message
SMS_CDR_TEXT_ERROR_LOG	ORA_ERR_NUMBER\$	deleted in 3.6.0	NUMBER	22	Y	ORA error number



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
SMS_CDR_TEXT_ERROR_LOG	ORA_ERR_OPTYP\$	deleted in 3.6.0	VARCHAR2	2	Y	ORA error type
SMS_CDR_TEXT_ERROR_LOG	ORA_ERR_ROWID\$	deleted in 3.6.0	UROWID	4000	Y	ORA error rowid
SMS_CDR_TEXT_ERROR_LOG	ORA_ERR_TAG\$	deleted in 3.6.0	VARCHAR2	2000	Y	ORA error tag
SMS_CDR_TMP	-- Table --	created in 3.6.0				Temporary table for SMS CDR processing
SMS_CDR_TMP	BILL_AMOUNT_DST	created in 3.6.0	NUMBER	22	Y	103 vendor billable amount
SMS_CDR_TMP	BILL_AMOUNT_SRC	created in 3.6.0	NUMBER	22	Y	102 client billable amount
SMS_CDR_TMP	CDR_ATTEMPT_NUM	created in 3.6.0	NUMBER	22	Y	29 attempt number
SMS_CDR_TMP	CDR_CALLED	created in 3.6.0	VARCHAR2	32	Y	6 b-number e.164
SMS_CDR_TMP	CDR_CALLING	created in 3.6.0	VARCHAR2	32	Y	5 a-number e.164



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
SMS_CDR_TMP	CDR_DELIVERY_STATU S	created in 3.6.0	NUMBER	22	Y	25 technical delivery code
SMS_CDR_TMP	CDR_DIAL_CODE	created in 3.6.0	VARCHAR2	16	Y	32 destination e.164 dial code
SMS_CDR_TMP	CDR_DLR_TECH_DETAI LS	created in 3.6.0	VARCHAR2	4000	Y	55 dlr technical details
SMS_CDR_TMP	CDR_DST_COST	created in 3.6.0	NUMBER	22	Y	75 vendor rate with tax
SMS_CDR_TMP	CDR_DST_CURRENCY_ CODE	created in 3.6.0	VARCHAR2	16	Y	24 vendor rate currency
SMS_CDR_TMP	CDR_DST_DIAL_CODE	created in 3.6.0	VARCHAR2	16	Y	47 dial code from vendor rate
SMS_CDR_TMP	CDR_DST_DID_BILL_SC HEME_ID	created in 3.6.0	NUMBER	22	Y	93 vendor billing scheme id
SMS_CDR_TMP	CDR_DST_DID_END_D ATE	created in 3.6.0	DATE	7	Y	92 vendor did end date



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
SMS_CDR_TMP	CDR_DST_DID_START_DATE	created in 3.6.0	DATE	7	Y	91 vendor did start date
SMS_CDR_TMP	CDR_DST_GUID	created in 3.6.0	VARCHAR2	36	Y	17 vendor smsc guid
SMS_CDR_TMP	CDR_DST_IP	created in 3.6.0	VARCHAR2	64	Y	18 vendor smsc ip address
SMS_CDR_TMP	CDR_DST_IS_SUCCESSFUL	created in 3.6.0	NUMBER	22	Y	43 vendor success flag: 1 - successful sms, 0 - not successful
SMS_CDR_TMP	CDR_DST_MCC_MNC	created in 3.6.0	VARCHAR2	6	Y	16 destination mccmnc from vendor rates
SMS_CDR_TMP	CDR_DST_MSG_ID	created in 3.6.0	VARCHAR2	65	Y	1 message id
SMS_CDR_TMP	CDR_DST_PART_AMOUNT	created in 3.6.0	NUMBER	22	Y	40 amount of billable parts (vendor)
SMS_CDR_TMP	CDR_DST_PORT	created in 3.6.0	NUMBER	22	Y	19 vendor smsc port
SMS_CDR_TMP	CDR_DST_PRODUCT_ID	created in 3.6.0	NUMBER	22	Y	22 vendor product id



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
SMS_CDR_TMP	CDR_DST_RATE	created in 3.6.0	NUMBER	22	Y	23 vendor rate
SMS_CDR_TMP	CDR_DST_RATE_ID	created in 3.6.0	NUMBER	22	Y	81
SMS_CDR_TMP	CDR_DST_SENDER_COUNTRY	created in 3.6.0	NUMBER	22	Y	85 vendor sender country id
SMS_CDR_TMP	CDR_DST_SENDER_ID_DATA	created in 3.6.0	VARCHAR2	16	Y	83 vendor sender mccmnc/id
SMS_CDR_TMP	CDR_DST_SENT_TIME	created in 3.6.0	DATE	7	Y	50 time when the submit has been sent to socket buffer
SMS_CDR_TMP	CDR_DST_SERVICE_TYPE	created in 3.6.0	VARCHAR2	9	Y	20 vendor service type
SMS_CDR_TMP	CDR_DST_SMSC_ID	created in 3.6.0	NUMBER	22	Y	21 vendor poi id
SMS_CDR_TMP	CDR_DST_TAX	created in 3.6.0	NUMBER	22	Y	76 vendor tax amount
SMS_CDR_TMP	CDR_DST_TAX_RATE	created in 3.6.0	NUMBER	22	Y	77 vendor tax rate



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
SMS_CDR_TMP	CDR_EDR_TYPE	created in 3.6.0	NUMBER	22	Y	44 edr type: 1 - usual, 2 - 2-way, 3 - test, 4 - buffered
SMS_CDR_TMP	CDR_EXTRA	created in 3.6.0	VARCHAR2	4000	Y	37 extra cdr field
SMS_CDR_TMP	CDR_HLR	created in 3.6.0	NUMBER	22	Y	28 flag: 1 - mccmnc from hlr, 0 - from routing/db
SMS_CDR_TMP	CDR_HLR_CURRENCY_CODE	created in 3.6.0	VARCHAR2	16	Y	54 hlr rate currency
SMS_CDR_TMP	CDR_HLR_MCC_MNC	created in 3.6.0	VARCHAR2	16	Y	33 destination mccmnc from hlr
SMS_CDR_TMP	CDR_HLR_PRODUCT_ID	created in 3.6.0	NUMBER	22	Y	53 hlr product id
SMS_CDR_TMP	CDR_HLR_RATE	created in 3.6.0	NUMBER	22	Y	48 hlr rate
SMS_CDR_TMP	CDR_HLR_RESPONSE_CODE	created in 3.6.0	VARCHAR2	4000	Y	57 hlr response code
SMS_CDR_TMP	CDR_HOST	created in 3.6.0	VARCHAR2	65	Y	45 switch ipv4 address



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
SMS_CDR_TMP	CDR_ID	created in 3.6.0	NUMBER	22	Y	0 record counter
SMS_CDR_TMP	CDR_IM_CHANNEL	created in 3.6.0	VARCHAR2	64	Y	56 im channel
SMS_CDR_TMP	CDR_IS_DST_DID	created in 3.6.0	NUMBER	22	Y	87 is sms sent to the did number currently linked to the vendor product in the dvd refbook
SMS_CDR_TMP	CDR_IS_LAST	created in 3.6.0	NUMBER	22	Y	30 flag: 1 - last attempt, 0 not last
SMS_CDR_TMP	CDR_IS_SRC_DID	created in 3.6.0	NUMBER	22	Y	86 is sms sent to the did number currently linked to the client product in the dvd refbook
SMS_CDR_TMP	CDR_IS_SUCCESSFUL	created in 3.6.0	NUMBER	22	Y	3 flag: 1 - successful sms, 0 - not successful
SMS_CDR_TMP	CDR_MCC_MNC	created in 3.6.0	VARCHAR2	6	Y	31 destination mcmnc



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
SMS_CDR_TMP	CDR_RULE_ID	created in 3.6.0	NUMBER	22	Y	49 routing rule id
SMS_CDR_TMP	CDR_SRC_COST	created in 3.6.0	NUMBER	22	Y	72 client rate with tax
SMS_CDR_TMP	CDR_SRC_CURRENCY_CODE	created in 3.6.0	VARCHAR2	16	Y	15 client rate currency
SMS_CDR_TMP	CDR_SRC_DIAL_CODE	created in 3.6.0	VARCHAR2	16	Y	46 dial code from client rate
SMS_CDR_TMP	CDR_SRC_DID_BILL_SCHEME_ID	created in 3.6.0	NUMBER	22	Y	90 client billing scheme id
SMS_CDR_TMP	CDR_SRC_DID_END_DATE	created in 3.6.0	DATE	7	Y	89 client did end date
SMS_CDR_TMP	CDR_SRC_DID_START_DATE	created in 3.6.0	DATE	7	Y	88 client did start date
SMS_CDR_TMP	CDR_SRC_GUID	created in 3.6.0	VARCHAR2	36	Y	8 client smsc guid
SMS_CDR_TMP	CDR_SRC_IP	created in 3.6.0	VARCHAR2	64	Y	9 client smsc ip address



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
SMS_CDR_TMP	CDR_SRC_IS_SUCCESSFUL	created in 3.6.0	NUMBER	22	Y	42 client success flag: 1 - successful sms, 0 - not successful
SMS_CDR_TMP	CDR_SRC_MCC_MNC	created in 3.6.0	VARCHAR2	6	Y	7 destination mccmnc from client rates
SMS_CDR_TMP	CDR_SRC_MSG_ID	created in 3.6.0	VARCHAR2	65	Y	34 sms session transaction id generated by sms switch for the client
SMS_CDR_TMP	CDR_SRC_PART_AMOUNT	created in 3.6.0	NUMBER	22	Y	39 amount of billable parts (client)
SMS_CDR_TMP	CDR_SRC_PORT	created in 3.6.0	NUMBER	22	Y	10 client smsc port
SMS_CDR_TMP	CDR_SRC_PRODUCT_ID	created in 3.6.0	NUMBER	22	Y	13 client product id
SMS_CDR_TMP	CDR_SRC_RATE	created in 3.6.0	NUMBER	22	Y	14 client rate
SMS_CDR_TMP	CDR_SRC_RATE_ID	created in 3.6.0	NUMBER	22	Y	80



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
SMS_CDR_TMP	CDR_SRC_SENDER_COUNTRY	created in 3.6.0	NUMBER	22	Y	84 client sender country id
SMS_CDR_TMP	CDR_SRC_SENDER_ID_DATA	created in 3.6.0	VARCHAR2	16	Y	82 client sender mccmnc/id
SMS_CDR_TMP	CDR_SRC_SERVICE_TYPE	created in 3.6.0	VARCHAR2	9	Y	11 client service type
SMS_CDR_TMP	CDR_SRC_SMSC_ID	created in 3.6.0	NUMBER	22	Y	12 client poi id
SMS_CDR_TMP	CDR_SRC_TAX	created in 3.6.0	NUMBER	22	Y	73 client tax amount
SMS_CDR_TMP	CDR_SRC_TAX_RATE	created in 3.6.0	NUMBER	22	Y	74 client tax rate
SMS_CDR_TMP	CDR_START_TIME	created in 3.6.0	DATE	7	Y	26 current attempt start time
SMS_CDR_TMP	CDR_STATUS	created in 3.6.0	VARCHAR2	30	Y	4 sms status, i.e. sent, delvrd according to smpp protocol



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
SMS_CDR_TMP	CDR_STATUS_CODE	created in 3.6.0	NUMBER	22	Y	35 numeric code of sms status
SMS_CDR_TMP	CDR_STOP_TIME	created in 3.6.0	DATE	7	Y	27 current attempt stop time
SMS_CDR_TMP	CDR_TECH_DETAILS	created in 3.6.0	VARCHAR2	4000	Y	38 sms technical details packed in json
SMS_CDR_TMP	CDR_TEXT	created in 3.6.0	VARCHAR2	4000	Y	41 cdr text
SMS_CDR_TMP	CDR_TIME	created in 3.6.0	DATE	7	Y	2 message time
SMS_CDR_TMP	CDR_TRANSACTION_ID	created in 3.6.0	VARCHAR2	65	Y	51 transaction id
SMS_CDR_TMP	CDR_TRANSLATED_TEXT	created in 3.6.0	VARCHAR2	4000	Y	52 Translated text
SMS_CDR_TMP	CDR_TRANSLATION_RULE_DETAILS	created in 3.6.0	VARCHAR2	4000	Y	58 translation rule details
SMS_CDR_TMP	CDR_VENDOR_ANI	created in 3.6.0	VARCHAR2	32	Y	36 translated vendor ani



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
SMS_CDR_TMP	CHANGED	created in 3.6.0	VARCHAR2	1	Y	59
SMS_CDR_TMP	DST_BILL_DELIVERED_ONLY	created in 3.6.0	NUMBER	22	Y	68
SMS_CDR_TMP	DST_MCC_MNC_FOR_RATE	created in 3.6.0	VARCHAR2	16	Y	71
SMS_CDR_TMP	DST_PARENT_PRODUCT_ID	created in 3.6.0	NUMBER	22	Y	67
SMS_CDR_TMP	DST_PRODUCT_DIRECTION	created in 3.6.0	NUMBER	22	Y	66
SMS_CDR_TMP	DST_RATE_INHERITANCE_MODE	created in 3.6.0	NUMBER	22	Y	69
SMS_CDR_TMP	DST_TAX_SCHEME_ID	created in 3.6.0	NUMBER	22	Y	79
SMS_CDR_TMP	DST_USE_SENDER_MC_CMNC_RATES	created in 3.6.0	NUMBER	22	Y	70
SMS_CDR_TMP	HLRCACHED	created in 3.6.0	NUMBER	22	Y	96 hlr cached



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
SMS_CDR_TMP	HLRPORTED	created in 3.6.0	VARCHAR2	8	Y	97 hlr ported
SMS_CDR_TMP	HLRSOURCENAME	created in 3.6.0	VARCHAR2	64	Y	98 hlr source name
SMS_CDR_TMP	HLRSOURCETYPE	created in 3.6.0	VARCHAR2	64	Y	101 hlr source type
SMS_CDR_TMP	NEED_RERATING	created in 3.6.0	NUMBER	22	Y	95
SMS_CDR_TMP	RECORD_HASH	created in 3.6.0	NUMBER	22	Y	94
SMS_CDR_TMP	REVERSE_CHARGE_DS T	created in 3.6.0	NUMBER	22	Y	Reverse charge for DST (-1,1)
SMS_CDR_TMP	REVERSE_CHARGE_SR C	created in 3.6.0	NUMBER	22	Y	Reverse charge for SRC (-1,1)
SMS_CDR_TMP	SARPARTNUMBER	created in 3.6.0	NUMBER	22	Y	100 sar part number
SMS_CDR_TMP	SRC_BILL_DELIVERED_ ONLY	created in 3.6.0	NUMBER	22	Y	62



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
SMS_CDR_TMP	SRC_MCC_MNC_FOR_RATE	created in 3.6.0	VARCHAR2	16	Y	65
SMS_CDR_TMP	SRC_PARENT_PRODUCT_ID	created in 3.6.0	NUMBER	22	Y	61
SMS_CDR_TMP	SRC_PRODUCT_DIRECTION	created in 3.6.0	NUMBER	22	Y	60
SMS_CDR_TMP	SRC_RATE_INHERITANCE_MODE	created in 3.6.0	NUMBER	22	Y	63
SMS_CDR_TMP	SRC_TAX_SCHEME_ID	created in 3.6.0	NUMBER	22	Y	78
SMS_CDR_TMP	SRC_USE_SENDER_MC_CMNC_RATES	created in 3.6.0	NUMBER	22	Y	64
SMS_CDR_TMP	STATEFULPROCESSING	created in 3.6.0	NUMBER	22	Y	99 stateful processing
SMS_CHANNEL	CALLBACK_TIMEOUT	created in 3.6.0	NUMBER	22	Y	Callback timeout, sec
SMS_CHANNEL	CREATED_BY	changed in 3.6.0	VARCHAR2	256	Y	Created by



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
SMS_CHANNEL	DLR_PUSH_HTTP_HEADERS	created in 3.6.0	VARCHAR2	2000	Y	DLR push HTTP headers
SMS_CHANNEL	DLR_PUSH_POST_TEMPLATE	created in 3.6.0	VARCHAR2	2000	Y	DLR push POST template
SMS_CHANNEL	FAST_RESPONSE_SEGMENT	created in 3.6.0	NUMBER	22	Y	Fast response for segmented submits
SMS_CHANNEL	HTTP_HEADERS	created in 3.6.0	VARCHAR2	4000	Y	List of HTTP headers
SMS_CHANNEL	MO_PUSH_HTTP_HEADERS	created in 3.6.0	VARCHAR2	2000	Y	MO push HTTP headers
SMS_CHANNEL	MO_PUSH_POST_TEMPLATE	created in 3.6.0	VARCHAR2	2000	Y	MO push POST template
SMS_CHANNEL	PARTNER_DIRECTION	created in 3.6.0	NUMBER	22	Y	Partner direction
SMS_CHANNEL	REJECT_INCOMPLETED_LONG_MSG	created in 3.6.0	NUMBER	22	Y	Reject incomplete segmented messages



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
SMS_CHANNEL	SEGMENT_CONCATENATION_TIMEOUT	created in 3.6.0	NUMBER	22	Y	segmented submit waiting period timeout.
SMS_CHANNEL	VALIDITY_PERIOD_VENDOR_FORMAT	changed in 3.6.0	NUMBER	22	N	Validity Period To Vendor Format (abs_0_timezone = 0 (default value), as_received = 1, relative = 2, abs_server_timezone = 3)
SMS_CHANNEL_STATUS	SWITCH_ID	created in 3.6.0	VARCHAR2	256	Y	Switch id
SMS_CHANNEL_STATUS_CHANGE	SWITCH_ID	created in 3.6.0	VARCHAR2	256	Y	Switch id
SMS_CHANNEL_STATUS_SW	-- Table --	created in 3.6.0				SMS channel and switch statuses
SMS_CHANNEL_STATUS_SW	ADDRESS	created in 3.6.0	VARCHAR2	256	Y	Carrier address
SMS_CHANNEL_STATUS_SW	BOUND_TIME	created in 3.6.0	VARCHAR2	256	Y	Bound time



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
SMS_CHANNEL_STATUS_SW	CHANNEL_COUNT	created in 3.6.0	VARCHAR2	256	Y	Channel bind number
SMS_CHANNEL_STATUS_SW	CHANNEL_DIRECTION	created in 3.6.0	VARCHAR2	256	Y	Channel direction CLI/VND/CLIR/CLIB/CLIRB
SMS_CHANNEL_STATUS_SW	CHANNEL_ID	created in 3.6.0	VARCHAR2	256	Y	Channel ID (primary key)
SMS_CHANNEL_STATUS_SW	CHANNEL_LOCAL_ADDRESS	created in 3.6.0	VARCHAR2	256	Y	Channel bind address
SMS_CHANNEL_STATUS_SW	CHANNEL_TYPE	created in 3.6.0	VARCHAR2	256	Y	Channel type
SMS_CHANNEL_STATUS_SW	DLR_COUNT	created in 3.6.0	VARCHAR2	256	Y	Number of new DLRs DLR records
SMS_CHANNEL_STATUS_SW	MPS_BUFFER	created in 3.6.0	VARCHAR2	256	Y	Mps buffer
SMS_CHANNEL_STATUS_SW	SMS_COUNT	created in 3.6.0	VARCHAR2	256	Y	Sms count



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
SMS_CHANNEL_STATUS_SW	STATUS	created in 3.6.0	VARCHAR2	256	Y	Status
SMS_CHANNEL_STATUS_SW	STATUS_CODE	created in 3.6.0	VARCHAR2	256	Y	Status code
SMS_CHANNEL_STATUS_SW	SUBMIT_BUFFER	created in 3.6.0	VARCHAR2	256	Y	Submit buffer
SMS_CHANNEL_STATUS_SW	SWITCH_ID	created in 3.6.0	VARCHAR2	256	Y	Switch id
SMS_CHANNEL_STATUS_SW	UPDATE_TIME	created in 3.6.0	VARCHAR2	256	Y	Update time
SMS_CHANNEL_TLV_FIELDS	-- Table --	created in 3.6.0				SMS channel TLV codes
SMS_CHANNEL_TLV_FIELDS	TLV_CODE	created in 3.6.0	VARCHAR2	16	Y	TLV code
SMS_CHANNEL_TLV_FIELDS	TLV_DESCR	created in 3.6.0	VARCHAR2	4000	Y	TLV code description



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
SMS_CUBE_DAY	CDR_STATUS	created in 3.6.0	VARCHAR2	30	Y	CDR status
SMS_CUBE_DAY	CLIENT_SENDER_ID	created in 3.6.0	VARCHAR2	32	Y	Client sender ID
SMS_CUBE_DAY	COUNT_TOTAL_SRC	created in 3.6.0	NUMBER	22	Y	Count total for client
SMS_CUBE_DAY	DST_TAX_LIST	created in 3.6.0	VARCHAR2	64	Y	Vendor tax list
SMS_CUBE_DAY	HLR_RESPONSE_CODE	created in 3.6.0	VARCHAR2	4000	Y	HLR response code
SMS_CUBE_DAY	MSG_TYPE	created in 3.6.0	VARCHAR2	32	Y	Method full name Message type, i.e. bas_utils.get_carrier_list
SMS_CUBE_DAY	SRC_TAX_LIST	created in 3.6.0	VARCHAR2	64	Y	Client tax list
SMS_CUBE_DAY	SUCCESSFUL_HLR_COUNT	created in 3.6.0	NUMBER	22	Y	Successful hlr attempts count
SMS_CUBE_DAY	SUM_DST_CHARGE_WITH_TAX	created in 3.6.0	NUMBER	22	Y	Sum of vendor charges with taxes



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
SMS_CUBE_DAY	SUM_DST_CHARGE_W ITH_TAX2	created in 3.6.0	NUMBER	22	Y	Sum of vendor charges with taxes
SMS_CUBE_DAY	SUM_DST_CHARGE_W ITH_TAX3	created in 3.6.0	NUMBER	22	Y	Sum of vendor charges with taxes
SMS_CUBE_DAY	SUM_DST_TAX	created in 3.6.0	NUMBER	22	Y	Sum of vendor taxes
SMS_CUBE_DAY	SUM_DST_TAX2	created in 3.6.0	NUMBER	22	Y	Sum of vendor taxes
SMS_CUBE_DAY	SUM_DST_TAX3	created in 3.6.0	NUMBER	22	Y	Sum of vendor taxes
SMS_CUBE_DAY	SUM_MARGIN_FULL	created in 3.6.0	NUMBER	22	Y	Sum of margin
SMS_CUBE_DAY	SUM_MARGIN_FULL2	created in 3.6.0	NUMBER	22	Y	Sum of margin
SMS_CUBE_DAY	SUM_MARGIN_FULL3	created in 3.6.0	NUMBER	22	Y	Sum of margin
SMS_CUBE_DAY	SUM_SRC_CHARGE_W ITH_TAX	created in 3.6.0	NUMBER	22	Y	Sum of client charges with taxes



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
SMS_CUBE_DAY	SUM_SRC_CHARGE_W ITH_TAX2	created in 3.6.0	NUMBER	22	Y	Sum of client charges with taxes
SMS_CUBE_DAY	SUM_SRC_CHARGE_W ITH_TAX3	created in 3.6.0	NUMBER	22	Y	Sum of client charges with taxes
SMS_CUBE_DAY	SUM_SRC_TAX	created in 3.6.0	NUMBER	22	Y	Sum of client taxes
SMS_CUBE_DAY	SUM_SRC_TAX2	created in 3.6.0	NUMBER	22	Y	Sum of client taxes
SMS_CUBE_DAY	SUM_SRC_TAX3	created in 3.6.0	NUMBER	22	Y	Sum of client taxes
SMS_CUBE_DAY	TRAFFIC_SUBTYPE	created in 3.6.0	NUMBER	22	Y	Traffic subtype
SMS_CUBE_DAY	VENDOR_SENDER_ID	created in 3.6.0	VARCHAR2	32	Y	Vendor sender id
SMS_CUBE_EXCHANGE	COUNT_TOTAL_SRC	created in 3.6.0	NUMBER	22	Y	Count total for client
SMS_CUBE_EXCHANGE	DST_TAX_LIST	created in 3.6.0	VARCHAR2	64	Y	Vendor tax list
SMS_CUBE_EXCHANGE	SRC_TAX_LIST	created in 3.6.0	VARCHAR2	64	Y	Client tax list



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
SMS_CUBE_EXCHANGE	SUM_DST_COST	created in 3.6.0	NUMBER	22	Y	Sum of vendor costs
SMS_CUBE_EXCHANGE	SUM_DST_COST2	created in 3.6.0	NUMBER	22	Y	Sum of vendor costs
SMS_CUBE_EXCHANGE	SUM_DST_COST3	created in 3.6.0	NUMBER	22	Y	Sum of vendor costs
SMS_CUBE_EXCHANGE	SUM_DST_TAX	created in 3.6.0	NUMBER	22	Y	Sum of vendor taxes
SMS_CUBE_EXCHANGE	SUM_DST_TAX2	created in 3.6.0	NUMBER	22	Y	Sum of vendor taxes
SMS_CUBE_EXCHANGE	SUM_DST_TAX3	created in 3.6.0	NUMBER	22	Y	Sum of vendor taxes
SMS_CUBE_EXCHANGE	SUM_MARGIN_FULL	created in 3.6.0	NUMBER	22	Y	Sum of margin
SMS_CUBE_EXCHANGE	SUM_MARGIN_FULL2	created in 3.6.0	NUMBER	22	Y	Sum of margin
SMS_CUBE_EXCHANGE	SUM_MARGIN_FULL3	created in 3.6.0	NUMBER	22	Y	Sum of margin
SMS_CUBE_EXCHANGE	SUM_SRC_COST	created in 3.6.0	NUMBER	22	Y	Sum of src cost
SMS_CUBE_EXCHANGE	SUM_SRC_COST2	created in 3.6.0	NUMBER	22	Y	Sum of client costs



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
SMS_CUBE_EXCHANGE	SUM_SRC_COST3	created in 3.6.0	NUMBER	22	Y	Sum of client costs
SMS_CUBE_EXCHANGE	SUM_SRC_TAX	created in 3.6.0	NUMBER	22	Y	Sum of client taxes
SMS_CUBE_EXCHANGE	SUM_SRC_TAX2	created in 3.6.0	NUMBER	22	Y	Sum of client taxes
SMS_CUBE_EXCHANGE	SUM_SRC_TAX3	created in 3.6.0	NUMBER	22	Y	Sum of client taxes
SMS_CUBE_GROUP	CDR_STATUS	created in 3.6.0	NUMBER	22	N	cdr status
SMS_CUBE_GROUP	CLIENT_SENDER_ID	created in 3.6.0	NUMBER	22	N	Client sender ID
SMS_CUBE_GROUP	HLR_RESPONSE_CODE	created in 3.6.0	NUMBER	22	N	HLR response code
SMS_CUBE_GROUP	MSG_TYPE	created in 3.6.0	NUMBER	22	N	Method full name Message type, i.e. bas_utils.get_carrier_list
SMS_CUBE_GROUP	TRAFFIC_SUBTYPE	created in 3.6.0	NUMBER	22	N	Traffic subtype
SMS_CUBE_GROUP	VENDOR_SENDER_ID	created in 3.6.0	NUMBER	22	N	Vendor sender id



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
SMS_CUBE_HOUR	CDR_STATUS	created in 3.6.0	VARCHAR2	30	Y	CDR status
SMS_CUBE_HOUR	CLIENT_SENDER_ID	created in 3.6.0	VARCHAR2	32	Y	Client sender ID
SMS_CUBE_HOUR	COUNT_TOTAL_SRC	created in 3.6.0	NUMBER	22	Y	Count total for client
SMS_CUBE_HOUR	DST_TAX_LIST	created in 3.6.0	VARCHAR2	64	Y	Vendor tax list
SMS_CUBE_HOUR	HLR_RESPONSE_CODE	created in 3.6.0	VARCHAR2	4000	Y	HLR response code
SMS_CUBE_HOUR	MSG_TYPE	created in 3.6.0	VARCHAR2	32	Y	Method full name Message type, i.e. bas_utils.get_carrier_list
SMS_CUBE_HOUR	SRC_TAX_LIST	created in 3.6.0	VARCHAR2	64	Y	Client tax list
SMS_CUBE_HOUR	SUCCESSFUL_HLR_COUNT	created in 3.6.0	NUMBER	22	Y	Successful hlr attempts count
SMS_CUBE_HOUR	SUM_DST_CHARGE_WITH_TAX	created in 3.6.0	NUMBER	22	Y	Sum of vendor charges with taxes



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
SMS_CUBE_HOUR	SUM_DST_CHARGE_W ITH_TAX2	created in 3.6.0	NUMBER	22	Y	Sum of vendor charges with taxes
SMS_CUBE_HOUR	SUM_DST_CHARGE_W ITH_TAX3	created in 3.6.0	NUMBER	22	Y	Sum of vendor charges with taxes
SMS_CUBE_HOUR	SUM_DST_TAX	created in 3.6.0	NUMBER	22	Y	Sum of vendor taxes
SMS_CUBE_HOUR	SUM_DST_TAX2	created in 3.6.0	NUMBER	22	Y	Sum of vendor taxes
SMS_CUBE_HOUR	SUM_DST_TAX3	created in 3.6.0	NUMBER	22	Y	Sum of vendor taxes
SMS_CUBE_HOUR	SUM_MARGIN_FULL	created in 3.6.0	NUMBER	22	Y	Sum of margin
SMS_CUBE_HOUR	SUM_MARGIN_FULL2	created in 3.6.0	NUMBER	22	Y	Sum of margin
SMS_CUBE_HOUR	SUM_MARGIN_FULL3	created in 3.6.0	NUMBER	22	Y	Sum of margin
SMS_CUBE_HOUR	SUM_SRC_CHARGE_W ITH_TAX	created in 3.6.0	NUMBER	22	Y	Sum of client charges with taxes



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
SMS_CUBE_HOUR	SUM_SRC_CHARGE_WITH_TAX2	created in 3.6.0	NUMBER	22	Y	Sum of client charges with taxes
SMS_CUBE_HOUR	SUM_SRC_CHARGE_WITH_TAX3	created in 3.6.0	NUMBER	22	Y	Sum of client charges with taxes
SMS_CUBE_HOUR	SUM_SRC_TAX	created in 3.6.0	NUMBER	22	Y	Sum of client taxes
SMS_CUBE_HOUR	SUM_SRC_TAX2	created in 3.6.0	NUMBER	22	Y	Sum of client taxes
SMS_CUBE_HOUR	SUM_SRC_TAX3	created in 3.6.0	NUMBER	22	Y	Sum of client taxes
SMS_CUBE_HOUR	TRAFFIC_SUBTYPE	created in 3.6.0	NUMBER	22	Y	Traffic subtype
SMS_CUBE_HOUR	VENDOR_SENDER_ID	created in 3.6.0	VARCHAR2	32	Y	Vendor sender id
SMS_CUBE_MIN	CDR_STATUS	created in 3.6.0	VARCHAR2	30	Y	CDR status
SMS_CUBE_MIN	CLIENT_SENDER_ID	created in 3.6.0	VARCHAR2	32	Y	Client sender ID
SMS_CUBE_MIN	COUNT_TOTAL_SRC	created in 3.6.0	NUMBER	22	Y	Count total for client



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
SMS_CUBE_MIN	DST_TAX_LIST	created in 3.6.0	VARCHAR2	64	Y	Vendor tax list
SMS_CUBE_MIN	HLR_RESPONSE_CODE	created in 3.6.0	VARCHAR2	4000	Y	HLR response code
SMS_CUBE_MIN	MSG_TYPE	created in 3.6.0	VARCHAR2	32	Y	Method full name Message type, i.e. bas_utils.get_carrier_list
SMS_CUBE_MIN	SRC_TAX_LIST	created in 3.6.0	VARCHAR2	64	Y	Client tax list
SMS_CUBE_MIN	SUCCESSFUL_HLR_COUNT	created in 3.6.0	NUMBER	22	Y	Successful hlr attempts count
SMS_CUBE_MIN	SUM_DST_CHARGE_WITH_TAX	created in 3.6.0	NUMBER	22	Y	Sum of vendor charges with taxes
SMS_CUBE_MIN	SUM_DST_CHARGE_WITH_TAX2	created in 3.6.0	NUMBER	22	Y	Sum of vendor charges with taxes
SMS_CUBE_MIN	SUM_DST_CHARGE_WITH_TAX3	created in 3.6.0	NUMBER	22	Y	Sum of vendor charges with taxes
SMS_CUBE_MIN	SUM_DST_TAX	created in 3.6.0	NUMBER	22	Y	Sum of vendor taxes



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
SMS_CUBE_MIN	SUM_DST_TAX2	created in 3.6.0	NUMBER	22	Y	Sum of vendor taxes
SMS_CUBE_MIN	SUM_DST_TAX3	created in 3.6.0	NUMBER	22	Y	Sum of vendor taxes
SMS_CUBE_MIN	SUM_MARGIN_FULL	created in 3.6.0	NUMBER	22	Y	Sum of margin
SMS_CUBE_MIN	SUM_MARGIN_FULL2	created in 3.6.0	NUMBER	22	Y	Sum of margin
SMS_CUBE_MIN	SUM_MARGIN_FULL3	created in 3.6.0	NUMBER	22	Y	Sum of margin
SMS_CUBE_MIN	SUM_SRC_CHARGE_W ITH_TAX	created in 3.6.0	NUMBER	22	Y	Sum of client charges with taxes
SMS_CUBE_MIN	SUM_SRC_CHARGE_W ITH_TAX2	created in 3.6.0	NUMBER	22	Y	Sum of client charges with taxes
SMS_CUBE_MIN	SUM_SRC_CHARGE_W ITH_TAX3	created in 3.6.0	NUMBER	22	Y	Sum of client charges with taxes
SMS_CUBE_MIN	SUM_SRC_TAX	created in 3.6.0	NUMBER	22	Y	Sum of client taxes
SMS_CUBE_MIN	SUM_SRC_TAX2	created in 3.6.0	NUMBER	22	Y	Sum of client taxes



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
SMS_CUBE_MIN	SUM_SRC_TAX3	created in 3.6.0	NUMBER	22	Y	Sum of client taxes
SMS_CUBE_MIN	TRAFFIC_SUBTYPE	created in 3.6.0	NUMBER	22	Y	Traffic subtype
SMS_CUBE_MIN	VENDOR_SENDER_ID	created in 3.6.0	VARCHAR2	32	Y	Vendor sender id
SMS_CUBE_MONTH	CDR_STATUS	created in 3.6.0	VARCHAR2	30	Y	CDR status
SMS_CUBE_MONTH	CLIENT_SENDER_ID	created in 3.6.0	VARCHAR2	32	Y	Client sender ID
SMS_CUBE_MONTH	COUNT_TOTAL_SRC	created in 3.6.0	NUMBER	22	Y	Count total for client
SMS_CUBE_MONTH	DST_TAX_LIST	created in 3.6.0	VARCHAR2	64	Y	Vendor tax list
SMS_CUBE_MONTH	HLR_RESPONSE_CODE	created in 3.6.0	VARCHAR2	4000	Y	HLR response code
SMS_CUBE_MONTH	MSG_TYPE	created in 3.6.0	VARCHAR2	32	Y	Method full name Message type, i.e. bas_utils.get_carrier_list
SMS_CUBE_MONTH	SRC_TAX_LIST	created in 3.6.0	VARCHAR2	64	Y	Client tax list



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
SMS_CUBE_MONTH	SUCCESSFUL_HLR_COUNT	created in 3.6.0	NUMBER	22	Y	Successful hlr attempts count
SMS_CUBE_MONTH	SUM_DST_CHARGE_WITH_TAX	created in 3.6.0	NUMBER	22	Y	Sum of vendor charges with taxes
SMS_CUBE_MONTH	SUM_DST_CHARGE_WITH_TAX2	created in 3.6.0	NUMBER	22	Y	Sum of vendor charges with taxes
SMS_CUBE_MONTH	SUM_DST_CHARGE_WITH_TAX3	created in 3.6.0	NUMBER	22	Y	Sum of vendor charges with taxes
SMS_CUBE_MONTH	SUM_DST_TAX	created in 3.6.0	NUMBER	22	Y	Sum of vendor taxes
SMS_CUBE_MONTH	SUM_DST_TAX2	created in 3.6.0	NUMBER	22	Y	Sum of vendor taxes
SMS_CUBE_MONTH	SUM_DST_TAX3	created in 3.6.0	NUMBER	22	Y	Sum of vendor taxes
SMS_CUBE_MONTH	SUM_MARGIN_FULL	created in 3.6.0	NUMBER	22	Y	Sum of margin
SMS_CUBE_MONTH	SUM_MARGIN_FULL2	created in 3.6.0	NUMBER	22	Y	Sum of margin



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
SMS_CUBE_MONTH	SUM_MARGIN_FULL3	created in 3.6.0	NUMBER	22	Y	Sum of margin
SMS_CUBE_MONTH	SUM_SRC_CHARGE_W ITH_TAX	created in 3.6.0	NUMBER	22	Y	Sum of client charges with taxes
SMS_CUBE_MONTH	SUM_SRC_CHARGE_W ITH_TAX2	created in 3.6.0	NUMBER	22	Y	Sum of client charges with taxes
SMS_CUBE_MONTH	SUM_SRC_CHARGE_W ITH_TAX3	created in 3.6.0	NUMBER	22	Y	Sum of client charges with taxes
SMS_CUBE_MONTH	SUM_SRC_TAX	created in 3.6.0	NUMBER	22	Y	Sum of client taxes
SMS_CUBE_MONTH	SUM_SRC_TAX2	created in 3.6.0	NUMBER	22	Y	Sum of client taxes
SMS_CUBE_MONTH	SUM_SRC_TAX3	created in 3.6.0	NUMBER	22	Y	Sum of client taxes
SMS_CUBE_MONTH	TRAFFIC_SUBTYPE	created in 3.6.0	NUMBER	22	Y	Traffic subtype
SMS_CUBE_MONTH	VENDOR_SENDER_ID	created in 3.6.0	VARCHAR2	32	Y	Vendor sender id



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
SMS_CUBE_TMP	-- Table --	created in 3.6.0				Temporary table for SMS stats
SMS_CUBE_WEEK	CDR_STATUS	created in 3.6.0	VARCHAR2	30	Y	CDR status
SMS_CUBE_WEEK	CLIENT_SENDER_ID	created in 3.6.0	VARCHAR2	32	Y	Client sender ID
SMS_CUBE_WEEK	COUNT_TOTAL_SRC	created in 3.6.0	NUMBER	22	Y	Count total for client
SMS_CUBE_WEEK	DST_TAX_LIST	created in 3.6.0	VARCHAR2	64	Y	Vendor tax list
SMS_CUBE_WEEK	HLR_RESPONSE_CODE	created in 3.6.0	VARCHAR2	4000	Y	HLR response code
SMS_CUBE_WEEK	MSG_TYPE	created in 3.6.0	VARCHAR2	32	Y	Method full name Message type, i.e. bas_utils.get_carrier_list
SMS_CUBE_WEEK	SRC_TAX_LIST	created in 3.6.0	VARCHAR2	64	Y	Client tax list
SMS_CUBE_WEEK	SUCCESSFUL_HLR_COUNT	created in 3.6.0	NUMBER	22	Y	Successful hlr attempts count



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
SMS_CUBE_WEEK	SUM_DST_CHARGE_W ITH_TAX	created in 3.6.0	NUMBER	22	Y	Sum of vendor charges with taxes
SMS_CUBE_WEEK	SUM_DST_CHARGE_W ITH_TAX2	created in 3.6.0	NUMBER	22	Y	Sum of vendor charges with taxes
SMS_CUBE_WEEK	SUM_DST_CHARGE_W ITH_TAX3	created in 3.6.0	NUMBER	22	Y	Sum of vendor charges with taxes
SMS_CUBE_WEEK	SUM_DST_TAX	created in 3.6.0	NUMBER	22	Y	Sum of vendor taxes
SMS_CUBE_WEEK	SUM_DST_TAX2	created in 3.6.0	NUMBER	22	Y	Sum of vendor taxes
SMS_CUBE_WEEK	SUM_DST_TAX3	created in 3.6.0	NUMBER	22	Y	Sum of vendor taxes
SMS_CUBE_WEEK	SUM_MARGIN_FULL	created in 3.6.0	NUMBER	22	Y	Sum of margin
SMS_CUBE_WEEK	SUM_MARGIN_FULL2	created in 3.6.0	NUMBER	22	Y	Sum of margin
SMS_CUBE_WEEK	SUM_MARGIN_FULL3	created in 3.6.0	NUMBER	22	Y	Sum of margin



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
SMS_CUBE_WEEK	SUM_SRC_CHARGE_W ITH_TAX	created in 3.6.0	NUMBER	22	Y	Sum of client charges with taxes
SMS_CUBE_WEEK	SUM_SRC_CHARGE_W ITH_TAX2	created in 3.6.0	NUMBER	22	Y	Sum of client charges with taxes
SMS_CUBE_WEEK	SUM_SRC_CHARGE_W ITH_TAX3	created in 3.6.0	NUMBER	22	Y	Sum of client charges with taxes
SMS_CUBE_WEEK	SUM_SRC_TAX	created in 3.6.0	NUMBER	22	Y	Sum of client taxes
SMS_CUBE_WEEK	SUM_SRC_TAX2	created in 3.6.0	NUMBER	22	Y	Sum of client taxes
SMS_CUBE_WEEK	SUM_SRC_TAX3	created in 3.6.0	NUMBER	22	Y	Sum of client taxes
SMS_CUBE_WEEK	TRAFFIC_SUBTYPE	created in 3.6.0	NUMBER	22	Y	Traffic subtype
SMS_CUBE_WEEK	VENDOR_SENDER_ID	created in 3.6.0	VARCHAR2	32	Y	Vendor sender id
SMS_DIAL_CODE_REF	CREATED	created in 3.6.0	DATE	7	Y	Create date
SMS_DIAL_CODE_REF	CREATED_BY	created in 3.6.0	VARCHAR2	256	Y	Created by



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
SMS_DIAL_CODE_REF	LAST_UPDATE	created in 3.6.0	DATE	7	Y	last update date
SMS_DIAL_CODE_REF	LAST_UPDATED	created in 3.6.0	DATE	7	Y	last update date
SMS_DIAL_CODE_REF	LAST_UPDATED_BY	created in 3.6.0	VARCHAR2	256	Y	Last updated by
SMS_DIAL_CODE_REF_IMP_TMP	-- Table --	created in 3.6.0				Temporary table for SMS reference book
SMS_DID_FIN_DETAIL	-- Table --	created in 3.6.0				DID-number financial aggregation
SMS_DID_FIN_DETAIL	ASSIGN_DATE	created in 3.6.0	DATE	7	Y	Assign date
SMS_DID_FIN_DETAIL	DCHECK	created in 3.6.0	DATE	7	Y	Date
SMS_DID_FIN_DETAIL	DID_NUMBER	created in 3.6.0	VARCHAR2	32	Y	DID number
SMS_DID_FIN_DETAIL	END_DATE	created in 3.6.0	DATE	7	Y	Date till
SMS_DID_FIN_DETAIL	MRC	created in 3.6.0	NUMBER	22	Y	MRC



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
SMS_DID_FIN_DETAIL	NRC	created in 3.6.0	NUMBER	22	Y	NRC
SMS_DID_FIN_DETAIL	PRODUCT_ID	created in 3.6.0	NUMBER	22	Y	Product ID
SMS_DID_FIN_DETAIL	SMS_COST	created in 3.6.0	NUMBER	22	Y	Cost
SMS_DID_FIN_DETAIL	SMS_COUNT	created in 3.6.0	NUMBER	22	Y	Count
SMS_DID_FIN_DETAIL	SMS_RATE	created in 3.6.0	NUMBER	22	Y	Rate
SMS_DID_FIN_DETAIL	TRAFFIC_TYPE	created in 3.6.0	NUMBER	22	Y	Traffic type
SMS_EMA_V	-- Table --	deleted in 3.6.0				SMS EMA statistics
SMS_EMA_V	EMA_ASR_ATTEMPTS	deleted in 3.6.0	NUMBER	22	Y	ASR pack count (bounded)
SMS_EMA_V	EMA_ASR_RATE	deleted in 3.6.0	NUMBER	22	Y	EMA ASR rate
SMS_EMA_V	EMA_DELIVERY_DELAY	deleted in 3.6.0	NUMBER	22	Y	EMA delivery delay
SMS_EMA_V	EMA_DELIVERY_RATE	deleted in 3.6.0	NUMBER	22	Y	EMA Delivery rate



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
SMS_EMA_V	EMA_DLR_ATTEMPTS	deleted in 3.6.0	NUMBER	22	Y	DLS pack count (bounded)
SMS_EMA_V	EMA_LAST_UPDATED	deleted in 3.6.0	DATE	7	Y	Last updated
SMS_EMA_V	EMA_MCC_MNC	deleted in 3.6.0	VARCHAR2	6	Y	MCCMNC
SMS_EMA_V	EMA_SMSC_ID	deleted in 3.6.0	NUMBER	22	Y	SMS POI ID (link to SMS_POI table)
SMS_EXP	AFTER_RATE	deleted in 3.6.0	NUMBER	22	Y	rate after date to
SMS_EXP	BEFORE_RATE	deleted in 3.6.0	NUMBER	22	Y	rate before date from
SMS_EXP	FROM_RATE	deleted in 3.6.0	NUMBER	22	Y	rate between date from and to
SMS_EXP	FROM_RD	deleted in 3.6.0	DATE	7	Y	effective date from
SMS_EXP	NOTE_TEXT	deleted in 3.6.0	VARCHAR2	1024	Y	note text
SMS_EXP	RATE_COUNTRY_NAME	deleted in 3.6.0	VARCHAR2	256	Y	country name



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
SMS_EXP	RATE_DIAL_CODE	deleted in 3.6.0	VARCHAR2	16	Y	dial code
SMS_EXP	RATE_END_DATE	deleted in 3.6.0	DATE	7	Y	rate record end date
SMS_EXP	RATE_MCC_MNC	deleted in 3.6.0	VARCHAR2	6	Y	mcc mnc
SMS_EXP	RATE_NET_NAME	deleted in 3.6.0	VARCHAR2	256	Y	network name
SMS_EXP	RATE_PARENT_PRODUCT_ID	deleted in 3.6.0	NUMBER	22	Y	rate parent product id
SMS_EXP	RATE_PRODUCT_ID	deleted in 3.6.0	NUMBER	22	Y	rate product id
SMS_EXP	RATE_SENDER_MCC_MNC	deleted in 3.6.0	VARCHAR2	6	Y	rate sender mcc mnc
SMS_EXP	RATE_START_DATE	deleted in 3.6.0	DATE	7	Y	rate record start date
SMS_EXP	TO_RD	deleted in 3.6.0	DATE	7	Y	effective date to
SMS_EXP_DATA	CDR_ACTIVATION_TIME	created in 3.6.0	DATE	7	Y	Activation time



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
SMS_EXP_DATA	CDR_CLIENT_CALLING	created in 3.6.0	VARCHAR2	32	Y	Client Sender ID
SMS_EXP_DATA	CDR_COUNTRY	changed in 3.6.0	VARCHAR2	4000	Y	Country
SMS_EXP_DATA	CDR_DLR_TECH_DETAILS	created in 3.6.0	VARCHAR2	4000	Y	DLR technical details Delivery
SMS_EXP_DATA	CLIENT_SENDER_COUNTRY	changed in 3.6.0	VARCHAR2	4000	Y	Client sender country
SMS_EXP_DATA	DELIVERY_DELAY_CLIENT	created in 3.6.0	NUMBER	22	Y	Client delivery delay
SMS_EXP_DATA	DELIVERY_DELAY_SECONDS	created in 3.6.0	NUMBER	22	Y	Delivery delay seconds
SMS_EXP_DATA	DELIVERY_DELAY_VENDOR	created in 3.6.0	NUMBER	22	Y	Vendor delivery delay
SMS_EXP_DATA	IMSI	created in 3.6.0	VARCHAR2	64	Y	IMSI
SMS_EXP_DATA	NET_REFBOOK	changed in 3.6.0	VARCHAR2	256	Y	Network for reference MCCMNC



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
SMS_EXP_DATA	PRE_ACTIVE_STATUS	created in 3.6.0	VARCHAR2	30	Y	Status before activation
SMS_EXP_DATA	RULE_ID	created in 3.6.0	NUMBER	22	Y	Routing rule ID Rule (primary key) rule_id id
SMS_EXP_DATA	VENDOR_STATUS_CODE	created in 3.6.0	NUMBER	22	Y	Vendor status code
SMS_FIN_DETAIL	CHARGE_WITH_TAX1	created in 3.6.0	NUMBER	22	Y	Charge with tax1
SMS_FIN_DETAIL	CHARGE_WITH_TAX2	created in 3.6.0	NUMBER	22	Y	Charge with tax2
SMS_FIN_DETAIL	CHARGE_WITH_TAX3	created in 3.6.0	NUMBER	22	Y	Charge with tax
SMS_FIN_DETAIL	SMS_COST	created in 3.6.0	NUMBER	22	Y	Sms cost
SMS_FIN_DETAIL	SMS_TAX_RATE	created in 3.6.0	NUMBER	22	Y	Sms tax rate
SMS_GEN_COMPILATION_DETAIL	ASR	changed in 3.6.0	NUMBER	22	Y	ASr
SMS_HLR_CUBE_STG01	SUM_CLI_CHARGE	changed in 3.6.0	NUMBER	22	Y	Client charge



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
SMS_HLR_CUBE_STG01	SUM_VND_CHARGE	changed in 3.6.0	NUMBER	22	Y	Vendor charge
SMS_HLR_CUBE_STG02	SUM_CLI_CHARGE	created in 3.6.0	NUMBER	22	Y	revenue
SMS_HLR_CUBE_STG02	SUM_VND_CHARGE	created in 3.6.0	NUMBER	22	Y	cost
SMS_HLR_CUBE_STG03	SUM_CLI_CHARGE	created in 3.6.0	NUMBER	22	Y	revenue
SMS_HLR_CUBE_STG03	SUM_VND_CHARGE	created in 3.6.0	NUMBER	22	Y	cost
SMS_HLR_CUBE_STG04	SUM_CLI_CHARGE	created in 3.6.0	NUMBER	22	Y	revenue
SMS_HLR_CUBE_STG04	SUM_VND_CHARGE	created in 3.6.0	NUMBER	22	Y	cost
SMS_HLR_CUBE_STG05	SUM_CLI_CHARGE	created in 3.6.0	NUMBER	22	Y	revenue
SMS_HLR_CUBE_STG05	SUM_VND_CHARGE	created in 3.6.0	NUMBER	22	Y	cost
SMS_HLR_CUBE_TMP	-- Table --	created in 3.6.0				Temporary table for SMS HLR stats
SMS_HLR_EDR	-- Table --	changed in 3.6.0				HLR EDR's



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
SMS_HLR_EDR_ERROR_LOG	-- Table --	deleted in 3.6.0				DML Error Logging table for "SMS_HLR_EDR"
SMS_HLR_EDR_EXP_TMP	-- Table --	created in 3.6.0				Temporary table for SMS HLR EDR processing
SMS_IGNORABLE_RATES	-- Table --	created in 3.6.0				Additional SMS rates
SMS_IGNORABLE_RATES	END_DATE	created in 3.6.0	DATE	7	N	Effective till
SMS_IGNORABLE_RATES	MCC_MNC	created in 3.6.0	VARCHAR2	6	N	MCCMNC
SMS_IGNORABLE_RATES	PRODUCT_ID	created in 3.6.0	NUMBER	22	N	Product ID
SMS_IGNORABLE_RATES	START_DATE	created in 3.6.0	DATE	7	N	Effective from
SMS_IGNORABLE_RATES	TASK_JOB_NAME	created in 3.6.0	VARCHAR2	100	Y	Task job name (prv_task)
SMS_IMP	-- Table --	created in 3.6.0				Temporary table for SMS rate import
SMS_IMP	CHANGE_TYPE	created in 3.6.0	VARCHAR2	100	Y	Change type



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
SMS_IMP	COUNTRY_DIAL_CODE	created in 3.6.0	VARCHAR2	16	Y	Country prefix dial code
SMS_IMP	COUNTRY_NAME	created in 3.6.0	VARCHAR2	256	Y	Country name
SMS_IMP	E212	created in 3.6.0	VARCHAR2	6	N	MCCMNC
SMS_IMP	END_DATE	created in 3.6.0	DATE	7	Y	Effective till
SMS_IMP	LINE	created in 3.6.0	VARCHAR2	2000	N	Import line
SMS_IMP	NET_NAME	created in 3.6.0	VARCHAR2	256	Y	Network name
SMS_IMP	ORIGINAL_START_DATE	created in 3.6.0	DATE	7	Y	Original start date
SMS_IMP	PRODUCT_ID	created in 3.6.0	NUMBER	22	Y	Product IDs
SMS_IMP	RATE	created in 3.6.0	NUMBER	22	Y	Rate
SMS_IMP	RATE_NOTE	created in 3.6.0	VARCHAR2	2000	Y	Note
SMS_IMP	SENDER_E212	created in 3.6.0	VARCHAR2	6	Y	Sender e212



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
SMS_IMP	START_DATE	created in 3.6.0	DATE	7	Y	Effective from
SMS_IMP_CHECK	-- Table --	created in 3.6.0				Temporary table for SMS rate import
SMS_IMP_CHECK	ERROR_CODE	created in 3.6.0	VARCHAR2	4000	Y	Error code
SMS_IMP_CHECK	ERROR_ID	created in 3.6.0	NUMBER	22	N	Error ID code
SMS_IMP_CHECK	ERROR_INFO	created in 3.6.0	VARCHAR2	4000	Y	Error text
SMS_IMP_CHECK	LINE	created in 3.6.0	NUMBER	22	N	Import line
SMS_IMP_CHECK	PAYLOAD	created in 3.6.0	VARCHAR2	4000	Y	Payload - set of values which substitute the relevant placeholders in the error messages appearing during rate-import process.
SMS_IMP_ERROR	ERROR_CODE	created in 3.6.0	VARCHAR2	256	Y	Error code



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
SMS_IMP_SRC	-- Table --	created in 3.6.0				Temporary table for SMS rate import
SMS_IMP_SRC	COUNTRY_DIAL_CODE	created in 3.6.0	VARCHAR2	4000	Y	Country prefix dial code
SMS_IMP_SRC	COUNTRY_NAME	created in 3.6.0	VARCHAR2	4000	Y	Country name
SMS_IMP_SRC	E212	created in 3.6.0	VARCHAR2	4000	Y	MCCMNC
SMS_IMP_SRC	END_DATE	created in 3.6.0	VARCHAR2	4000	Y	Effective till
SMS_IMP_SRC	LINE	created in 3.6.0	NUMBER	22	N	Import line
SMS_IMP_SRC	MCC	created in 3.6.0	VARCHAR2	4000	Y	Mcc
SMS_IMP_SRC	MNC	created in 3.6.0	VARCHAR2	4000	Y	Mnc
SMS_IMP_SRC	NET_NAME	created in 3.6.0	VARCHAR2	4000	Y	Network name
SMS_IMP_SRC	RATE	created in 3.6.0	VARCHAR2	4000	Y	Rate
SMS_IMP_SRC	SENDER_E212	created in 3.6.0	VARCHAR2	4000	Y	Sender e212



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
SMS_IMP_SRC	START_DATE	created in 3.6.0	VARCHAR2	4000	Y	Effective from
SMS_LOOP_DETECTION	-- Table --	created in 3.6.0				SMS loop detection rules
SMS_LOOP_DETECTION	BLOCK_TYPE	created in 3.6.0	NUMBER	22	N	Block type: 0 = Accumulative, 1 = Periodic.
SMS_LOOP_DETECTION	CALCULATE_BY	created in 3.6.0	NUMBER	22	Y	Calculate loops by messages (1) or by segments (2)
SMS_LOOP_DETECTION	CHANNEL_LIST	created in 3.6.0	VARCHAR2	4000	Y	Channel list
SMS_LOOP_DETECTION	CHANNEL_SCOPE	created in 3.6.0	NUMBER	22	Y	Channel list scope (0 - all, 1 - inclusive)
SMS_LOOP_DETECTION	CREATED	created in 3.6.0	DATE	7	Y	Record creation date
SMS_LOOP_DETECTION	CREATED_BY	created in 3.6.0	VARCHAR2	256	Y	Name of user who created record
SMS_LOOP_DETECTION	DETECTION_TYPE	created in 3.6.0	NUMBER	22	N	bit mask: 1(+1) - Sender ID, 2(+2) -DNIS, 3(+4) - text



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
SMS_LOOP_DETECTION	IS_ACTIVE	created in 3.6.0	NUMBER	22	N	Is active: 0,1
SMS_LOOP_DETECTION	LAST_UPDATED	created in 3.6.0	DATE	7	Y	Record last updating date
SMS_LOOP_DETECTION	LAST_UPDATED_BY	created in 3.6.0	VARCHAR2	256	Y	Name of user who last updated record
SMS_LOOP_DETECTION	NUMBER_OF_SMS	created in 3.6.0	NUMBER	22	Y	Number of sms
SMS_LOOP_DETECTION	PERIOD	created in 3.6.0	NUMBER	22	Y	Period in seconds
SMS_LOOP_DETECTION	POSITIVE_RESPONSE	created in 3.6.0	NUMBER	22	N	Positive response,
SMS_LOOP_DETECTION	PREFIX_LIST	created in 3.6.0	VARCHAR2	4000	Y	Prefix list
SMS_LOOP_DETECTION	PRIORITY	created in 3.6.0	NUMBER	22	N	Priority value 1-100, 100=max priority
SMS_LOOP_DETECTION	RULE_DESCRIPTION	created in 3.6.0	VARCHAR2	256	Y	Description
SMS_LOOP_DETECTION	RULE_ID	created in 3.6.0	NUMBER	22	N	Rule id



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
SMS_LOOP_DETECTION	SENDER_ID_LIST	created in 3.6.0	VARCHAR2	4000	Y	Sender_id list
SMS_MCC_MNC_ROUTE	-- Table --	created in 3.6.0				SMS MCCMNC routes
SMS_MCC_MNC_ROUTE	MCC_MNC	created in 3.6.0	VARCHAR2	10	Y	MCCMNC
SMS_MCC_MNC_ROUTE	MCC_MNC_DESCR	created in 3.6.0	VARCHAR2	1000	Y	Mcc mnc description
SMS_MCC_MNC_ROUTE	MCC_MNC_ID	created in 3.6.0	NUMBER	22	N	Mcc\mnc id
SMS_MCC_MNC_ROUTE	MCC_MNC_ROUTE_CN T	created in 3.6.0	NUMBER	22	Y	Route count
SMS_MSG_TEMPLATE	-- Table --	created in 3.6.0				SMS message templates
SMS_MSG_TEMPLATE	TEMPLATE_ID	created in 3.6.0	NUMBER	22	N	Template ID
SMS_MSG_TEMPLATE	TEMPLATE_NAME	created in 3.6.0	VARCHAR2	256	Y	Template name user
SMS_MSG_TEMPLATE	TEMPLATE_PATTERN	created in 3.6.0	VARCHAR2	4000	Y	Template pattern



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
SMS_MSG_TEMPLATE	TEMPLATE_PRODUCT_ID	created in 3.6.0	NUMBER	22	Y	Template product id
SMS_NET_REF	CREATED	created in 3.6.0	DATE	7	Y	Create date
SMS_NET_REF	CREATED_BY	created in 3.6.0	VARCHAR2	256	Y	Created by
SMS_NET_REF	LAST_UPDATE	created in 3.6.0	DATE	7	Y	last update date
SMS_NET_REF	LAST_UPDATED	created in 3.6.0	DATE	7	Y	last update date
SMS_NET_REF	LAST_UPDATED_BY	created in 3.6.0	VARCHAR2	256	Y	Last updated by
SMS_NET_REF_ERROR_LOG	-- Table --	deleted in 3.6.0				Error log for SMS_NET_REF
SMS_NET_REF_ERROR_LOG	COUNTRY_DIAL_CODE	deleted in 3.6.0	VARCHAR2	4000	Y	Country prefix
SMS_NET_REF_ERROR_LOG	COUNTRY_NAME	deleted in 3.6.0	VARCHAR2	4000	Y	Country name



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
SMS_NET_REF_ERROR_LOG	DSC	deleted in 3.6.0	VARCHAR2	2000	Y	Description
SMS_NET_REF_ERROR_LOG	END_DATE	deleted in 3.6.0	VARCHAR2	4000	Y	End date
SMS_NET_REF_ERROR_LOG	LOT	deleted in 3.6.0	VARCHAR2	4000	Y	LOT
SMS_NET_REF_ERROR_LOG	MCC_MNC	deleted in 3.6.0	VARCHAR2	4000	Y	MCCMNC
SMS_NET_REF_ERROR_LOG	NET_NAME	deleted in 3.6.0	VARCHAR2	4000	Y	Network name
SMS_NET_REF_ERROR_LOG	NET_REF_ID	deleted in 3.6.0	VARCHAR2	4000	Y	Reference ID
SMS_NET_REF_ERROR_LOG	ORA_ERR_MESG\$	deleted in 3.6.0	VARCHAR2	2000	Y	ORA error message
SMS_NET_REF_ERROR_LOG	ORA_ERR_NUMBER\$	deleted in 3.6.0	NUMBER	22	Y	ORA error number



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
SMS_NET_REF_ERROR_LOG	ORA_ERR_OPTYP\$	deleted in 3.6.0	VARCHAR2	2	Y	ORA error type
SMS_NET_REF_ERROR_LOG	ORA_ERR_ROWID\$	deleted in 3.6.0	UROWID	4000	Y	ORA error rowid
SMS_NET_REF_ERROR_LOG	ORA_ERR_TAG\$	deleted in 3.6.0	VARCHAR2	2000	Y	ORA error tag
SMS_NET_REF_ERROR_LOG	START_DATE	deleted in 3.6.0	VARCHAR2	4000	Y	Start date
SMS_NET_REF_IMP_TMP	-- Table --	created in 3.6.0				Temporary table for SMS reference book
SMS_NET_REF_LOAD	-- Table --	created in 3.6.0				Table for loading SMS reference book
SMS_NET_REF_LOAD	COUNTRY_DIAL_CODE	created in 3.6.0	VARCHAR2	16	Y	Country prefix dial code
SMS_NET_REF_LOAD	COUNTRY_NAME	created in 3.6.0	VARCHAR2	256	N	Country name
SMS_NET_REF_LOAD	DSC	created in 3.6.0	VARCHAR2	2000	Y	Description description



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
SMS_NET_REF_LOAD	END_DATE	created in 3.6.0	DATE	7	N	Effective till
SMS_NET_REF_LOAD	LOT	created in 3.6.0	NUMBER	22	N	LOT Level of trust (from 0 to 100) trust: from 100
SMS_NET_REF_LOAD	MCC_MNC	created in 3.6.0	VARCHAR2	6	N	MCCMNC
SMS_NET_REF_LOAD	NET_NAME	created in 3.6.0	VARCHAR2	256	N	Network name
SMS_NET_REF_LOAD	NET_REF_ID	created in 3.6.0	NUMBER	22	N	Reference ID Record (primary key)
SMS_NET_REF_LOAD	START_DATE	created in 3.6.0	DATE	7	N	Effective from
SMS_PACK	IM_CHANNEL	created in 3.6.0	NUMBER	22	Y	IM channel
SMS_PACK	PACK_PURPOSE	created in 3.6.0	VARCHAR2	11	Y	Pack purpose
SMS_PACK_SUBSCR	IM_CHANNEL	created in 3.6.0	VARCHAR2	4000	Y	IM channel
SMS_PACK_SUBSCR	PACK_PURPOSE	created in 3.6.0	VARCHAR2	4000	Y	Pack purpose



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
SMS_PART_CHANGE	DID_COUNT	created in 3.6.0	NUMBER	22	Y	Number of new DIDs
SMS_PART_STATE	SUM_COUNT_OK	created in 3.6.0	NUMBER	22	Y	Sum for get_sms_mm_cnt
SMS_POI	POI_MESSAGE_TYPE	created in 3.6.0	VARCHAR2	16	Y	Poi message type
SMS_POI	POI_PRIORITY	created in 3.6.0	NUMBER	22	Y	Poi priority
SMS_POI	POI_TRAFFIC_TYPE	created in 3.6.0	VARCHAR2	16	Y	Poi traffic type
SMS_POI_PROD_CACHE_TMP	-- Table --	created in 3.6.0				Temporary table for searching product
SMS_PRODUCT_TMP	-- Table --	created in 3.6.0				Temporary table for SMS CDR processing
SMS_RATES_GRP_TMP	-- Table --	created in 3.6.0				Temporary table for filter groups in SMS rate editor
SMS_RATES_SEL_TMP	-- Table --	created in 3.6.0				Temporary table for filtered rates in SMS rate editor



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
SMS_RATE_IMPORT_TMP	RATE1	deleted in 3.6.0	NUMBER	22	N	Price
SMS_RATE_IMPORT_TMP	RATE_COUNTRY_NAME	deleted in 3.6.0	VARCHAR2	256	Y	Country name
SMS_RATE_IMPORT_TMP	RATE_DIAL_CODE	deleted in 3.6.0	VARCHAR2	16	Y	Dial code/Sender ID
SMS_RATE_IMPORT_TMP	RATE_END_DATE	deleted in 3.6.0	DATE	7	N	End date
SMS_RATE_IMPORT_TMP	RATE_ID	deleted in 3.6.0	NUMBER	22	N	Rate ID
SMS_RATE_IMPORT_TMP	RATE_MCC_MNC	deleted in 3.6.0	VARCHAR2	6	N	MCCMNC
SMS_RATE_IMPORT_TMP	RATE_NET_NAME	deleted in 3.6.0	VARCHAR2	256	Y	Net name
SMS_RATE_IMPORT_TMP	RATE_NOTE_ID	deleted in 3.6.0	NUMBER	22	Y	Note id
SMS_RATE_IMPORT_TMP	RATE_PRODUCT_ID	deleted in 3.6.0	NUMBER	22	N	Product ID
SMS_RATE_IMPORT_TMP	RATE_SENDER_MCC_MNC	deleted in 3.6.0	VARCHAR2	6	N	Sender mccmnc



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
SMS_RATE_IMPORT_TMP	RATE_START_DATE	deleted in 3.6.0	DATE	7	N	Start date
SMS_RATE_IMPORT_TMP	RATE_TYPE	deleted in 3.6.0	VARCHAR2	100	Y	Type(new\old)
SMS_RATE_IMPORT_TMP_NEW	-- Table --	created in 3.6.0				Temporary table for SMS rate import
SMS_RATE_IMPORT_TMP_OLD	-- Table --	created in 3.6.0				Temporary table for SMS rate import
SMS_RATE_STATUSES	SENDER_E212	created in 3.6.0	VARCHAR2	6	Y	Sender e212
SMS_RERATE_DATA	-- Table --	created in 3.6.0				SMS rerating internal table
SMS_RERATE_DATA	END_DATE	created in 3.6.0	DATE	7	Y	Effective till
SMS_RERATE_DATA	MCCMNC	created in 3.6.0	VARCHAR2	12	Y	MCCMNC Destination Client message ID
SMS_RERATE_DATA	PRODUCT_CATEGORY	created in 3.6.0	NUMBER	22	Y	Product category
SMS_RERATE_DATA	PRODUCT_ID	created in 3.6.0	NUMBER	22	Y	Product ID



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
SMS_RERATE_DATA	START_DATE	created in 3.6.0	DATE	7	Y	Effective from
SMS_RERATE_DATA	TASK_NAME	created in 3.6.0	VARCHAR2	128	Y	Task name
SMS_RERATE_DATA_TMP	-- Table --	created in 3.6.0				SMS rerating temporary table
SMS_REVERSE_CHARGE	-- Table --	created in 3.6.0				SMS reverse charge
SMS_REVERSE_CHARGE	ALLOW_NEGATIVE	created in 3.6.0	NUMBER	22	Y	Allow negative margin (0\1)
SMS_REVERSE_CHARGE	MCC_MNC	created in 3.6.0	VARCHAR2	6	Y	mcc_mnc
SMS_REVERSE_CHARGE	PRODUCT_ID	created in 3.6.0	NUMBER	22	N	Product ID (primary key)
SMS_RTL_AUTH_TOKEN	-- Table --	created in 3.6.0				RESTMAN tokens
SMS_RTL_AUTH_TOKEN	ACC_ID	created in 3.6.0	NUMBER	22	Y	Account ID account id,
SMS_RTL_AUTH_TOKEN	EXP_DATE	created in 3.6.0	TIMESTAMP(6)	11	N	Expire date



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
SMS_RTL_AUTH_TOKEN	IP	created in 3.6.0	VARCHAR2	4000	Y	Ip
SMS_RTL_AUTH_TOKEN	TOKEN	created in 3.6.0	VARCHAR2	4000	N	Token
SMS_RTL_AUTH_TOKEN	TOKEN_ID	created in 3.6.0	NUMBER	22	N	Token id
SMS_RTL_AUTH_TOKEN	USER_ID	created in 3.6.0	NUMBER	22	N	User numeric ID (primary key) Manager User-creator
SMS_RTL_AUTH_TOKEN	UUID	created in 3.6.0	VARCHAR2	36	Y	Token UUID
SMS_RTL_AUTH_TOKEN_BLACKLIST	-- Table --	created in 3.6.0				RESTMAN tokens blacklist
SMS_RTL_AUTH_TOKEN_BLACKLIST	ACC_ID	created in 3.6.0	NUMBER	22	Y	Account ID
SMS_RTL_AUTH_TOKEN_BLACKLIST	EXP_DATE	created in 3.6.0	TIMESTAMP(6)	11	N	Expire date
SMS_RTL_AUTH_TOKEN_BLACKLIST	IP	created in 3.6.0	VARCHAR2	4000	Y	Ip



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
SMS_RTL_AUTH_TOKEN_BLACKLIST	TOKEN	created in 3.6.0	VARCHAR2	4000	N	Token
SMS_RTL_AUTH_TOKEN_BLACKLIST	TOKEN_ID	created in 3.6.0	NUMBER	22	Y	Token id
SMS_RTL_AUTH_TOKEN_BLACKLIST	USER_ID	created in 3.6.0	NUMBER	22	N	User numeric ID
SMS_RTL_BLACK_LIST	TAG_ID	created in 3.6.0	NUMBER	22	Y	Tag ID
SMS_RTL_EDR	EXTRA	created in 3.6.0	VARCHAR2	4000	Y	Extra field
SMS_RTL_EDR	IM_CHANNEL	created in 3.6.0	VARCHAR2	1000	Y	IM channel
SMS_RTL_EDR	IS_MULTI_CHANNEL	created in 3.6.0	NUMBER	22	Y	Is multi channel
SMS_RTL_EDR	MESSAGE_LABEL	created in 3.6.0	VARCHAR2	256	Y	Message label
SMS_RTL_EDR	SOURCE_MESSAGE_DATE	created in 3.6.0	DATE	7	Y	Source message date



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
SMS_RTL_EDR	SOURCE_MESSAGE_ID	created in 3.6.0	VARCHAR2	65	Y	Source message id
SMS_RTL_EDR	TRANSACTION_ID	created in 3.6.0	VARCHAR2	65	Y	Transaction ID
SMS_RTL_EDR	VENDOR_ANI	created in 3.6.0	VARCHAR2	32	Y	Vendor sender ID
SMS_RTL_EDR	VENDOR_DNIS	created in 3.6.0	VARCHAR2	32	Y	Vendor destination address dest.
SMS_RTL_EDR_STATUS	IM_CHANNEL	created in 3.6.0	VARCHAR2	4000	Y	IM channel
SMS_RTL_EDR_STATUS	TECH_DETAILS	created in 3.6.0	VARCHAR2	4000	Y	Tech details
SMS_RTL_EDR_UNLOCK_BUFF	-- Table --	created in 3.6.0				Unblocking EDRs
SMS_RTL_EDR_UNLOCK_BUFF	EDR_IS_SUCCESSFUL	created in 3.6.0	NUMBER	22	Y	Flag: 1 - successful HLR request, 0 not Is flag
SMS_RTL_EDR_UNLOCK_BUFF	IM_CHANNEL	created in 3.6.0	VARCHAR2	1000	Y	IM channel



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
SMS_RTL_EDR_UNLOCK_BUFF	MESSAGE_ID	created in 3.6.0	VARCHAR2	65	Y	Client message ID SMS Message text
SMS_RTL_EDR_UNLOCK_BUFF	SUBSCR_ID	created in 3.6.0	NUMBER	22	Y	Fee ID Subscription
SMS_RULE	RULE_COLOR	created in 3.6.0	VARCHAR2	100	Y	Rule color
SMS_RULE	RULE_CONTENT_GROUP_LIST	created in 3.6.0	VARCHAR2	4000	Y	tag id list
SMS_RULE	RULE_CONTENT_GROUP_LIST_SCOPE	created in 3.6.0	NUMBER	22	N	0 - All, 1 - Inclusive list, -1 - Exclusive list
SMS_RULE	RULE_DEST_NUM_GROUP_LIST	created in 3.6.0	VARCHAR2	4000	Y	tag id list
SMS_RULE	RULE_DEST_NUM_GROUP_LIST_SCOPE	created in 3.6.0	NUMBER	22	N	0 - All, 1 - Inclusive list, -1 - Exclusive list
SMS_RULE	RULE_SENDERID_GROUP_LIST	created in 3.6.0	VARCHAR2	4000	Y	tag id list



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
SMS_RULE	RULE_SENDERID_GROUP_LIST_SCOPE	created in 3.6.0	NUMBER	22	N	0 - All, 1 - Inclusive list, -1 - Exclusive list
SMS_RUT_LIM_DESTINATION	-- Table --	created in 3.6.0				SMS limitation rule destinations
SMS_RUT_LIM_DESTINATION	LAST_THRESHOLD	created in 3.6.0	NUMBER	22	Y	Last threshold
SMS_RUT_LIM_DESTINATION	LAST_THRESHOLD_CHANGE	created in 3.6.0	DATE	7	Y	Last threshold date
SMS_RUT_LIM_DESTINATION	MCC_MNC_MASK	created in 3.6.0	VARCHAR2	22	N	Mcc mnc mask
SMS_RUT_LIM_DESTINATION	MCC_MNC_MASKS	created in 3.6.0	VARCHAR2	4000	Y	Mcc mnc masks
SMS_RUT_LIM_DESTINATION	PRODUCT_ID	created in 3.6.0	NUMBER	22	N	Product ID
SMS_RUT_LIM_DESTINATION	PRODUCT_IDS	created in 3.6.0	VARCHAR2	4000	Y	Product IDs



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
SMS_RUT_LIM_DESTINATION	RULE_ID	created in 3.6.0	NUMBER	22	N	Routing rule ID Rule (primary key) rule_id id
SMS_RUT_LIM_LOCK	-- Table --	created in 3.6.0				SMS limitation rule lock
SMS_RUT_LIM_LOCK	EFFECTIVE_TILL	created in 3.6.0	DATE	7	Y	Effective till
SMS_RUT_LIM_LOCK	MCC_MNC_MASK	created in 3.6.0	VARCHAR2	772	Y	Mcc mnc mask
SMS_RUT_LIM_LOCK	PRODUCT_ID	created in 3.6.0	NUMBER	22	N	Product ID
SMS_RUT_LIM_LOCK	RULE_ID	created in 3.6.0	NUMBER	22	N	Routing rule ID Rule (primary key) rule_id id
SMS_RUT_LIM_METRIC	-- Table --	created in 3.6.0				SMS limitation rule metrics
SMS_RUT_LIM_METRIC	ASC_DESC	created in 3.6.0	VARCHAR2	4	Y	Ascending/Descending metric
SMS_RUT_LIM_METRIC	CREATED	created in 3.6.0	DATE	7	Y	Record creation date



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
SMS_RUT_LIM_METRIC	CREATED_BY	created in 3.6.0	VARCHAR2	256	Y	Name of user who created record
SMS_RUT_LIM_METRIC	LAST_UPDATED	created in 3.6.0	DATE	7	Y	Record last updating date
SMS_RUT_LIM_METRIC	LAST_UPDATED_BY	created in 3.6.0	VARCHAR2	256	Y	Name of user who last updated record
SMS_RUT_LIM_METRIC	METRIC_CODE	created in 3.6.0	VARCHAR2	256	Y	Metric code for translation of limitations rules
SMS_RUT_LIM_METRIC	METRIC_ID	created in 3.6.0	NUMBER	22	N	Metric ID Link to metric
SMS_RUT_LIM_METRIC	METRIC_NAME	created in 3.6.0	VARCHAR2	256	N	Metric name
SMS_RUT_LIM_METRIC	THRESHOLD_LIST	created in 3.6.0	VARCHAR2	1000	Y	Threshold list
SMS_RUT_LIM_REFRESH_QUEUE	-- Table --	created in 3.6.0				SMS limitation rule internal table
SMS_RUT_LIM_REFRESH_QUEUE	DCHECK	created in 3.6.0	DATE	7	Y	Date Last updated day check date of charging Cube



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
SMS_RUT_LIM_REFRESH_QUEUE	FMT	created in 3.6.0	VARCHAR2	4	Y	Format (HH24/DD/DAY/MON) Table period type
SMS_RUT_LIM_RULE	-- Table --	created in 3.6.0				SMS limitation rules
SMS_RUT_LIM_RULE	ALERT_RECIPIENTS	created in 3.6.0	VARCHAR2	4000	Y	List of alert recipients email emails
SMS_RUT_LIM_RULE	BLOCK_LENGTH	created in 3.6.0	NUMBER	22	Y	Block length (period count)
SMS_RUT_LIM_RULE	CREATED	created in 3.6.0	DATE	7	Y	Record creation date
SMS_RUT_LIM_RULE	CREATED_BY	created in 3.6.0	VARCHAR2	256	Y	Name of user who created record
SMS_RUT_LIM_RULE	END_DATE	created in 3.6.0	DATE	7	N	Effective till
SMS_RUT_LIM_RULE	IS_ACTIVE	created in 3.6.0	NUMBER	22	N	Activity flag
SMS_RUT_LIM_RULE	LAST_CHECKED_DATE	created in 3.6.0	TIMESTAMP(6)	11	Y	Last check date



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
SMS_RUT_LIM_RULE	LAST_UPDATED	created in 3.6.0	DATE	7	Y	Record last updating date
SMS_RUT_LIM_RULE	LAST_UPDATED_BY	created in 3.6.0	VARCHAR2	256	Y	Name of user who last updated record
SMS_RUT_LIM_RULE	LIMIT_VALUE	created in 3.6.0	NUMBER	22	N	Value of the limit to activate lock or alert
SMS_RUT_LIM_RULE	METRIC_ID	created in 3.6.0	NUMBER	22	N	Metric ID Link to metric
SMS_RUT_LIM_RULE	PERIOD_LENGTH	created in 3.6.0	NUMBER	22	N	Length of the period, must be >= 1
SMS_RUT_LIM_RULE	PERIOD_TYPE	created in 3.6.0	VARCHAR2	4	N	Period: HH24 - hour, DD - day, DAY - week, MM - month, ONCE - single
SMS_RUT_LIM_RULE	RULE_ID	created in 3.6.0	NUMBER	22	N	Routing rule ID Rule (primary key) rule_id id
SMS_RUT_LIM_RULE	RULE_TYPE	created in 3.6.0	NUMBER	22	N	Rule type



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
SMS_RUT_LIM_RULE	SEND_ALERTS	created in 3.6.0	NUMBER	22	N	Flag: 1 - send alerts to account manager, 0 do not send
SMS_RUT_LIM_RULE	START_DATE	created in 3.6.0	DATE	7	N	Effective from
SMS_RUT_LIM_RULE	STATS_DELAY	created in 3.6.0	NUMBER	22	Y	Statistics delay
SMS_RUT_LIM_STATS	-- Table --	created in 3.6.0				SMS limitation rule statistics
SMS_RUT_LIM_STATS	COST	created in 3.6.0	NUMBER	22	Y	Vendor average cost Cost
SMS_RUT_LIM_STATS	COUNT_ACTIVATED	created in 3.6.0	NUMBER	22	Y	Count of activated messages
SMS_RUT_LIM_STATS	COUNT_DELIVRD	created in 3.6.0	NUMBER	22	Y	Total delivered SMS Count of messages Number
SMS_RUT_LIM_STATS	COUNT_DST_OK	created in 3.6.0	NUMBER	22	Y	Count of billable messages for vendor
SMS_RUT_LIM_STATS	COUNT_OK	created in 3.6.0	NUMBER	22	Y	Total successful attempts



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
SMS_RUT_LIM_STATS	COUNT_REPORTED	created in 3.6.0	NUMBER	22	Y	Count of messages with delivery status
SMS_RUT_LIM_STATS	COUNT_SENT	created in 3.6.0	NUMBER	22	Y	Count of sent messages Number
SMS_RUT_LIM_STATS	COUNT_SRC_OK	created in 3.6.0	NUMBER	22	Y	Count of billable messages for client
SMS_RUT_LIM_STATS	COUNT_TOTAL	created in 3.6.0	NUMBER	22	Y	Total count
SMS_RUT_LIM_STATS	DCHECK	created in 3.6.0	DATE	7	N	Date Last updated day check date of charging Cube
SMS_RUT_LIM_STATS	MARGIN	created in 3.6.0	NUMBER	22	Y	Margin Total margin
SMS_RUT_LIM_STATS	MCC_MNC_MASK	created in 3.6.0	VARCHAR2	772	Y	Mcc mnc mask
SMS_RUT_LIM_STATS	PRODUCT_ID	created in 3.6.0	NUMBER	22	Y	Product ID
SMS_RUT_LIM_STATS	RULE_ID	created in 3.6.0	NUMBER	22	N	Routing rule ID Rule (primary key) rule_id id



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
SMS_RUT_LIM_STATS	SUM_DELIVERY_DELAY	created in 3.6.0	NUMBER	22	Y	Total delivery delay
SMS_RUT_LIM_STATS_TMP	-- Table --	created in 3.6.0				Temporary table for SMS limitation rule statistic
SMS_SENDER	SMS_SENDER_ID	changed in 3.6.0	NUMBER	22	N	Sender ID
SMS_SS7_MSG_TYPE	-- Table --	created in 3.6.0				SS7 message type detection rules
SMS_SS7_MSG_TYPE	DESTINATION_ADDR	created in 3.6.0	VARCHAR2	64	N	Destination address
SMS_SS7_MSG_TYPE	ID	created in 3.6.0	NUMBER	22	N	ID
SMS_SS7_MSG_TYPE	ORIGINATION_ADDR	created in 3.6.0	VARCHAR2	64	N	Origination addr
SMS_TAB_PARAM	-- Table --	deleted in 3.6.0				SMS analytic cubes parameters
SMS_TAB_PARAM	ALLOW_STA_RAW_SOURCE	deleted in 3.6.0	NUMBER	22	N	Flag: 1 - allow recalculation from raw CDRs, 0 - do not allow



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
SMS_TAB_PARAM	FMT	deleted in 3.6.0	VARCHAR2	4	N	Table period type
SMS_TAB_PARAM	FUTURE_CNT	deleted in 3.6.0	NUMBER	22	N	Future periods count
SMS_TAB_PARAM	REFRESH_DELAY	deleted in 3.6.0	NUMBER	22	N	Refresh delay, fraction of day
SMS_TAB_PARAM	STORE_CNT_PARAM	deleted in 3.6.0	VARCHAR2	30	N	Window width
SMS_TAB_PARAM	TABLE_NAME	deleted in 3.6.0	VARCHAR2	30	N	Table name
SMS_TEST_DEAL_HIST	DEAL_ID	changed in 3.6.0	NUMBER	22	Y	id of test deal
SMS_TEST_TASK	TASK_UPDATE_DATE	created in 3.6.0	DATE	7	Y	Task update date
SMS_TEST_TASK_TEMPLATE	TT_SELECTED_ROWS	changed in 3.6.0	VARCHAR2	4000	Y	Selected rows
SMS_TRANSLATION_LIST	-- Table --	created in 3.6.0				SMS translate expression lists
SMS_TRANSLATION_LIST	EXPR_LIST	created in 3.6.0	CLOB	4000	N	Translation expressions list



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
SMS_TRANSLATION_LIST	ID	created in 3.6.0	NUMBER	22	N	List ID
SMS_TRANSLATION_LIST	LIST_NAME	created in 3.6.0	VARCHAR2	256	N	List name
SMS_TRANSLATION_RULE	CREATED	created in 3.6.0	DATE	7	Y	Record creation date
SMS_TRANSLATION_RULE	CREATED_BY	created in 3.6.0	VARCHAR2	256	Y	Name of user who created record
SMS_TRANSLATION_RULE	LAST_UPDATED	created in 3.6.0	DATE	7	Y	Record last updating date
SMS_TRANSLATION_RULE	LAST_UPDATED_BY	created in 3.6.0	VARCHAR2	256	Y	Name of user who last updated record
SMS_TRANSLATION_RULE	RULE_CONTENT_GROUP_LIST	created in 3.6.0	VARCHAR2	4000	Y	tag id list
SMS_TRANSLATION_RULE	RULE_CONTENT_GROUP_LIST_SCOPE	created in 3.6.0	NUMBER	22	Y	0 - All, 1 - Inclusive list, -1 - Exclusive list
SMS_TRANSLATION_RULE	RULE_DEST_NUM_GROUPS_LIST	created in 3.6.0	VARCHAR2	4000	Y	tag id list



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
SMS_TRANSLATION_RULE	RULE_DEST_NUM_GRP OUP_LIST_SCOPE	created in 3.6.0	NUMBER	22	Y	0 - All, 1 - Inclusive list, -1 - Exclusive list
SMS_TRANSLATION_RULE	RULE_SENDERID_GROUP UP_LIST	created in 3.6.0	VARCHAR2	4000	Y	tag id list
SMS_TRANSLATION_RULE	RULE_SENDERID_GROUP UP_LIST_SCOPE	created in 3.6.0	NUMBER	22	Y	0 - All, 1 - Inclusive list, -1 - Exclusive list
SMS_TRANSLATION_RULE	TR_TLV_TAG	created in 3.6.0	VARCHAR2	6	Y	TLV tag
SMS_TRANSLATION_RULE	TR_TLV_TYPE	created in 3.6.0	NUMBER	22	Y	TLV tag type
SMS_TRANSLATION_RULE	TR_TRANS_LIST_ID	created in 3.6.0	NUMBER	22	Y	ID expression list (link to sms_translation_list.id)
SMS_TRANSLATION_RULE	TR_TRANS_LIST_MODE	created in 3.6.0	NUMBER	22	Y	Text translation mode (0 - list cycle, 1 - random)
SMS_TRANSLATION_RULE	TR_TRANS_TYPE	created in 3.6.0	NUMBER	22	Y	Text translation type (0 - regex, 1 - expression list)
SMS_TRNSL_CODE	CODE	changed in 3.6.0	VARCHAR2	4000	N	code



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
SMS_TRNSL_CODE	DESCR	changed in 3.6.0	VARCHAR2	4000	N	description
SMS_TRNSL_ERRCODE	-- Table --	deleted in 3.6.0				Error code translations
SMS_TRNSL_ERRCODE	CHANNEL_IDS	deleted in 3.6.0	VARCHAR2	4000	N	List of channels
SMS_TRNSL_ERRCODE	ID	deleted in 3.6.0	NUMBER	22	N	Unique ID
SMS_TRNSL_ERRCODE	MCC_MNC_LIST	deleted in 3.6.0	VARCHAR2	4000	Y	List of MCCMNCs translation rule applied to
SMS_TRNSL_ERRCODE	RES_CODE_MANUAL	deleted in 3.6.0	VARCHAR2	1000	Y	Manually entered resulting code
SMS_TRNSL_ERRCODE	RES_DLV_STATUS	deleted in 3.6.0	NUMBER	22	Y	Resulting delivery status
SMS_TRNSL_ERRCODE	RES_SMB_RESP_STAT US	deleted in 3.6.0	NUMBER	22	Y	Resulting submit_sm_resp code
SMS_TRNSL_ERRCODE	RES_SYS_DLV_ERR_CO DE	deleted in 3.6.0	NUMBER	22	Y	Resulting system delivery error code



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
SMS_TRNSL_ERRCODE	SRC_CODE_MANUAL	deleted in 3.6.0	VARCHAR2	1000	Y	Manually entered source code
SMS_TRNSL_ERRCODE	SRC_DLV_STATUS	deleted in 3.6.0	NUMBER	22	Y	Source delivery status
SMS_TRNSL_ERRCODE	SRC_SYS_DLV_ERR_CODE	deleted in 3.6.0	NUMBER	22	Y	Source system delivery error code
SMS_TRNSL_ERRCODE	SRC_SYS_SRC_CODE	deleted in 3.6.0	NUMBER	22	Y	Source system submit_sm_resp code
SMS_TRNSL_ERRCODE	TRNSL_TYPE_CODE	deleted in 3.6.0	NUMBER	22	N	Translation type
SMS_TRNSL_RULE_CODE_REF	-- Table --	created in 3.6.0				Code translation reference book
SMS_TRNSL_RULE_CODE_REF	CODE_TYPE	created in 3.6.0	NUMBER	22	Y	code type: routing/system/error/status/protocol
SMS_TRNSL_RULE_CODE_REF	RULE_CODE_TYPE	created in 3.6.0	VARCHAR2	12	Y	Rule code type



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
SMS_TRNSL_RULE_CODE_REF	RULE_PROTOCOL	created in 3.6.0	VARCHAR2	4	Y	Rule protocol
SMS_TRNSL_RULE_CODE_REF	RULE_TYPE	created in 3.6.0	NUMBER	22	Y	Rule type
SMS_TRNSL_SBM_RESP_S TATUS	-- Table --	deleted in 3.6.0				List of submit_sm_resp status codes
SMS_TRNSL_SBM_RESP_S TATUS	CLASS_RESPONSE	deleted in 3.6.0	VARCHAR2	256	Y	Response class name
SMS_TRNSL_SBM_RESP_S TATUS	DESCR	deleted in 3.6.0	VARCHAR2	1024	Y	Description
SMS_TRNSL_SBM_RESP_S TATUS	ERROR_CODE	deleted in 3.6.0	VARCHAR2	1024	Y	Error code
SMS_TRNSL_SBM_RESP_S TATUS	ID	deleted in 3.6.0	NUMBER	22	N	Unique ID
SMS_TRNSL_SBM_RESP_S TATUS	STATUS_CODE	deleted in 3.6.0	VARCHAR2	16	N	Status code



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
SMS_TRNSL_SBM_RESP_STATUS	TYPE	deleted in 3.6.0	VARCHAR2	5	N	Code type
SMS_TRNSL_SYS_DLV_ERR_CODE	-- Table --	deleted in 3.6.0				List of system delivery error codes
SMS_TRNSL_SYS_DLV_ERR_CODE	DESCR	deleted in 3.6.0	VARCHAR2	256	Y	Description
SMS_TRNSL_SYS_DLV_ERR_CODE	ERR_CODE	deleted in 3.6.0	VARCHAR2	16	N	Error code
SMS_TRNSL_SYS_DLV_ERR_CODE	ID	deleted in 3.6.0	NUMBER	22	N	Unique ID
SMS_TRNSL_SYS_DLV_STATUS	-- Table --	deleted in 3.6.0				List of system delivery statuses
SMS_TRNSL_SYS_DLV_STATUS	ID	deleted in 3.6.0	NUMBER	22	N	Unique ID
SMS_TRNSL_SYS_DLV_STATUS	STATUS	deleted in 3.6.0	VARCHAR2	16	N	Status name



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
SMS_TRNSL_SYS_SRC_CODE	-- Table --	deleted in 3.6.0				List of system EDR statuses
SMS_TRNSL_SYS_SRC_CODE	CODE_NUM	deleted in 3.6.0	VARCHAR2	10	N	Code number
SMS_TRNSL_SYS_SRC_CODE	CODE_TXT	deleted in 3.6.0	VARCHAR2	2000	N	Code text
SMS_TRNSL_SYS_SRC_CODE	ID	deleted in 3.6.0	NUMBER	22	N	Unique ID
SMS_TRNSL_TYPE_CODE	-- Table --	created in 3.6.0				Translation error code types
SMS_TRNSL_TYPE_CODE	DESCR	created in 3.6.0	VARCHAR2	4000	Y	Description description Installation
SMS_TRNSL_TYPE_CODE	ID	created in 3.6.0	NUMBER	22	N	ID
SMS_TRNSL_TYPE_CODE	TYPE_CODE	created in 3.6.0	NUMBER	22	N	Code type
SMS_VBD2	DEAL_PERIOD_TYPE	created in 3.6.0	NUMBER	22	Y	Deal period type



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
SMS_VBD_PERIOD	-- Table --	created in 3.6.0				SMS volume-based deal periods
SMS_VBD_PERIOD	CURRENT_THRESHOLD	created in 3.6.0	NUMBER	22	Y	Current threshold
SMS_VBD_PERIOD	CURRENT_VOLUME	created in 3.6.0	NUMBER	22	Y	Current volume
SMS_VBD_PERIOD	DEAL_ID	created in 3.6.0	NUMBER	22	Y	Deal ID
SMS_VBD_PERIOD	EXPECTED_VOLUME	created in 3.6.0	NUMBER	22	Y	Expected volume
SMS_VBD_PERIOD	LAST_ACTUALIZATION_DATE	created in 3.6.0	DATE	7	Y	Last actualization date
SMS_VBD_PERIOD	PERIOD_END	created in 3.6.0	DATE	7	Y	Deal period end date
SMS_VBD_PERIOD	PERIOD_ID	created in 3.6.0	NUMBER	22	N	Period ID
SMS_VBD_PERIOD	PERIOD_NO	created in 3.6.0	NUMBER	22	Y	Deal period number
SMS_VBD_PERIOD	PERIOD_SCRUTINY	created in 3.6.0	NUMBER	22	Y	Scrutiny period



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
SMS_VBD_PERIOD	PERIOD_START	created in 3.6.0	DATE	7	Y	Deal period start date
SMS_VBD_PERIOD	PERIOD_STATE	created in 3.6.0	VARCHAR2	1	Y	Deal period state (A - actual, I invalid, O obsolete)
SMS_VBD_PERIOD_INFO_TMP	-- Table --	created in 3.6.0				Temporary table for SMS volume-based deal
SMS_VBD_PERIOD_TYPE	-- Table --	created in 3.6.0				SMS volume-based deal period type
SMS_VBD_PERIOD_TYPE	ACCURACY	created in 3.6.0	NUMBER	22	Y	Accuracy
SMS_VBD_PERIOD_TYPE	DAYS_COUNT	created in 3.6.0	NUMBER	22	Y	Days count
SMS_VBD_PERIOD_TYPE	PERIOD_TYPE_ID	created in 3.6.0	NUMBER	22	N	Type of deal period
SMS_VBD_PERIOD_TYPE	PERIOD_TYPE_NAME	created in 3.6.0	VARCHAR2	100	Y	Period type name
SMS_VBD_PRODUCT	-- Table --	created in 3.6.0				SMS volume-based deal products



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
SMS_VBD_PRODUCT	DEAL_ID	created in 3.6.0	NUMBER	22	N	Deal ID
SMS_VBD_PRODUCT	LAST_RERATING_THRESHOLD	created in 3.6.0	NUMBER	22	Y	Last rerating threshold
SMS_VBD_PRODUCT	LAST_RERATING_TIME	created in 3.6.0	DATE	7	Y	Last rerating time
SMS_VBD_PRODUCT	PRODUCT_ID	created in 3.6.0	NUMBER	22	N	Product ID
SMS_VBD_RATE	-- Table --	created in 3.6.0				SMS volume-based deal rates
SMS_VBD_RATE	MCC_MNC	created in 3.6.0	NUMBER	22	Y	MCCMNC
SMS_VBD_RATE	PERIOD_ID	created in 3.6.0	NUMBER	22	Y	Period ID
SMS_VBD_RATE	RATE	created in 3.6.0	NUMBER	22	Y	Price Rate per minute rate Pack ID
SMS_VBD_RATE	SENDER	created in 3.6.0	VARCHAR2	50	Y	Mail from
SMS_VBD_RATE	THRESHOLD_NO	created in 3.6.0	NUMBER	22	Y	Threshold number



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
SMS_VBD_RATE	VOLUME	created in 3.6.0	NUMBER	22	Y	Volume lower threshold volume Total
SMS_VBD_RATE_TMP	-- Table --	created in 3.6.0				SMS volume-based deal temporary table
STA_CUBE_DAY	CALLED_LATA	changed in 3.6.0	NUMBER	22	Y	B-side LATA
STA_CUBE_DAY	CALLED_OCN	changed in 3.6.0	VARCHAR2	4	Y	B-side OCN
STA_CUBE_DAY	CALLED_STATE	changed in 3.6.0	VARCHAR2	2	Y	B-side State
STA_CUBE_DAY	CALLING_LATA	changed in 3.6.0	NUMBER	22	Y	A-side LATA
STA_CUBE_DAY	CALLING_OCN	changed in 3.6.0	VARCHAR2	4	Y	A-side OCN
STA_CUBE_DAY	CALLING_STATE	changed in 3.6.0	VARCHAR2	2	Y	A-side State
STA_CUBE_DAY	CALL_TYPE	created in 3.6.0	NUMBER	22	Y	Call type
STA_CUBE_DAY	COUNT_OK	changed in 3.6.0	NUMBER	22	Y	Successful calls



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
STA_CUBE_DAY	COUNT_RES	changed in 3.6.0	NUMBER	22	Y	Attempts with successful code
STA_CUBE_DAY	COUNT_SHORT	changed in 3.6.0	NUMBER	22	Y	Short calls
STA_CUBE_DAY	COUNT_TOTAL	changed in 3.6.0	NUMBER	22	Y	Attempts count
STA_CUBE_DAY	COUNT_VERY_SHORT	changed in 3.6.0	NUMBER	22	Y	Very short calls
STA_CUBE_DAY	DCHECK	changed in 3.6.0	DATE	7	Y	Date
STA_CUBE_DAY	DST_DIAL_CODE	changed in 3.6.0	VARCHAR2	256	Y	Vendor dial code from rates
STA_CUBE_DAY	DST_RATE_LIST	changed in 3.6.0	VARCHAR2	64	Y	3 sample vendor rates
STA_CUBE_DAY	GROUP_ID	changed in 3.6.0	NUMBER	22	Y	Aggregation group ID
STA_CUBE_DAY	HOST	changed in 3.6.0	VARCHAR2	256	Y	Softswitch
STA_CUBE_DAY	SRC_DIAL_CODE	changed in 3.6.0	VARCHAR2	256	Y	Client dial code from rates



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
STA_CUBE_DAY	SRC_RATE_LIST	changed in 3.6.0	VARCHAR2	64	Y	3 sample client rates
STA_CUBE_DAY	SUM_DST_CHARGE	changed in 3.6.0	NUMBER	22	Y	Vendor charge
STA_CUBE_DAY	SUM_DST_CONN_FEE	created in 3.6.0	NUMBER	22	Y	Sum of vendor connection fees
STA_CUBE_DAY	SUM_MARGIN	changed in 3.6.0	NUMBER	22	Y	Margin
STA_CUBE_DAY	SUM_SRC_CHARGE	changed in 3.6.0	NUMBER	22	Y	Client charge
STA_CUBE_GROUP	CALL_TYPE	created in 3.6.0	NUMBER	22	N	Call type
STA_CUBE_GROUP	GROUP_ID	changed in 3.6.0	NUMBER	22	Y	Group ID
STA_CUBE_GROUP	MANAGER_ID	created in 3.6.0	NUMBER	22	N	Manager ID
STA_CUBE_HOUR	CALLED_LATA	changed in 3.6.0	NUMBER	22	Y	B-side LATA
STA_CUBE_HOUR	CALLED_OCN	changed in 3.6.0	VARCHAR2	4	Y	B-side OCN
STA_CUBE_HOUR	CALLED_STATE	changed in 3.6.0	VARCHAR2	2	Y	B-side State



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
STA_CUBE_HOUR	CALLING_LATA	changed in 3.6.0	NUMBER	22	Y	A-side LATA
STA_CUBE_HOUR	CALLING_OCN	changed in 3.6.0	VARCHAR2	4	Y	A-side OCN
STA_CUBE_HOUR	CALLING_STATE	changed in 3.6.0	VARCHAR2	2	Y	A-side State
STA_CUBE_HOUR	CALL_TYPE	created in 3.6.0	NUMBER	22	Y	Call type
STA_CUBE_HOUR	COUNT_OK	changed in 3.6.0	NUMBER	22	Y	Successful calls
STA_CUBE_HOUR	COUNT_RES	changed in 3.6.0	NUMBER	22	Y	Attempts with successful code
STA_CUBE_HOUR	COUNT_SHORT	changed in 3.6.0	NUMBER	22	Y	Short calls
STA_CUBE_HOUR	COUNT_TOTAL	changed in 3.6.0	NUMBER	22	Y	Attempts count
STA_CUBE_HOUR	COUNT_VERY_SHORT	changed in 3.6.0	NUMBER	22	Y	Very short calls
STA_CUBE_HOUR	DCHECK	changed in 3.6.0	DATE	7	Y	Date



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
STA_CUBE_HOUR	DST_DIAL_CODE	changed in 3.6.0	VARCHAR2	256	Y	Vendor dial code from rates
STA_CUBE_HOUR	DST_RATE_LIST	changed in 3.6.0	VARCHAR2	64	Y	3 sample vendor rates
STA_CUBE_HOUR	GROUP_ID	changed in 3.6.0	NUMBER	22	Y	Aggregation group ID
STA_CUBE_HOUR	HOST	changed in 3.6.0	VARCHAR2	256	Y	Softswitch
STA_CUBE_HOUR	SRC_DIAL_CODE	changed in 3.6.0	VARCHAR2	256	Y	Client dial code from rates
STA_CUBE_HOUR	SRC_RATE_LIST	changed in 3.6.0	VARCHAR2	64	Y	3 sample client rates
STA_CUBE_HOUR	SUM_DST_CHARGE	changed in 3.6.0	NUMBER	22	Y	Vendor charge
STA_CUBE_HOUR	SUM_DST_CONN_FEE	created in 3.6.0	NUMBER	22	Y	Sum of vendor connection fees
STA_CUBE_HOUR	SUM_MARGIN	changed in 3.6.0	NUMBER	22	Y	Margin
STA_CUBE_HOUR	SUM_SRC_CHARGE	changed in 3.6.0	NUMBER	22	Y	Client charge



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
STA_CUBE_INDX_QUEUE	PARTITION_DATE	created in 3.6.0	DATE	7	Y	Partition date
STA_CUBE_INDX_QUEUE	TABLE_NAME	created in 3.6.0	VARCHAR2	50	Y	Table name Analytic cube table
STA_CUBE_MANAGER_D AY	-- Table --	created in 3.6.0				Manager voice analytic daily cube
STA_CUBE_MANAGER_D AY	AVG_PDD	created in 3.6.0	NUMBER	22	Y	Average PDD
STA_CUBE_MANAGER_D AY	CALLED_LATA	created in 3.6.0	NUMBER	22	Y	B-side LATA
STA_CUBE_MANAGER_D AY	CALLED_OCN	created in 3.6.0	VARCHAR2	4	Y	B-side OCN
STA_CUBE_MANAGER_D AY	CALLED_STATE	created in 3.6.0	VARCHAR2	2	Y	B-side State
STA_CUBE_MANAGER_D AY	CALLING_DIAL_CODE	created in 3.6.0	VARCHAR2	256	Y	A-number dial code



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
STA_CUBE_MANAGER_D AY	CALLING_LATA	created in 3.6.0	NUMBER	22	Y	A-side LATA
STA_CUBE_MANAGER_D AY	CALLING_OCN	created in 3.6.0	VARCHAR2	4	Y	A-side OCN
STA_CUBE_MANAGER_D AY	CALLING_STATE	created in 3.6.0	VARCHAR2	2	Y	A-side State
STA_CUBE_MANAGER_D AY	CALL_TYPE	created in 3.6.0	NUMBER	22	Y	Call type
STA_CUBE_MANAGER_D AY	COUNT_ACCOUNTABL E	created in 3.6.0	NUMBER	22	Y	Count of total attempts accountable for PDD calculation
STA_CUBE_MANAGER_D AY	COUNT_OK	created in 3.6.0	NUMBER	22	Y	Successful calls
STA_CUBE_MANAGER_D AY	COUNT_RES	created in 3.6.0	NUMBER	22	Y	Attempts with successful code
STA_CUBE_MANAGER_D AY	COUNT_SHORT	created in 3.6.0	NUMBER	22	Y	Short calls



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
STA_CUBE_MANAGER_D AY	COUNT_TOTAL	created in 3.6.0	NUMBER	22	Y	Attempts count
STA_CUBE_MANAGER_D AY	COUNT_VERY_SHORT	created in 3.6.0	NUMBER	22	Y	Very short calls
STA_CUBE_MANAGER_D AY	DCHECK	created in 3.6.0	DATE	7	Y	Date
STA_CUBE_MANAGER_D AY	DST_DIAL_CODE	created in 3.6.0	VARCHAR2	256	Y	Vendor dial code from rates
STA_CUBE_MANAGER_D AY	DST_POI_ID	created in 3.6.0	NUMBER	22	Y	Vendor POI ID
STA_CUBE_MANAGER_D AY	DST_RATE_LIST	created in 3.6.0	VARCHAR2	64	Y	3 sample vendor rates
STA_CUBE_MANAGER_D AY	EXTRA	created in 3.6.0	VARCHAR2	128	Y	Extra field
STA_CUBE_MANAGER_D AY	EXTRA_CNT	created in 3.6.0	NUMBER	22	Y	CDR count with extra sign



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
STA_CUBE_MANAGER_D AY	GROUP_ID	created in 3.6.0	NUMBER	22	Y	Aggregation group ID
STA_CUBE_MANAGER_D AY	HOST	created in 3.6.0	VARCHAR2	256	Y	Softswitch
STA_CUBE_MANAGER_D AY	MANAGER_ID	created in 3.6.0	NUMBER	22	Y	Manager ID
STA_CUBE_MANAGER_D AY	MAX_PDD	created in 3.6.0	NUMBER	22	Y	Maximum PDD
STA_CUBE_MANAGER_D AY	MIN_PDD	created in 3.6.0	NUMBER	22	Y	Minimum PDD
STA_CUBE_MANAGER_D AY	RULE_ID	created in 3.6.0	NUMBER	22	Y	Routing rule ID
STA_CUBE_MANAGER_D AY	SRC_DIAL_CODE	created in 3.6.0	VARCHAR2	256	Y	Client dial code from rates
STA_CUBE_MANAGER_D AY	SRC_POI_ID	created in 3.6.0	NUMBER	22	Y	Client POI ID



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
STA_CUBE_MANAGER_D AY	SRC_RATE_LIST	created in 3.6.0	VARCHAR2	64	Y	3 sample client rates
STA_CUBE_MANAGER_D AY	SUM_DST_CHARGE	created in 3.6.0	NUMBER	22	Y	Vendor charge
STA_CUBE_MANAGER_D AY	SUM_DST_CONN_FEE	created in 3.6.0	NUMBER	22	Y	Sum of vendor connection fees
STA_CUBE_MANAGER_D AY	SUM_DST_DURATION	created in 3.6.0	NUMBER	22	Y	Vendor duration, sec
STA_CUBE_MANAGER_D AY	SUM_DST_RAW_DURA TION	created in 3.6.0	NUMBER	22	Y	Total vendor raw duration (in seconds)
STA_CUBE_MANAGER_D AY	SUM_DURATION	created in 3.6.0	NUMBER	22	Y	Raw duration, sec
STA_CUBE_MANAGER_D AY	SUM_MARGIN	created in 3.6.0	NUMBER	22	Y	Margin
STA_CUBE_MANAGER_D AY	SUM_SRC_CHARGE	created in 3.6.0	NUMBER	22	Y	Client charge



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
STA_CUBE_MANAGER_D AY	SUM_SRC_CONN_FEE	created in 3.6.0	NUMBER	22	Y	Total client connection fee
STA_CUBE_MANAGER_D AY	SUM_SRC_DURATION	created in 3.6.0	NUMBER	22	Y	Client duration, sec
STA_CUBE_MANAGER_D AY	SUM_SRC_RAW_DURA TION	created in 3.6.0	NUMBER	22	Y	Total client raw duration (in seconds)
STA_CUBE_MANAGER_D AY	SWAP	created in 3.6.0	NUMBER	22	Y	Swap deals flag
STA_CUBE_MANAGER_H OUR	-- Table --	created in 3.6.0				Manager voice analytic hourly cube
STA_CUBE_MANAGER_H OUR	AVG_PDD	created in 3.6.0	NUMBER	22	Y	Average PDD
STA_CUBE_MANAGER_H OUR	CALLED_LATA	created in 3.6.0	NUMBER	22	Y	B-side LATA
STA_CUBE_MANAGER_H OUR	CALLED_OCN	created in 3.6.0	VARCHAR2	4	Y	B-side OCN



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
STA_CUBE_MANAGER_HOUR	CALLED_STATE	created in 3.6.0	VARCHAR2	2	Y	B-side State
STA_CUBE_MANAGER_HOUR	CALLING_DIAL_CODE	created in 3.6.0	VARCHAR2	256	Y	A-number dial code
STA_CUBE_MANAGER_HOUR	CALLING_LATA	created in 3.6.0	NUMBER	22	Y	A-side LATA
STA_CUBE_MANAGER_HOUR	CALLING_OCN	created in 3.6.0	VARCHAR2	4	Y	A-side OCN
STA_CUBE_MANAGER_HOUR	CALLING_STATE	created in 3.6.0	VARCHAR2	2	Y	A-side State
STA_CUBE_MANAGER_HOUR	CALL_TYPE	created in 3.6.0	NUMBER	22	Y	Call type
STA_CUBE_MANAGER_HOUR	COUNT_ACCOUNTABLE	created in 3.6.0	NUMBER	22	Y	Count of total attempts accountable for PDD calculation
STA_CUBE_MANAGER_HOUR	COUNT_OK	created in 3.6.0	NUMBER	22	Y	Successful calls



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
STA_CUBE_MANAGER_H OUR	COUNT_RES	created in 3.6.0	NUMBER	22	Y	Attempts with successful code
STA_CUBE_MANAGER_H OUR	COUNT_SHORT	created in 3.6.0	NUMBER	22	Y	Short calls
STA_CUBE_MANAGER_H OUR	COUNT_TOTAL	created in 3.6.0	NUMBER	22	Y	Attempts count
STA_CUBE_MANAGER_H OUR	COUNT_VERY_SHORT	created in 3.6.0	NUMBER	22	Y	Very short calls
STA_CUBE_MANAGER_H OUR	DCHECK	created in 3.6.0	DATE	7	Y	Date
STA_CUBE_MANAGER_H OUR	DST_DIAL_CODE	created in 3.6.0	VARCHAR2	256	Y	Vendor dial code from rates
STA_CUBE_MANAGER_H OUR	DST_POI_ID	created in 3.6.0	NUMBER	22	Y	Vendor POI ID
STA_CUBE_MANAGER_H OUR	DST_RATE_LIST	created in 3.6.0	VARCHAR2	64	Y	3 sample vendor rates



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
STA_CUBE_MANAGER_HOUR	EXTRA	created in 3.6.0	VARCHAR2	128	Y	Extra field
STA_CUBE_MANAGER_HOUR	EXTRA_CNT	created in 3.6.0	NUMBER	22	Y	CDR count with extra sign
STA_CUBE_MANAGER_HOUR	GROUP_ID	created in 3.6.0	NUMBER	22	Y	Aggregation group ID
STA_CUBE_MANAGER_HOUR	HOST	created in 3.6.0	VARCHAR2	256	Y	Softswitch
STA_CUBE_MANAGER_HOUR	MANAGER_ID	created in 3.6.0	NUMBER	22	Y	Manager ID
STA_CUBE_MANAGER_HOUR	MAX_PDD	created in 3.6.0	NUMBER	22	Y	Maximum PDD
STA_CUBE_MANAGER_HOUR	MIN_PDD	created in 3.6.0	NUMBER	22	Y	Minimum PDD
STA_CUBE_MANAGER_HOUR	RULE_ID	created in 3.6.0	NUMBER	22	Y	Routing rule ID



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
STA_CUBE_MANAGER_HOUR	SRC_DIAL_CODE	created in 3.6.0	VARCHAR2	256	Y	Client dial code from rates
STA_CUBE_MANAGER_HOUR	SRC_POI_ID	created in 3.6.0	NUMBER	22	Y	Client POI ID
STA_CUBE_MANAGER_HOUR	SRC_RATE_LIST	created in 3.6.0	VARCHAR2	64	Y	3 sample client rates
STA_CUBE_MANAGER_HOUR	SUM_DST_CHARGE	created in 3.6.0	NUMBER	22	Y	Vendor charge
STA_CUBE_MANAGER_HOUR	SUM_DST_CONN_FEE	created in 3.6.0	NUMBER	22	Y	Sum of vendor connection fees
STA_CUBE_MANAGER_HOUR	SUM_DST_DURATION	created in 3.6.0	NUMBER	22	Y	Vendor duration, sec
STA_CUBE_MANAGER_HOUR	SUM_DST_RAW_DURATION	created in 3.6.0	NUMBER	22	Y	Total vendor raw duration (in seconds)
STA_CUBE_MANAGER_HOUR	SUM_DURATION	created in 3.6.0	NUMBER	22	Y	Raw duration, sec



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
STA_CUBE_MANAGER_HOUR	SUM_MARGIN	created in 3.6.0	NUMBER	22	Y	Margin
STA_CUBE_MANAGER_HOUR	SUM_SRC_CHARGE	created in 3.6.0	NUMBER	22	Y	Client charge
STA_CUBE_MANAGER_HOUR	SUM_SRC_CONN_FEE	created in 3.6.0	NUMBER	22	Y	Total client connection fee
STA_CUBE_MANAGER_HOUR	SUM_SRC_DURATION	created in 3.6.0	NUMBER	22	Y	Client duration, sec
STA_CUBE_MANAGER_HOUR	SUM_SRC_RAW_DURATION	created in 3.6.0	NUMBER	22	Y	Total client raw duration (in seconds)
STA_CUBE_MANAGER_HOUR	SWAP	created in 3.6.0	NUMBER	22	Y	Swap deals flag
STA_CUBE_MANAGER_INFO_TMP	-- Table --	created in 3.6.0				Manager voice analytic temporary table
STA_CUBE_MANAGER_MIN	-- Table --	created in 3.6.0				Manager voice analytic minute cube



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
STA_CUBE_MANAGER_MIN	AVG_PDD	created in 3.6.0	NUMBER	22	Y	Average PDD
STA_CUBE_MANAGER_MIN	CALLED_LATA	created in 3.6.0	NUMBER	22	Y	B-side LATA
STA_CUBE_MANAGER_MIN	CALLED_OCN	created in 3.6.0	VARCHAR2	4	Y	B-side OCN
STA_CUBE_MANAGER_MIN	CALLED_STATE	created in 3.6.0	VARCHAR2	2	Y	B-side State
STA_CUBE_MANAGER_MIN	CALLING_DIAL_CODE	created in 3.6.0	VARCHAR2	256	Y	A-number dial code
STA_CUBE_MANAGER_MIN	CALLING_LATA	created in 3.6.0	NUMBER	22	Y	A-side LATA
STA_CUBE_MANAGER_MIN	CALLING_OCN	created in 3.6.0	VARCHAR2	4	Y	A-side OCN
STA_CUBE_MANAGER_MIN	CALLING_STATE	created in 3.6.0	VARCHAR2	2	Y	A-side State



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
STA_CUBE_MANAGER_MIN	CALL_TYPE	created in 3.6.0	NUMBER	22	Y	Call type
STA_CUBE_MANAGER_MIN	COUNT_ACCOUNTABLE	created in 3.6.0	NUMBER	22	Y	Count of total attempts accountable for PDD calculation
STA_CUBE_MANAGER_MIN	COUNT_OK	created in 3.6.0	NUMBER	22	Y	Successful calls
STA_CUBE_MANAGER_MIN	COUNT_RES	created in 3.6.0	NUMBER	22	Y	Attempts with successful code
STA_CUBE_MANAGER_MIN	COUNT_SHORT	created in 3.6.0	NUMBER	22	Y	Short calls
STA_CUBE_MANAGER_MIN	COUNT_TOTAL	created in 3.6.0	NUMBER	22	Y	Attempts count
STA_CUBE_MANAGER_MIN	COUNT_VERY_SHORT	created in 3.6.0	NUMBER	22	Y	Very short calls
STA_CUBE_MANAGER_MIN	DCHECK	created in 3.6.0	DATE	7	Y	Date



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
STA_CUBE_MANAGER_MIN	DST_DIAL_CODE	created in 3.6.0	VARCHAR2	256	Y	Vendor dial code from rates
STA_CUBE_MANAGER_MIN	DST_POI_ID	created in 3.6.0	NUMBER	22	Y	Vendor POI ID
STA_CUBE_MANAGER_MIN	DST_RATE_LIST	created in 3.6.0	VARCHAR2	64	Y	3 sample vendor rates
STA_CUBE_MANAGER_MIN	EXTRA	created in 3.6.0	VARCHAR2	128	Y	Extra field
STA_CUBE_MANAGER_MIN	EXTRA_CNT	created in 3.6.0	NUMBER	22	Y	CDR count with extra sign
STA_CUBE_MANAGER_MIN	GROUP_ID	created in 3.6.0	NUMBER	22	Y	Aggregation group ID
STA_CUBE_MANAGER_MIN	HOST	created in 3.6.0	VARCHAR2	256	Y	Softswitch
STA_CUBE_MANAGER_MIN	MANAGER_ID	created in 3.6.0	NUMBER	22	Y	Manager ID



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
STA_CUBE_MANAGER_MIN	MAX_PDD	created in 3.6.0	NUMBER	22	Y	Maximum PDD
STA_CUBE_MANAGER_MIN	MIN_PDD	created in 3.6.0	NUMBER	22	Y	Minimum PDD
STA_CUBE_MANAGER_MIN	RULE_ID	created in 3.6.0	NUMBER	22	Y	Routing rule ID
STA_CUBE_MANAGER_MIN	SRC_DIAL_CODE	created in 3.6.0	VARCHAR2	256	Y	Client dial code from rates
STA_CUBE_MANAGER_MIN	SRC_POI_ID	created in 3.6.0	NUMBER	22	Y	Client POI ID
STA_CUBE_MANAGER_MIN	SRC_RATE_LIST	created in 3.6.0	VARCHAR2	64	Y	3 sample client rates
STA_CUBE_MANAGER_MIN	SUM_DST_CHARGE	created in 3.6.0	NUMBER	22	Y	Vendor charge
STA_CUBE_MANAGER_MIN	SUM_DST_CONN_FEE	created in 3.6.0	NUMBER	22	Y	Sum of vendor connection fees



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
STA_CUBE_MANAGER_MIN	SUM_DST_DURATION	created in 3.6.0	NUMBER	22	Y	Vendor duration, sec
STA_CUBE_MANAGER_MIN	SUM_DST_RAW_DURATION	created in 3.6.0	NUMBER	22	Y	Total vendor raw duration (in seconds)
STA_CUBE_MANAGER_MIN	SUM_DURATION	created in 3.6.0	NUMBER	22	Y	Raw duration, sec
STA_CUBE_MANAGER_MIN	SUM_MARGIN	created in 3.6.0	NUMBER	22	Y	Margin
STA_CUBE_MANAGER_MIN	SUM_SRC_CHARGE	created in 3.6.0	NUMBER	22	Y	Client charge
STA_CUBE_MANAGER_MIN	SUM_SRC_CONN_FEE	created in 3.6.0	NUMBER	22	Y	Total client connection fee
STA_CUBE_MANAGER_MIN	SUM_SRC_DURATION	created in 3.6.0	NUMBER	22	Y	Client duration, sec
STA_CUBE_MANAGER_MIN	SUM_SRC_RAW_DURATION	created in 3.6.0	NUMBER	22	Y	Total client raw duration (in seconds)



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
STA_CUBE_MANAGER_MIN	SWAP	created in 3.6.0	NUMBER	22	Y	Swap deals flag
STA_CUBE_MANAGER_MONTH	-- Table --	created in 3.6.0				Manager voice analytic monthly cube
STA_CUBE_MANAGER_MONTH	AVG_PDD	created in 3.6.0	NUMBER	22	Y	Average PDD
STA_CUBE_MANAGER_MONTH	CALLED_LATA	created in 3.6.0	NUMBER	22	Y	B-side LATA
STA_CUBE_MANAGER_MONTH	CALLED_OCN	created in 3.6.0	VARCHAR2	4	Y	B-side OCN
STA_CUBE_MANAGER_MONTH	CALLED_STATE	created in 3.6.0	VARCHAR2	2	Y	B-side State
STA_CUBE_MANAGER_MONTH	CALLING_DIAL_CODE	created in 3.6.0	VARCHAR2	256	Y	A-number dial code
STA_CUBE_MANAGER_MONTH	CALLING_LATA	created in 3.6.0	NUMBER	22	Y	A-side LATA



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
STA_CUBE_MANAGER_MONTH	CALLING_OCN	created in 3.6.0	VARCHAR2	4	Y	A-side OCN
STA_CUBE_MANAGER_MONTH	CALLING_STATE	created in 3.6.0	VARCHAR2	2	Y	A-side State
STA_CUBE_MANAGER_MONTH	CALL_TYPE	created in 3.6.0	NUMBER	22	Y	Call type
STA_CUBE_MANAGER_MONTH	COUNT_ACCOUNTABLE	created in 3.6.0	NUMBER	22	Y	Count of total attempts accountable for PDD calculation
STA_CUBE_MANAGER_MONTH	COUNT_OK	created in 3.6.0	NUMBER	22	Y	Successful calls
STA_CUBE_MANAGER_MONTH	COUNT_RES	created in 3.6.0	NUMBER	22	Y	Attempts with successful code
STA_CUBE_MANAGER_MONTH	COUNT_SHORT	created in 3.6.0	NUMBER	22	Y	Short calls
STA_CUBE_MANAGER_MONTH	COUNT_TOTAL	created in 3.6.0	NUMBER	22	Y	Attempts count



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
STA_CUBE_MANAGER_MONTH	COUNT_VERY_SHORT	created in 3.6.0	NUMBER	22	Y	Very short calls
STA_CUBE_MANAGER_MONTH	DCHECK	created in 3.6.0	DATE	7	Y	Date
STA_CUBE_MANAGER_MONTH	DST_DIAL_CODE	created in 3.6.0	VARCHAR2	256	Y	Vendor dial code from rates
STA_CUBE_MANAGER_MONTH	DST_POI_ID	created in 3.6.0	NUMBER	22	Y	Vendor POI ID
STA_CUBE_MANAGER_MONTH	DST_RATE_LIST	created in 3.6.0	VARCHAR2	64	Y	3 sample vendor rates
STA_CUBE_MANAGER_MONTH	EXTRA	created in 3.6.0	VARCHAR2	128	Y	Extra field
STA_CUBE_MANAGER_MONTH	EXTRA_CNT	created in 3.6.0	NUMBER	22	Y	CDR count with extra sign
STA_CUBE_MANAGER_MONTH	GROUP_ID	created in 3.6.0	NUMBER	22	Y	Aggregation group ID



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
STA_CUBE_MANAGER_MONTH	HOST	created in 3.6.0	VARCHAR2	256	Y	Softswitch
STA_CUBE_MANAGER_MONTH	MANAGER_ID	created in 3.6.0	NUMBER	22	Y	Manager ID
STA_CUBE_MANAGER_MONTH	MAX_PDD	created in 3.6.0	NUMBER	22	Y	Maximum PDD
STA_CUBE_MANAGER_MONTH	MIN_PDD	created in 3.6.0	NUMBER	22	Y	Minimum PDD
STA_CUBE_MANAGER_MONTH	RULE_ID	created in 3.6.0	NUMBER	22	Y	Routing rule ID
STA_CUBE_MANAGER_MONTH	SRC_DIAL_CODE	created in 3.6.0	VARCHAR2	256	Y	Client dial code from rates
STA_CUBE_MANAGER_MONTH	SRC_POI_ID	created in 3.6.0	NUMBER	22	Y	Client POI ID
STA_CUBE_MANAGER_MONTH	SRC_RATE_LIST	created in 3.6.0	VARCHAR2	64	Y	3 sample client rates



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
STA_CUBE_MANAGER_MONTH	SUM_DST_CHARGE	created in 3.6.0	NUMBER	22	Y	Vendor charge
STA_CUBE_MANAGER_MONTH	SUM_DST_CONN_FEE	created in 3.6.0	NUMBER	22	Y	Sum of vendor connection fees
STA_CUBE_MANAGER_MONTH	SUM_DST_DURATION	created in 3.6.0	NUMBER	22	Y	Vendor duration, sec
STA_CUBE_MANAGER_MONTH	SUM_DST_RAW_DURATION	created in 3.6.0	NUMBER	22	Y	Total vendor raw duration (in seconds)
STA_CUBE_MANAGER_MONTH	SUM_DURATION	created in 3.6.0	NUMBER	22	Y	Raw duration, sec
STA_CUBE_MANAGER_MONTH	SUM_MARGIN	created in 3.6.0	NUMBER	22	Y	Margin
STA_CUBE_MANAGER_MONTH	SUM_SRC_CHARGE	created in 3.6.0	NUMBER	22	Y	Client charge
STA_CUBE_MANAGER_MONTH	SUM_SRC_CONN_FEE	created in 3.6.0	NUMBER	22	Y	Total client connection fee



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
STA_CUBE_MANAGER_MONTH	SUM_SRC_DURATION	created in 3.6.0	NUMBER	22	Y	Client duration, sec
STA_CUBE_MANAGER_MONTH	SUM_SRC_RAW_DURATION	created in 3.6.0	NUMBER	22	Y	Total client raw duration (in seconds)
STA_CUBE_MANAGER_MONTH	SWAP	created in 3.6.0	NUMBER	22	Y	Swap deals flag
STA_CUBE_MANAGER_WEEK	-- Table --	created in 3.6.0				Manager voice analytic weekly cube
STA_CUBE_MANAGER_WEEK	AVG_PDD	created in 3.6.0	NUMBER	22	Y	Average PDD
STA_CUBE_MANAGER_WEEK	CALLED_LATA	created in 3.6.0	NUMBER	22	Y	B-side LATA
STA_CUBE_MANAGER_WEEK	CALLED_OCN	created in 3.6.0	VARCHAR2	4	Y	B-side OCN
STA_CUBE_MANAGER_WEEK	CALLED_STATE	created in 3.6.0	VARCHAR2	2	Y	B-side State



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
STA_CUBE_MANAGER_WEEK	CALLING_DIAL_CODE	created in 3.6.0	VARCHAR2	256	Y	A-number dial code
STA_CUBE_MANAGER_WEEK	CALLING_LATA	created in 3.6.0	NUMBER	22	Y	A-side LATA
STA_CUBE_MANAGER_WEEK	CALLING_OCN	created in 3.6.0	VARCHAR2	4	Y	A-side OCN
STA_CUBE_MANAGER_WEEK	CALLING_STATE	created in 3.6.0	VARCHAR2	2	Y	A-side State
STA_CUBE_MANAGER_WEEK	CALL_TYPE	created in 3.6.0	NUMBER	22	Y	Call type
STA_CUBE_MANAGER_WEEK	COUNT_ACCOUNTABLE	created in 3.6.0	NUMBER	22	Y	Count of total attempts accountable for PDD calculation
STA_CUBE_MANAGER_WEEK	COUNT_OK	created in 3.6.0	NUMBER	22	Y	Successful calls
STA_CUBE_MANAGER_WEEK	COUNT_RES	created in 3.6.0	NUMBER	22	Y	Attempts with successful code



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
STA_CUBE_MANAGER_WEEK	COUNT_SHORT	created in 3.6.0	NUMBER	22	Y	Short calls
STA_CUBE_MANAGER_WEEK	COUNT_TOTAL	created in 3.6.0	NUMBER	22	Y	Attempts count
STA_CUBE_MANAGER_WEEK	COUNT_VERY_SHORT	created in 3.6.0	NUMBER	22	Y	Very short calls
STA_CUBE_MANAGER_WEEK	DCHECK	created in 3.6.0	DATE	7	Y	Date
STA_CUBE_MANAGER_WEEK	DST_DIAL_CODE	created in 3.6.0	VARCHAR2	256	Y	Vendor dial code from rates
STA_CUBE_MANAGER_WEEK	DST_POI_ID	created in 3.6.0	NUMBER	22	Y	Vendor POI ID
STA_CUBE_MANAGER_WEEK	DST_RATE_LIST	created in 3.6.0	VARCHAR2	64	Y	3 sample vendor rates
STA_CUBE_MANAGER_WEEK	EXTRA	created in 3.6.0	VARCHAR2	128	Y	Extra field



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
STA_CUBE_MANAGER_WEEK	EXTRA_CNT	created in 3.6.0	NUMBER	22	Y	CDR count with extra sign
STA_CUBE_MANAGER_WEEK	GROUP_ID	created in 3.6.0	NUMBER	22	Y	Aggregation group ID
STA_CUBE_MANAGER_WEEK	HOST	created in 3.6.0	VARCHAR2	256	Y	Softswitch
STA_CUBE_MANAGER_WEEK	MANAGER_ID	created in 3.6.0	NUMBER	22	Y	Manager ID
STA_CUBE_MANAGER_WEEK	MAX_PDD	created in 3.6.0	NUMBER	22	Y	Maximum PDD
STA_CUBE_MANAGER_WEEK	MIN_PDD	created in 3.6.0	NUMBER	22	Y	Minimum PDD
STA_CUBE_MANAGER_WEEK	RULE_ID	created in 3.6.0	NUMBER	22	Y	Routing rule ID
STA_CUBE_MANAGER_WEEK	SRC_DIAL_CODE	created in 3.6.0	VARCHAR2	256	Y	Client dial code from rates



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
STA_CUBE_MANAGER_WEEK	SRC_POI_ID	created in 3.6.0	NUMBER	22	Y	Client POI ID
STA_CUBE_MANAGER_WEEK	SRC_RATE_LIST	created in 3.6.0	VARCHAR2	64	Y	3 sample client rates
STA_CUBE_MANAGER_WEEK	SUM_DST_CHARGE	created in 3.6.0	NUMBER	22	Y	Vendor charge
STA_CUBE_MANAGER_WEEK	SUM_DST_CONN_FEE	created in 3.6.0	NUMBER	22	Y	Sum of vendor connection fees
STA_CUBE_MANAGER_WEEK	SUM_DST_DURATION	created in 3.6.0	NUMBER	22	Y	Vendor duration, sec
STA_CUBE_MANAGER_WEEK	SUM_DST_RAW_DURATION	created in 3.6.0	NUMBER	22	Y	Total vendor raw duration (in seconds)
STA_CUBE_MANAGER_WEEK	SUM_DURATION	created in 3.6.0	NUMBER	22	Y	Raw duration, sec
STA_CUBE_MANAGER_WEEK	SUM_MARGIN	created in 3.6.0	NUMBER	22	Y	Margin



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
STA_CUBE_MANAGER_WEEK	SUM_SRC_CHARGE	created in 3.6.0	NUMBER	22	Y	Client charge
STA_CUBE_MANAGER_WEEK	SUM_SRC_CONN_FEE	created in 3.6.0	NUMBER	22	Y	Total client connection fee
STA_CUBE_MANAGER_WEEK	SUM_SRC_DURATION	created in 3.6.0	NUMBER	22	Y	Client duration, sec
STA_CUBE_MANAGER_WEEK	SUM_SRC_RAW_DURATION	created in 3.6.0	NUMBER	22	Y	Total client raw duration (in seconds)
STA_CUBE_MANAGER_WEEK	SWAP	created in 3.6.0	NUMBER	22	Y	Swap deals flag
STA_CUBE_MANAGER_YEAR	-- Table --	created in 3.6.0				Manager voice analytic yearly cube
STA_CUBE_MIN	AVG_PDD	created in 3.6.0	NUMBER	22	Y	Average PDD
STA_CUBE_MIN	CALLED_LATA	created in 3.6.0	NUMBER	22	Y	B-side LATA Flag: 1 - present in aggregation, 0 not



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
STA_CUBE_MIN	CALLED_OCN	created in 3.6.0	VARCHAR2	4	Y	B-side OCN Flag: 1 - present in aggregation, 0 not
STA_CUBE_MIN	CALLED_STATE	created in 3.6.0	VARCHAR2	2	Y	Flag: 1 - B-side Start present in aggregation, 0 - not
STA_CUBE_MIN	CALLING_DIAL_CODE	created in 3.6.0	VARCHAR2	256	Y	A-number dial code
STA_CUBE_MIN	CALLING_LATA	created in 3.6.0	NUMBER	22	Y	A-side LATA Flag: 1 - present in aggregation, 0 not
STA_CUBE_MIN	CALLING_OCN	created in 3.6.0	VARCHAR2	4	Y	Flag: 1 - A-side OCN present in aggregation, 0 not
STA_CUBE_MIN	CALLING_STATE	created in 3.6.0	VARCHAR2	2	Y	A-side State Flag: 1 - present in aggregation, 0 not



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
STA_CUBE_MIN	CALL_TYPE	created in 3.6.0	NUMBER	22	Y	Call type
STA_CUBE_MIN	COUNT_OK	created in 3.6.0	NUMBER	22	Y	Total successful attempts
STA_CUBE_MIN	COUNT_RES	created in 3.6.0	NUMBER	22	Y	Successful attempts count
STA_CUBE_MIN	COUNT_SHORT	created in 3.6.0	NUMBER	22	Y	Short calls count
STA_CUBE_MIN	COUNT_TOTAL	created in 3.6.0	NUMBER	22	Y	Total count
STA_CUBE_MIN	COUNT_VERY_SHORT	created in 3.6.0	NUMBER	22	Y	Very short calls count
STA_CUBE_MIN	DCHECK	created in 3.6.0	DATE	7	Y	Date Last updated day check date of charging Cube
STA_CUBE_MIN	DST_DIAL_CODE	created in 3.6.0	VARCHAR2	256	Y	Vendor dial code
STA_CUBE_MIN	DST_POI_ID	created in 3.6.0	NUMBER	22	Y	Vendor POI ID
STA_CUBE_MIN	DST_RATE_LIST	created in 3.6.0	VARCHAR2	64	Y	3 sample vendor rates Vendor rate list



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
STA_CUBE_MIN	EXTRA_CNT	created in 3.6.0	NUMBER	22	Y	CDR count with extra sign
STA_CUBE_MIN	GROUP_ID	created in 3.6.0	NUMBER	22	Y	Group ID
STA_CUBE_MIN	HOST	created in 3.6.0	VARCHAR2	256	Y	Softswitch Flag: 1 - present in aggregation, 0 not
STA_CUBE_MIN	MAX_PDD	created in 3.6.0	NUMBER	22	Y	Maximum PDD
STA_CUBE_MIN	MIN_PDD	created in 3.6.0	NUMBER	22	Y	Minimum PDD
STA_CUBE_MIN	SRC_DIAL_CODE	created in 3.6.0	VARCHAR2	256	Y	Client dial code
STA_CUBE_MIN	SRC_POI_ID	created in 3.6.0	NUMBER	22	Y	Client POI ID
STA_CUBE_MIN	SRC_RATE_LIST	created in 3.6.0	VARCHAR2	64	Y	3 sample client rates Client rate list
STA_CUBE_MIN	SUM_DST_CHARGE	created in 3.6.0	NUMBER	22	Y	Total vendor cost in currency 1 Vendor charge



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
STA_CUBE_MIN	SUM_DST_CONN_FEE	created in 3.6.0	NUMBER	22	Y	Sum of vendor connection fees
STA_CUBE_MIN	SUM_DST_DURATION	created in 3.6.0	NUMBER	22	Y	Vendor duration, sec
STA_CUBE_MIN	SUM_DURATION	created in 3.6.0	NUMBER	22	Y	Raw duration, sec
STA_CUBE_MIN	SUM_MARGIN	created in 3.6.0	NUMBER	22	Y	Margin Total margin in currency 1
STA_CUBE_MIN	SUM_SRC_CHARGE	created in 3.6.0	NUMBER	22	Y	Client charge Total client revenue in currency 1
STA_CUBE_MIN	SUM_SRC_DURATION	created in 3.6.0	NUMBER	22	Y	Client duration, sec
STA_CUBE_MONTH	AVG_PDD	created in 3.6.0	NUMBER	22	Y	Average PDD
STA_CUBE_MONTH	CALLED_LATA	created in 3.6.0	NUMBER	22	Y	B-side LATA Flag: 1 - present in aggregation, 0 not



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
STA_CUBE_MONTH	CALLED_OCN	created in 3.6.0	VARCHAR2	4	Y	B-side OCN Flag: 1 - present in aggregation, 0 not
STA_CUBE_MONTH	CALLED_STATE	created in 3.6.0	VARCHAR2	2	Y	Flag: 1 - B-side Start present in aggregation, 0 - not
STA_CUBE_MONTH	CALLING_DIAL_CODE	created in 3.6.0	VARCHAR2	256	Y	A-number dial code
STA_CUBE_MONTH	CALLING_LATA	created in 3.6.0	NUMBER	22	Y	A-side LATA Flag: 1 - present in aggregation, 0 not
STA_CUBE_MONTH	CALLING_OCN	created in 3.6.0	VARCHAR2	4	Y	Flag: 1 - A-side OCN present in aggregation, 0 not
STA_CUBE_MONTH	CALLING_STATE	created in 3.6.0	VARCHAR2	2	Y	A-side State Flag: 1 - present in aggregation, 0 not



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
STA_CUBE_MONTH	CALL_TYPE	created in 3.6.0	NUMBER	22	Y	Call type
STA_CUBE_MONTH	COUNT_ACCOUNTABLE	created in 3.6.0	NUMBER	22	Y	Count of total attempts accountable for PDD calculation
STA_CUBE_MONTH	COUNT_OK	created in 3.6.0	NUMBER	22	Y	Total successful attempts
STA_CUBE_MONTH	COUNT_RES	created in 3.6.0	NUMBER	22	Y	Successful attempts count
STA_CUBE_MONTH	COUNT_SHORT	created in 3.6.0	NUMBER	22	Y	Short calls count
STA_CUBE_MONTH	COUNT_TOTAL	created in 3.6.0	NUMBER	22	Y	Total count
STA_CUBE_MONTH	COUNT_VERY_SHORT	created in 3.6.0	NUMBER	22	Y	Very short calls count
STA_CUBE_MONTH	DCHECK	created in 3.6.0	DATE	7	Y	Date Last updated day check date of charging Cube
STA_CUBE_MONTH	DST_DIAL_CODE	created in 3.6.0	VARCHAR2	256	Y	Vendor dial code



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
STA_CUBE_MONTH	DST_POI_ID	created in 3.6.0	NUMBER	22	Y	Vendor POI ID
STA_CUBE_MONTH	DST_RATE_LIST	created in 3.6.0	VARCHAR2	64	Y	3 sample vendor rates Vendor rate list
STA_CUBE_MONTH	EXTRA	created in 3.6.0	VARCHAR2	128	Y	Extra field
STA_CUBE_MONTH	EXTRA_CNT	created in 3.6.0	NUMBER	22	Y	CDR count with extra sign
STA_CUBE_MONTH	GROUP_ID	created in 3.6.0	NUMBER	22	Y	Group ID
STA_CUBE_MONTH	HOST	created in 3.6.0	VARCHAR2	256	Y	Softswitch Flag: 1 - present in aggregation, 0 not
STA_CUBE_MONTH	MAX_PDD	created in 3.6.0	NUMBER	22	Y	Maximum PDD
STA_CUBE_MONTH	MIN_PDD	created in 3.6.0	NUMBER	22	Y	Minimum PDD
STA_CUBE_MONTH	RULE_ID	created in 3.6.0	NUMBER	22	Y	Routing rule ID
STA_CUBE_MONTH	SRC_DIAL_CODE	created in 3.6.0	VARCHAR2	256	Y	Client dial code



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
STA_CUBE_MONTH	SRC_POI_ID	created in 3.6.0	NUMBER	22	Y	Client POI ID
STA_CUBE_MONTH	SRC_RATE_LIST	created in 3.6.0	VARCHAR2	64	Y	3 sample client rates Client rate list
STA_CUBE_MONTH	SUM_DST_CHARGE	created in 3.6.0	NUMBER	22	Y	Total vendor cost in currency 1 Vendor charge
STA_CUBE_MONTH	SUM_DST_CONN_FEE	created in 3.6.0	NUMBER	22	Y	Sum of vendor connection fees
STA_CUBE_MONTH	SUM_DST_DURATION	created in 3.6.0	NUMBER	22	Y	Vendor duration, sec
STA_CUBE_MONTH	SUM_DST_RAW_DURATION	created in 3.6.0	NUMBER	22	Y	Total vendor raw duration (in seconds)
STA_CUBE_MONTH	SUM_DURATION	created in 3.6.0	NUMBER	22	Y	Raw duration, sec
STA_CUBE_MONTH	SUM_MARGIN	created in 3.6.0	NUMBER	22	Y	Margin Total margin in currency 1
STA_CUBE_MONTH	SUM_SRC_CHARGE	created in 3.6.0	NUMBER	22	Y	Client charge Total client revenue in currency 1



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
STA_CUBE_MONTH	SUM_SRC_CONN_FEE	created in 3.6.0	NUMBER	22	Y	Total client connection fee
STA_CUBE_MONTH	SUM_SRC_DURATION	created in 3.6.0	NUMBER	22	Y	Client duration, sec
STA_CUBE_MONTH	SUM_SRC_RAW_DURATION	created in 3.6.0	NUMBER	22	Y	Total client raw duration (in seconds)
STA_CUBE_MONTH	SWAP	created in 3.6.0	NUMBER	22	Y	Swap deals flag
STA_CUBE_REPORT_TMP	-- Table --	created in 3.6.0				Temporary table for voice analytic
STA_CUBE_STATS_PARAMS	-- Table --	created in 3.6.0				Voice analytic internal table
STA_CUBE_STATS_PARAMS	CUBE_STATS_ID	created in 3.6.0	RAW	32	N	ID
STA_CUBE_STATS_PARAMS	PARAM_NAME	created in 3.6.0	VARCHAR2	4000	Y	Parameter name
STA_CUBE_STATS_PARAMS	PARAM_VALUE	created in 3.6.0	VARCHAR2	4000	Y	Parameter value



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
STA_CUBE_WEEK	CALLED_LATA	changed in 3.6.0	NUMBER	22	Y	B-side LATA
STA_CUBE_WEEK	CALLED_OCN	changed in 3.6.0	VARCHAR2	4	Y	B-side OCN
STA_CUBE_WEEK	CALLED_STATE	changed in 3.6.0	VARCHAR2	2	Y	B-side State
STA_CUBE_WEEK	CALLING_LATA	changed in 3.6.0	NUMBER	22	Y	A-side LATA
STA_CUBE_WEEK	CALLING_OCN	changed in 3.6.0	VARCHAR2	4	Y	A-side OCN
STA_CUBE_WEEK	CALLING_STATE	changed in 3.6.0	VARCHAR2	2	Y	A-side State
STA_CUBE_WEEK	CALL_TYPE	created in 3.6.0	NUMBER	22	Y	Call type
STA_CUBE_WEEK	COUNT_OK	changed in 3.6.0	NUMBER	22	Y	Successful calls
STA_CUBE_WEEK	COUNT_RES	changed in 3.6.0	NUMBER	22	Y	Attempts with successful code
STA_CUBE_WEEK	COUNT_SHORT	changed in 3.6.0	NUMBER	22	Y	Short calls
STA_CUBE_WEEK	COUNT_TOTAL	changed in 3.6.0	NUMBER	22	Y	Attempts count



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
STA_CUBE_WEEK	COUNT_VERY_SHORT	changed in 3.6.0	NUMBER	22	Y	Very short calls
STA_CUBE_WEEK	DCHECK	changed in 3.6.0	DATE	7	Y	Date
STA_CUBE_WEEK	DST_DIAL_CODE	changed in 3.6.0	VARCHAR2	256	Y	Vendor dial code from rates
STA_CUBE_WEEK	DST_RATE_LIST	changed in 3.6.0	VARCHAR2	64	Y	3 sample vendor rates
STA_CUBE_WEEK	GROUP_ID	changed in 3.6.0	NUMBER	22	Y	Aggregation group ID
STA_CUBE_WEEK	HOST	changed in 3.6.0	VARCHAR2	256	Y	Softswitch
STA_CUBE_WEEK	SRC_DIAL_CODE	changed in 3.6.0	VARCHAR2	256	Y	Client dial code from rates
STA_CUBE_WEEK	SRC_RATE_LIST	changed in 3.6.0	VARCHAR2	64	Y	3 sample client rates
STA_CUBE_WEEK	SUM_DST_CHARGE	changed in 3.6.0	NUMBER	22	Y	Vendor charge
STA_CUBE_WEEK	SUM_DST_CONN_FEE	created in 3.6.0	NUMBER	22	Y	Sum of vendor connection fees



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
STA_CUBE_WEEK	SUM_MARGIN	changed in 3.6.0	NUMBER	22	Y	Margin
STA_CUBE_WEEK	SUM_SRC_CHARGE	changed in 3.6.0	NUMBER	22	Y	Client charge
STA_EXP_DATA	CDR_DST_ANI_DIAL_CODE	created in 3.6.0	VARCHAR2	16	Y	Vendor origin dial code
STA_EXP_DATA	CDR_DST_DESTINATION	created in 3.6.0	VARCHAR2	2000	Y	Cdr vendor destination
STA_EXP_DATA	CDR_LIM_RULE_ID	created in 3.6.0	NUMBER	22	Y	Limitation rule ID,
STA_EXP_DATA	CDR_SRC_ANI_DIAL_CODE	created in 3.6.0	VARCHAR2	16	Y	Client origin dial code
STA_EXP_DATA	CDR_SRC_DESTINATION	created in 3.6.0	VARCHAR2	2000	Y	Cdr client destination
STA_EXP_DATA	CDR_TEN_DIGIT_US	created in 3.6.0	NUMBER	22	Y	Treat 10-digit A-number as US (for DID only now)
STA_FIN_DETAIL	CONN_FEE3	changed in 3.6.0	NUMBER	22	Y	Connection fee in currency 3



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
STA_FIN_DETAIL_DAY	CONN_FEE3	changed in 3.6.0	NUMBER	22	Y	Connection fee in currency 3
STA_PART_STATE	AUX	created in 3.6.0	NUMBER	22	Y	Aux
STA_PROD_DIAL_CODE_P AIRS_TMP	-- Table --	created in 3.6.0				Temporary table for voice reraiting
STA_PROD_DIAL_CODE_T MP	-- Table --	created in 3.6.0				Temporary table for voice reraiting
STA_RAW	CDR_CALL_TYPE	created in 3.6.0	NUMBER	22	Y	Cdr call type
STA_RAW	CDR_EXTRA_JSON	created in 3.6.0	VARCHAR2	4000	Y	Cdr extra json
STA_RAW	CDR_LIM_RULE_ID	created in 3.6.0	NUMBER	22	Y	Limitation rule ID
STA_RAW_ARCHIVE	-- Table --	changed in 3.6.0				Voice CDR archive
STA_RAW_ARCHIVE	CDR_CALL_TYPE	created in 3.6.0	NUMBER	22	Y	Cdr call type
STA_RAW_ARCHIVE	CDR_EXTRA_JSON	created in 3.6.0	VARCHAR2	4000	Y	Cdr extra json



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
STA_RAW_ARCHIVE	CDR_LIM_RULE_ID	created in 3.6.0	NUMBER	22	Y	Limitation rule ID
STA_RAW_ARCHIVE	CDR_TEN_DIGIT_US	created in 3.6.0	NUMBER	22	Y	Treat 10-digit A-number as US (for DID only now)
STA_RAW_ERROR_LOG	-- Table --	deleted in 3.6.0				DML Error Logging table for "STA_RAW"
STA_RAW_ERROR_LOG	CDR_ATTEMPT	deleted in 3.6.0	VARCHAR2	4000	Y	Attempt number
STA_RAW_ERROR_LOG	CDR_CALLED	deleted in 3.6.0	VARCHAR2	4000	Y	Client B number (e.164)
STA_RAW_ERROR_LOG	CDR_CALL_ID	deleted in 3.6.0	VARCHAR2	4000	Y	Call ID
STA_RAW_ERROR_LOG	CDR_CONF_ID	deleted in 3.6.0	VARCHAR2	4000	Y	Conference call id
STA_RAW_ERROR_LOG	CDR_CONNECT_TIME	deleted in 3.6.0	VARCHAR2	4000	Y	Connect time
STA_RAW_ERROR_LOG	CDR_CREATE_DATE	deleted in 3.6.0	VARCHAR2	4000	Y	CDR arrival date
STA_RAW_ERROR_LOG	CDR_DC	deleted in 3.6.0	VARCHAR2	4000	Y	Disconnect code (Q.931, SIP)



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
STA_RAW_ERROR_LOG	CDR_DIAL_CODE	deleted in 3.6.0	VARCHAR2	4000	Y	Destination dial code (from system reference book)
STA_RAW_ERROR_LOG	CDR_DISCONNECT_TIME	deleted in 3.6.0	VARCHAR2	4000	Y	Disconnect time
STA_RAW_ERROR_LOG	CDR_DST_BILL_INC_ID	deleted in 3.6.0	VARCHAR2	4000	Y	Vendor billing increment id
STA_RAW_ERROR_LOG	CDR_DST_BLOCK	deleted in 3.6.0	VARCHAR2	4000	Y	Called Block ID
STA_RAW_ERROR_LOG	CDR_DST_CALLED	deleted in 3.6.0	VARCHAR2	4000	Y	B number (vendor leg)
STA_RAW_ERROR_LOG	CDR_DST_CALLING	deleted in 3.6.0	VARCHAR2	4000	Y	A number (vendor leg)
STA_RAW_ERROR_LOG	CDR_DST_CONN_FEE	deleted in 3.6.0	VARCHAR2	4000	Y	Connection fee (vendor)
STA_RAW_ERROR_LOG	CDR_DST_COST	deleted in 3.6.0	VARCHAR2	4000	Y	Vendor cost
STA_RAW_ERROR_LOG	CDR_DST_CURRENCY_CODE	deleted in 3.6.0	VARCHAR2	4000	Y	Vendor currency code
STA_RAW_ERROR_LOG	CDR_DST_DIAL_CODE	deleted in 3.6.0	VARCHAR2	4000	Y	Vendor dial code



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
STA_RAW_ERROR_LOG	CDR_DST_DURATION	deleted in 3.6.0	VARCHAR2	4000	Y	Call duration (for vendor)
STA_RAW_ERROR_LOG	CDR_DST_E164_CALLED	deleted in 3.6.0	VARCHAR2	4000	Y	Vendor e.164 B-number
STA_RAW_ERROR_LOG	CDR_DST_IP	deleted in 3.6.0	VARCHAR2	4000	Y	Vendor IP address
STA_RAW_ERROR_LOG	CDR_DST_LATA	deleted in 3.6.0	VARCHAR2	4000	Y	Called LATA
STA_RAW_ERROR_LOG	CDR_DST_LRN	deleted in 3.6.0	VARCHAR2	4000	Y	Called LRN
STA_RAW_ERROR_LOG	CDR_DST_NPA	deleted in 3.6.0	VARCHAR2	4000	Y	Called NPA
STA_RAW_ERROR_LOG	CDR_DST_NXX	deleted in 3.6.0	VARCHAR2	4000	Y	Called NXX
STA_RAW_ERROR_LOG	CDR_DST_OCN	deleted in 3.6.0	VARCHAR2	4000	Y	Called OCN
STA_RAW_ERROR_LOG	CDR_DST_POI_ID	deleted in 3.6.0	VARCHAR2	4000	Y	Vendor POI id
STA_RAW_ERROR_LOG	CDR_DST_PRODUCT_ID	deleted in 3.6.0	VARCHAR2	4000	Y	Vendor product id



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
STA_RAW_ERROR_LOG	CDR_DST_RATE	deleted in 3.6.0	VARCHAR2	4000	Y	Vendor rate
STA_RAW_ERROR_LOG	CDR_DST_RATE_ID	deleted in 3.6.0	VARCHAR2	4000	Y	Vendor rate id
STA_RAW_ERROR_LOG	CDR_DST_RAW_DURATION	deleted in 3.6.0	VARCHAR2	4000	Y	Raw call duration (for vendor)
STA_RAW_ERROR_LOG	CDR_DST_STATE	deleted in 3.6.0	VARCHAR2	4000	Y	Called State
STA_RAW_ERROR_LOG	CDR_DST_SWITCH	deleted in 3.6.0	VARCHAR2	4000	Y	Outgoing switch host
STA_RAW_ERROR_LOG	CDR_DST_TRUNK_CODE	deleted in 3.6.0	VARCHAR2	4000	Y	Vendor trunk code
STA_RAW_ERROR_LOG	CDR_DURATION	deleted in 3.6.0	VARCHAR2	4000	Y	Call duration
STA_RAW_ERROR_LOG	CDR_EXTRA	deleted in 3.6.0	VARCHAR2	4000	Y	CDR extra field
STA_RAW_ERROR_LOG	CDR_FILE_IDX	deleted in 3.6.0	VARCHAR2	4000	Y	Source file index
STA_RAW_ERROR_LOG	CDR_HOST	deleted in 3.6.0	VARCHAR2	4000	Y	Switch host



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
STA_RAW_ERROR_LOG	CDR_ID	deleted in 3.6.0	VARCHAR2	4000	Y	CDR ID
STA_RAW_ERROR_LOG	CDR_IS_LAST	deleted in 3.6.0	VARCHAR2	4000	Y	CDR is last
STA_RAW_ERROR_LOG	CDR_LAST_REBILL_DATE	deleted in 3.6.0	VARCHAR2	4000	Y	Last rebill date
STA_RAW_ERROR_LOG	CDR_PDD	deleted in 3.6.0	VARCHAR2	4000	Y	PDD
STA_RAW_ERROR_LOG	CDR_RULE_ID	deleted in 3.6.0	VARCHAR2	4000	Y	Routing rule ID
STA_RAW_ERROR_LOG	CDR_SETUP_TIME	deleted in 3.6.0	VARCHAR2	4000	Y	Setup time
STA_RAW_ERROR_LOG	CDR_SRC_BILL_INC_ID	deleted in 3.6.0	VARCHAR2	4000	Y	Client billing increment id
STA_RAW_ERROR_LOG	CDR_SRC_BLOCK	deleted in 3.6.0	VARCHAR2	4000	Y	Calling Block ID
STA_RAW_ERROR_LOG	CDR_SRC_CALLED	deleted in 3.6.0	VARCHAR2	4000	Y	B number (client leg)
STA_RAW_ERROR_LOG	CDR_SRC_CALLING	deleted in 3.6.0	VARCHAR2	4000	Y	A number (client leg)
STA_RAW_ERROR_LOG	CDR_SRC_CONN_FEE	deleted in 3.6.0	VARCHAR2	4000	Y	Connection fee (client)



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
STA_RAW_ERROR_LOG	CDR_SRC_COST	deleted in 3.6.0	VARCHAR2	4000	Y	Client cost
STA_RAW_ERROR_LOG	CDR_SRC_CURRENCY_CODE	deleted in 3.6.0	VARCHAR2	4000	Y	Client currency code
STA_RAW_ERROR_LOG	CDR_SRC_DIAL_CODE	deleted in 3.6.0	VARCHAR2	4000	Y	Client dial code
STA_RAW_ERROR_LOG	CDR_SRC_DURATION	deleted in 3.6.0	VARCHAR2	4000	Y	Call duration (for client)
STA_RAW_ERROR_LOG	CDR_SRC_IP	deleted in 3.6.0	VARCHAR2	4000	Y	Client IP address
STA_RAW_ERROR_LOG	CDR_SRC_LATA	deleted in 3.6.0	VARCHAR2	4000	Y	Calling LATA
STA_RAW_ERROR_LOG	CDR_SRC_LRN	deleted in 3.6.0	VARCHAR2	4000	Y	Calling LRN
STA_RAW_ERROR_LOG	CDR_SRC_NPA	deleted in 3.6.0	VARCHAR2	4000	Y	Calling NPA
STA_RAW_ERROR_LOG	CDR_SRC_NXX	deleted in 3.6.0	VARCHAR2	4000	Y	Calling NXX
STA_RAW_ERROR_LOG	CDR_SRC_OCN	deleted in 3.6.0	VARCHAR2	4000	Y	Calling OCN
STA_RAW_ERROR_LOG	CDR_SRC_POI_ID	deleted in 3.6.0	VARCHAR2	4000	Y	Client POI id



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
STA_RAW_ERROR_LOG	CDR_SRC_PRODUCT_ID	deleted in 3.6.0	VARCHAR2	4000	Y	Client product id
STA_RAW_ERROR_LOG	CDR_SRC_RATE	deleted in 3.6.0	VARCHAR2	4000	Y	Client rate
STA_RAW_ERROR_LOG	CDR_SRC_RATE_ID	deleted in 3.6.0	VARCHAR2	4000	Y	Client rate id
STA_RAW_ERROR_LOG	CDR_SRC_RAW_DURATION	deleted in 3.6.0	VARCHAR2	4000	Y	Client raw duration
STA_RAW_ERROR_LOG	CDR_SRC_STATE	deleted in 3.6.0	VARCHAR2	4000	Y	Calling State
STA_RAW_ERROR_LOG	CDR_SRC_TRUNK_CODE	deleted in 3.6.0	VARCHAR2	4000	Y	Client trunk code
STA_RAW_ERROR_LOG	CDR_TIME	deleted in 3.6.0	VARCHAR2	4000	Y	Connect/disconnect time
STA_RAW_ERROR_LOG	ORA_ERR_MESG\$	deleted in 3.6.0	VARCHAR2	2000	Y	ORA error message
STA_RAW_ERROR_LOG	ORA_ERR_NUMBER\$	deleted in 3.6.0	NUMBER	22	Y	ORA error number
STA_RAW_ERROR_LOG	ORA_ERR_OPTYP\$	deleted in 3.6.0	VARCHAR2	2	Y	ORA error type



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
STA_RAW_ERROR_LOG	ORA_ERR_ROWID\$	deleted in 3.6.0	UROWID	4000	Y	ORA error rowid
STA_RAW_ERROR_LOG	ORA_ERR_TAG\$	deleted in 3.6.0	VARCHAR2	2000	Y	ORA error tag
STA_RERATE_STAT	JOB_NAME	created in 3.6.0	VARCHAR2	30	Y	Rerating job name (scheduled or completed)
SWAP_ALERT_THRESHOLD_TMP	-- Table --	created in 3.6.0				Swap deals 2.0 alert temporary table
SWAP_DEAL	RATING_ALERT	created in 3.6.0	VARCHAR2	1	Y	Change threshold alert flag (1 - on, 0 - off)
SWAP_GROUP_PERIOD	ALERTED_RATE_NO	created in 3.6.0	NUMBER	22	Y	Alerted threshold number
TRD_BLEND	BLEND_ASR_K	changed in 3.6.0	NUMBER	22	Y	ASR coefficient
TRD_SWAP	FORECAST_CALC_DAYS	created in 3.6.0	NUMBER	22	Y	Dys of average traffic value
VBD_DEAL	DEAL_BILL_INC_ID	changed in 3.6.0	NUMBER	22	N	Billing Increment ID
VPD_ACCOUNT	-- Table --	created in 3.6.0				VPD-access to account



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
VPD_ACCOUNT	ACCESS_MASK	created in 3.6.0	NUMBER	22	N	Access mask
VPD_ACCOUNT	ACC_ID	created in 3.6.0	NUMBER	22	N	Account ID account id
VPD_ACCOUNT	USER_ID	created in 3.6.0	NUMBER	22	N	User numeric ID (primary key) Manager User-creator
VPD_CARRIER	-- Table --	created in 3.6.0				VPD-access to carrier
VPD_CARRIER	ACCESS_MASK	created in 3.6.0	NUMBER	22	N	Access mask
VPD_CARRIER	CAR_ID	created in 3.6.0	NUMBER	22	N	Carrier ID Alert group carrier
VPD_CARRIER	USER_ID	created in 3.6.0	NUMBER	22	N	User numeric ID (primary key) Manager User-creator
VPD_CONTRACT_COMPANY	-- Table --	created in 3.6.0				VPD-access to contract company
VPD_CONTRACT_COMPANY	ACCESS_MASK	created in 3.6.0	NUMBER	22	N	Access mask



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
VPD_CONTRACT_COMPANY	CC_ID	created in 3.6.0	NUMBER	22	N	Contract company ID id contract
VPD_CONTRACT_COMPANY	USER_ID	created in 3.6.0	NUMBER	22	N	User numeric ID (primary key) Manager User-creator
VPD_OBJ_MAPPING	-- Table --	created in 3.6.0				VPD mapping
VPD_OBJ_MAPPING	OBJECT_NAME	created in 3.6.0	VARCHAR2	128	N	Object name
VPD_OBJ_MAPPING	ORIG_OBJECT	created in 3.6.0	VARCHAR2	128	N	Original object name
VPD_OBJ_MAPPING	ORIG_OBJECT_SCHEMA	created in 3.6.0	VARCHAR2	128	N	Original object schema
VPD_OBJ_MAPPING	ORIG_OBJECT_TYPE	created in 3.6.0	VARCHAR2	128	Y	Original object type
VPD_POI	-- Table --	created in 3.6.0				VPD-access to POI
VPD_POI	ACCESS_MASK	created in 3.6.0	NUMBER	22	N	Access mask



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
VPD_POI	POI_ID	created in 3.6.0	NUMBER	22	N	POI ID (primary key) ORA error rowid Client
VPD_POI	USER_ID	created in 3.6.0	NUMBER	22	N	User numeric ID (primary key) Manager User-creator
VPD_POLICIES	-- Table --	created in 3.6.0				VPD policies
VPD_POLICIES	CHK_OPTION	created in 3.6.0	VARCHAR2	3	N	Check option
VPD_POLICIES	DEL	created in 3.6.0	VARCHAR2	3	N	Delete flag
VPD_POLICIES	ENABLED	created in 3.6.0	VARCHAR2	3	N	Enabled/Disabled
VPD_POLICIES	INS	created in 3.6.0	VARCHAR2	3	N	Insert flag
VPD_POLICIES	OBJECT_NAME	created in 3.6.0	VARCHAR2	128	N	Object name
VPD_POLICIES	POLICY_FUNCTION	created in 3.6.0	VARCHAR2	128	N	Policy function
VPD_POLICIES	POLICY_NAME	created in 3.6.0	VARCHAR2	128	N	Policy name



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
VPD_POLICIES	SEC_RELEVANT_COLS	created in 3.6.0	VARCHAR2	4000	Y	Columns
VPD_POLICIES	SEL	created in 3.6.0	VARCHAR2	3	N	Select flag
VPD_POLICIES	STATUS	created in 3.6.0	VARCHAR2	1	N	Status
VPD_POLICIES	UPD	created in 3.6.0	VARCHAR2	3	N	Update flag
VPD_PRODUCT	-- Table --	created in 3.6.0				VPD-access to product
VPD_PRODUCT	ACCESS_MASK	created in 3.6.0	NUMBER	22	N	Access mask
VPD_PRODUCT	PRODUCT_ID	created in 3.6.0	NUMBER	22	N	Product ID
VPD_PRODUCT	USER_ID	created in 3.6.0	NUMBER	22	N	User numeric ID (primary key) Manager User-creator
VPD_SMS_POI	-- Table --	created in 3.6.0				VPD-access to SMS POI
VPD_SMS_POI	ACCESS_MASK	created in 3.6.0	NUMBER	22	N	Access mask



Database structure changes

Table	Column	Change	Data type	Data length	Nullable	Comments
VPD_SMS_POI	POI_ID	created in 3.6.0	NUMBER	22	N	POI ID (primary key) ORA error rowid Client
VPD_SMS_POI	USER_ID	created in 3.6.0	NUMBER	22	N	User numeric ID (primary key) Manager User-creator



REST API changes

5 REST API changes

Resource	Parameter	Change	Description	Auth required	Parameter descr.	Direction	Param. required	Param. type	Param. in	Order index	Validation json
GET:auth	ip	changed in 3.6.0	Authorization	1	Allowed IP (0.0.0.0/0 - requires trust all addresses)	0	0	string	query		
POST:black_list	tag_id	changed in 3.6.0	Add new record to black list	1	tag ID	0	0	integer	body		
PUT:param/{id}	id	deleted in 3.6.0	Update system parameter	1	Parameter ID	0	1	string	path		
PUT:param/{id}	rows_affected	deleted in 3.6.0	Update system parameter	1	Number of rows affected by the method	1	1	integer	body		
PUT:param/{id}	value	deleted in 3.6.0	Update system parameter	1	Parameter value	0	1	string	query		



REST API changes

Resource	Parameter	Change	Description	Auth required	Parameter descr.	Direction	Param. required	Param. type	Param. in	Order index	Validation json
POST:register_user	portal	created in 3.6.0	Register new user	0	portal	0	0	string	body		{ "type": "list", "values": ["partner"] }
GET:send_sms	dnis	deleted in 3.6.0	Send SMS	1	B-number	1	0	string	body		
GET:send_sms	message_text	created in 3.6.0	Send SMS	1	Message text	1	0	string	body		
GET:send_sms	segment_num	deleted in 3.6.0	Send SMS	1	Segment number (for splitted SMS)	1	0	integer	body		
POST:send_sms	dnis	deleted in 3.6.0	Send SMS	1	B-number	1	0	string	body		
POST:send_sms	message_text	created in 3.6.0	Send SMS	1	Message text	1	0	string	body		
POST:send_sms	segment_num	deleted in 3.6.0	Send SMS	1	Segment number (for splitted SMS)	1	0	integer	body		



REST API changes

Resource	Parameter	Change	Description	Auth required	Parameter descr.	Direction	Param. required	Param. type	Param. in	Order index	Validation json
GET:sms_campaign	keyword	deleted in 3.6.0	Get campaign list	1	Campaign keyword	1	0	string	body	20	
POST:sms_campaign	keyword	deleted in 3.6.0	Create new campaign	1	Campaign keyword	0	0	string	body		
GET:sms_campaign/{id}	keyword	deleted in 3.6.0	Get specific campaign	1	Campaign keyword	1	0	string	body		
PUT:sms_campaign/{id}	keyword	deleted in 3.6.0	Update sms campaign	1	Campaign keyword	0	0	string	body		
PUT:sms_channel/{id}	bind_status	deleted in 3.6.0	Update specific sms channel	1	Bind status	0	0	integer	body	20	{"type":"list", "values":[0,1,2]}



REST API changes

Resource	Parameter	Change	Description	Auth required	Parameter descr.	Direction	Param. required	Param. type	Param. in	Order index	Validation json
PUT:sms_channel/{id}	sigtran_smsc	deleted in 3.6.0	Update specific sms channel	1	Sigtran SMSC	0	0	integer	body	20	{"type":"list", "values":[0,1]}
DELETE:token/{id}	id	created in 3.6.0	Delete token	1	Token ID	0	1	integer	path		
DELETE:token/{id}	rows_affected	created in 3.6.0	Delete token	1	Number of rows affected by the method	1	1	integer	body		
POST:voice_poi	voip_poi_rtp_type	created in 3.6.0	Add new POI	1	RTP type	0	0	string	body		{"type":"list", "values":["1","2","0"]}
PUT:voice_poi/{id}	voip_poi_rtp_type	created in 3.6.0	Update POI	1	RTP type	0	0	string	body		{"type":"list", "values":["1","2","0"]}